


Description

The MVL-914SG , utilizes a new generation of solid state LED emitters which combine highly efficient InGaN material with SiC substrate .

The package is water clear type .

Package Dimensions



Features

- Ultra - brightness
- Low power consumption
- TTL compatible
- Reliable

NOTES:

- 1.Dimensions are in millimeter(inches).
- 2.Dimensions without tolerances are nominal.







Absolute Maximum Ratings

@ T_A=25°C

Parameter	Symbol	Maximum Rating	Unit
Power Dissipation	P _{ad}	150	mW
Continuous Forward Current	I _{af}	40	mA
Reverse Voltage	V _R	5	V
Operating Temperature Range	T _{opr}	-20°C to +80°C	
Storage Temperature Range	T _{stg}	-30°C to +100°C	
Solder temperature 1.6 mm from body for 5 seconds at 260°C			

Optical-Electrical Characteristics
The MVL-914SG , utilizes a new generation of
 $\text{@ } T_A=25^\circ\text{C}$

Parameter	Test Conditions	Symbol	Min .	Typ .	Max .	Unit .
Total Flux	$I_F=40\text{mA}$	I_V	250	580	-	mlm
Forward Voltage	$I_F=40\text{mA}$	V_F	-	4.0	4.5	V
Reverse Current	$V_R=5\text{V}$	I_R	-	-	10	μA
Wavelength	$I_F=20\text{mA}$	λ_p/λ_d	-	502/505	-	nm
Viewing Angle	$I_F=20\text{mA}$	$2\theta_{1/2}$	-	60	-	deg.

Typical Optical-Electrical Characteristic Curves

FIG.1 SPECTRAL DISTRIBUTION

**FIG.2 LUMINOUS INTENSITY VS.
AMBIENT TEMPERATURE**

**FIG.3 FORWARD CURRENT VS.
FORWARD VOLTAGE**

**FIG.4 RELATIVE RADIANT INTENSITY
VS. AMBIENT TEMPERATURE**

**FIG.5 RELATIVE RADIANT INTENSITY
VS. FORWARD CURRENT**

FIG.6 RADIATION DIAGRAM