

3.0 V OPERATION SILICON RF POWER LD-MOS FET FOR 460 MHz 0.6 W TRANSMISSION AMPLIFIERS

DESCRIPTION

The NE552R679A is an N-channel silicon power laterally diffused MOS FET specially designed as the transmission power amplifier for 3.0 V FRS (Family Radio Service). Dies are manufactured using our NEWMOS2 technology (our WSi gate lateral-diffusion MOS FET) and housed in a surface mount package. This device can deliver 28.0 dBm output power with 60% power added efficiency at 460 MHz under the 3.0 V supply voltage.

FEATURES

- High output power : $P_{out} = 28.0$ dBm TYP. ($V_{DS} = 3.0$ V, $I_{Dset} = 300$ mA, $f = 460$ MHz, $P_{in} = 15$ dBm)
- High power added efficiency : $\eta_{add} = 60\%$ TYP. ($V_{DS} = 3.0$ V, $I_{Dset} = 300$ mA, $f = 460$ MHz, $P_{in} = 15$ dBm)
- High linear gain : $G_L = 20$ dB TYP. ($V_{DS} = 3.0$ V, $I_{Dset} = 300$ mA, $f = 460$ MHz, $P_{in} = 5$ dBm)
- Surface mount package : $5.7 \times 5.7 \times 1.1$ mm MAX.
- Single supply : $V_{DS} = 2.8$ to 6.0 V

APPLICATIONS

- Family Radio Service : 3.0 V Handsets

ORDERING INFORMATION

Part Number	Package	Marking	Supplying Form
NE552R679A-T1	79A	AU	<ul style="list-style-type: none"> • 12 mm wide embossed taping • Gate pin face the perforation side of the tape • Qty 1 kpcs/reel
NE552R679A-T1A			<ul style="list-style-type: none"> • 12 mm wide embossed taping • Gate pin face the perforation side of the tape • Qty 5 kpcs/reel

Remark To order evaluation samples, contact your nearby sales office.

Part number for sample order: NE552R679A

Caution Please handle this device at static-free workstation, because this is an electrostatic sensitive device.

The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.
Not all devices/types available in every country. Please check with local NEC Compound Semiconductor Devices representative for availability and additional information.

ABSOLUTE MAXIMUM RATINGS (T_A = +25°C)

Parameter	Symbol	Ratings	Unit
Drain to Source Voltage	V _{DS}	8.0	V
Gate to Source Voltage	V _{GS}	5.0	V
Drain Current	I _{DS}	350	mA
Drain Current (Pulse Test)	I _{DS} ^{Note}	600	mA
Total Power Dissipation	P _t	10	W
Channel Temperature	T _{ch}	125	°C
Storage Temperature	T _{stg}	-55 to +125	°C

Note Duty Cycle 50%, T_{on} ≤ 1 s

RECOMMENDED OPERATING CONDITIONS

Parameter	Symbol	Test Conditions	MIN.	TYP.	MAX.	Unit
Drain to Source Voltage	V _{DS}		2.8	3.0	6.0	V
Gate to Source Voltage	V _{GS}		0	2.0	3.0	V
Drain Current	I _{DS}		–	300	500	mA
Input Power	P _{in}	f = 460 MHz, V _{DS} = 3.0 V	14	15	20	dBm

ELECTRICAL CHARACTERISTICS

(T_A = +25°C, Unless otherwise specified, using NEC standard test fixture)





Parameter	Symbol	Test Conditions	MIN.	TYP.	MAX.	Unit
Gate to Source Leak Current	I _{GSO}	V _{GS} = 5.0 V	–	–	100	nA
Saturated Drain Current (Zero Gate Voltage Drain Current)	I _{DSS}	V _{DS} = 8.0 V	–	–	100	nA
Gate Threshold Voltage	V _{th}	V _{DS} = 3.5 V, I _{DS} = 1 mA	1.0	1.4	1.9	V
Thermal Resistance	R _{th}	Channel to Case	–	–	10	°C/W
Transconductance	g _m	V _{DS} = 3.0 V, I _{DS} = 300 mA	–	0.6	–	S
Drain to Source Breakdown Voltage	BV _{DSS}	I _{DSS} = 10 μA	15	18	–	V
Output Power	P _{out}	f = 460 MHz, V _{DS} = 3.0 V,	26.0	28.0	–	dBm
Drain Current	I _D	P _{in} = 15 dBm,	–	320	–	mA
Power Added Efficiency	η _{add}	I _{Dset} = 300 mA (RF OFF) , Note1	55	60	–	%
Linear Gain ^{Note2}	G _L		–	20	–	dB

Note 1. DC performance is 100% testing. RF performance is testing several samples per wafer.

Wafer rejection criteria for standard devices is 1 reject for several samples.

2. P_{in} = 5 dBm

TYPICAL CHARACTERISTICS (T_A = +25°C)



Remark The graphs indicate nominal characteristics.

S-PARAMETERS

Test Conditions: $V_{DS} = 3.0\text{ V}$, $I_{Dset} = 300\text{ mA}$, $T_A = +25\text{ }^\circ\text{C}$

Frequency GHz	S11			S21			S12		S22		MAG ^{Note}	MSG ^{Note}	K
	Mag.	Ang.	dB	Mag.	Ang.	dB	Mag.	Ang.	Mag.	Ang.	dB	dB	-
0.1	0.655	-120.2	21.2	11.42	115.3	-31.6	0.026	28.7	0.633	-167.5		26.4	0.59
0.2	0.651	-142.0	17.2	7.25	99.3	-29.0	0.035	10.3	0.757	-167.9		23.1	0.36
0.3	0.666	-156.1	13.8	4.89	88.2	-29.3	0.034	-0.1	0.796	-173.0		21.5	0.40
0.4	0.660	-161.4	11.5	3.74	81.6	-29.2	0.034	-5.6	0.808	-175.0		20.4	0.50
0.5	0.656	-165.8	9.4	2.96	77.2	-29.2	0.035	-11.8	0.815	-175.9		19.3	0.62
0.6	0.655	-168.4	7.8	2.46	72.6	-29.3	0.034	-15.9	0.819	-176.8		18.6	0.76
0.7	0.654	-170.2	6.5	2.10	68.4	-29.5	0.033	-20.1	0.823	-177.4		18.0	0.91
0.8	0.658	-171.8	5.2	1.81	64.4	-29.6	0.033	-24.2	0.828	-178.0	16.2		1.04
0.9	0.656	-172.8	4.1	1.61	60.6	-29.7	0.033	-27.6	0.831	-179.4	14.2		1.20
1.0	0.658	-173.8	3.1	1.43	56.6	-29.8	0.032	-31.5	0.835	-179.9	12.8		1.37
1.1	0.663	-175.0	2.1	1.27	53.3	-30.0	0.031	-35.3	0.840	179.6	11.7		1.54
1.2	0.668	-175.8	1.1	1.14	49.9	-30.2	0.031	-39.1	0.843	179.2	10.7		1.75
1.3	0.668	-176.8	0.4	1.04	46.6	-30.3	0.030	-42.1	0.846	178.7	9.8		1.93
1.4	0.668	-177.6	-0.4	0.96	43.7	-30.6	0.030	-45.4	0.851	178.2	9.1		2.14
1.5	0.672	-178.5	-1.1	0.88	40.6	-30.7	0.029	-49.0	0.853	177.7	8.2		2.38
1.6	0.674	-179.2	-1.8	0.81	37.5	-31.0	0.028	-51.8	0.857	177.4	7.6		2.61
1.7	0.673	-180.0	-2.5	0.75	34.6	-31.1	0.028	-55.3	0.859	176.6	6.8		2.87
1.8	0.675	179.2	-3.2	0.69	31.7	-31.3	0.027	-58.6	0.862	176.1	6.1		3.20
1.9	0.677	178.5	-3.8	0.65	28.9	-31.6	0.026	-61.5	0.864	175.5	5.5		3.51
2.0	0.677	177.8	-4.4	0.61	26.4	-31.7	0.026	-64.6	0.867	174.9	5.0		3.76
2.1	0.677	177.0	-4.9	0.57	24.0	-31.9	0.025	-68.3	0.869	174.2	4.4		4.12
2.2	0.677	176.2	-5.4	0.54	21.2	-32.2	0.025	-71.4	0.869	173.6	3.8		4.57
2.3	0.681	175.4	-6.0	0.50	19.2	-32.2	0.025	-75.1	0.863	172.6	3.0		5.14
2.4	0.677	174.7	-6.5	0.48	16.6	-32.5	0.024	-78.2	0.873	172.4	2.8		5.35
2.5	0.675	174.6	-6.9	0.45	13.9	-32.7	0.023	-82.0	0.874	171.7	2.2		5.82
2.6	0.674	173.8	-7.4	0.43	11.7	-32.8	0.023	-85.1	0.874	170.9	1.7		6.29
2.7	0.673	173.2	-7.9	0.40	9.5	-33.0	0.022	-89.7	0.873	170.1	1.2		6.90
2.8	0.670	172.3	-8.3	0.39	7.8	-33.2	0.022	-92.3	0.875	169.4	0.8		7.45
2.9	0.667	171.4	-8.7	0.37	5.7	-33.4	0.021	-96.7	0.874	168.7	0.3		8.10
3.0	0.665	170.7	-9.1	0.35	3.5	-33.4	0.021	-101.5	0.873	167.9	-0.2		8.64
3.1	0.662	169.9	-9.5	0.33	1.4	-33.7	0.021	-106.4	0.873	167.2	-0.8		9.63
3.2	0.648	168.9	-9.8	0.32	-0.1	-34.1	0.020	-111.8	0.879	166.8	-1.0		10.28
3.3	0.656	168.6	-10.4	0.30	-1.4	-34.6	0.019	-117.6	0.872	165.7	-1.7		12.13
3.4	0.652	167.6	-10.6	0.29	-2.8	-35.3	0.017	-122.0	0.871	164.9	-2.1		13.80
3.5	0.651	167.1	-11.0	0.28	-4.5	-35.6	0.017	-123.8	0.871	164.1	-2.4		14.87
3.6	0.648	166.2	-11.3	0.27	-6.6	-35.6	0.017	-126.7	0.870	163.1	-2.8		15.51
3.7	0.644	165.4	-11.6	0.26	-7.9	-35.7	0.016	-130.5	0.869	162.3	-3.2		16.66
3.8	0.641	164.7	-12.0	0.25	-10.1	-36.0	0.016	-135.9	0.868	161.4	-3.7		18.41
3.9	0.636	163.8	-12.3	0.24	-11.5	-36.1	0.016	-140.3	0.867	160.4	-4.0		19.61
4.0	0.633	163.0	-12.6	0.23	-12.5	-36.2	0.015	-144.7	0.865	159.4	-4.4		21.02

Note When $K \geq 1$, the MAG (Maximum Available Gain) is used. $MAG = \left| \frac{S_{21}}{S_{12}} \right| (K - \sqrt{K^2 - 1})$

When $K < 1$, the MSG (Maximum Stable Gain) is used. $MSG = \left| \frac{S_{21}}{S_{12}} \right|, K = \frac{1 + |\Delta|^2 - |S_{11}|^2}{-|S_{22}|^2}$,

$$\Delta = S_{11} \cdot S_{22} - S_{21} \cdot S_{12}$$


LARGE SIGNAL IMPEDANCE ($V_{DS} = 3.0\text{ V}$, $I_{DS} = 300\text{ mA}$, $f = 460\text{ MHz}$)

f (MHz)	$Z_{in} (\Omega)$	$Z_{OL} (\Omega)$ ^{Note}
460	7.47 +j18.24	4.82 +j5.04

Note Z_{OL} is the conjugate of optimum load impedance at given voltage, idling current, input power and frequency.

EVALUATION BOARD for 460 MHz


Unit : mm




Symbol	Value	Comment
C1	9.1 pF	
C2	12 pF	
C3	20 pF	
C4	3.3 pF	
C5	13 pF	
C6	22 pF	
C7	1 000 pF	
C8	0.33 μ F	
C9	3.3 μ F - 16V	
R1	1 000 Ω	
L1	22 nH	
Circuit Board	t = 0.4 mm, ϵ r = 4.5	R4775

PACKAGE DIMENSIONS

79A (UNIT: mm)



79A PACKAGE RECOMMENDED P.C.B. LAYOUT (UNIT: mm)



RECOMMENDED SOLDERING CONDITIONS

This product should be soldered and mounted under the following recommended conditions. For soldering methods and conditions other than those recommended below, contact your nearby sales office.

Soldering Method	Soldering Conditions	Condition Symbol
Infrared Reflow	Peak temperature (package surface temperature) : 260°C or below Time at peak temperature : 10 seconds or less Time at temperature of 220°C or higher : 60 seconds or less Preheating time at 120 to 180°C : 120±30 seconds Maximum number of reflow processes : 3 times Maximum chlorine content of rosin flux (% mass) : 0.2%(Wt.) or below	IR260
VPS	Peak temperature (package surface temperature) : 215°C or below Time at temperature of 200°C or higher : 25 to 40 seconds Preheating time at 120 to 150°C : 30 to 60 seconds Maximum number of reflow processes : 3 times Maximum chlorine content of rosin flux (% mass) : 0.2%(Wt.) or below	VP215
Wave Soldering	Peak temperature (molten solder temperature) : 260°C or below Time at peak temperature : 10 seconds or less Preheating temperature (package surface temperature) : 120°C or below Maximum number of flow processes : 1 time Maximum chlorine content of rosin flux (% mass) : 0.2%(Wt.) or below	WS260
Partial Heating	Peak temperature (pin temperature) : 350°C or below Soldering time (per pin of device) : 3 seconds or less Maximum chlorine content of rosin flux (% mass) : 0.2%(Wt.) or below	HS350-P3

Caution Do not use different soldering methods together (except for partial heating).

- **The information in this document is current as of March, 2002. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC's data sheets or data books, etc., for the most up-to-date specifications of NEC semiconductor products. Not all products and/or types are available in every country. Please check with an NEC sales representative for availability and additional information.**
- No part of this document may be copied or reproduced in any form or by any means without prior written consent of NEC. NEC assumes no responsibility for any errors that may appear in this document.
- NEC does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC semiconductor products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC or others.
- Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of customer's equipment shall be done under the full responsibility of customer. NEC assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
- While NEC endeavours to enhance the quality, reliability and safety of NEC semiconductor products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC semiconductor products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment, and anti-failure features.
- NEC semiconductor products are classified into the following three quality grades:
 "Standard", "Special" and "Specific". The "Specific" quality grade applies only to semiconductor products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of a semiconductor product depend on its quality grade, as indicated below. Customers must check the quality grade of each semiconductor product before using it in a particular application.
 "Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots
 "Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)
 "Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.
 The quality grade of NEC semiconductor products is "Standard" unless otherwise expressly specified in NEC's data sheets or data books, etc. If customers wish to use NEC semiconductor products in applications not intended by NEC, they must contact an NEC sales representative in advance to determine NEC's willingness to support a given application.
 (Note)
 (1) "NEC" as used in this statement means NEC Corporation, NEC Compound Semiconductor Devices, Ltd. and also includes its majority-owned subsidiaries.
 (2) "NEC semiconductor products" means any semiconductor product developed or manufactured by or for NEC (as defined above).

M8E 00.4-0110

► **Business issue**

NEC Compound Semiconductor Devices, Ltd.

5th Sales Group, Sales Division TEL: +81-3-3798-6372 FAX: +81-3-3798-6783 E-mail: salesinfo@csd-nec.com

NEC Compound Semiconductor Devices Hong Kong Limited

Hong Kong Head Office TEL: +852-3107-7303 FAX: +852-3107-7309

Taipei Branch Office TEL: +886-2-8712-0478 FAX: +886-2-2545-3859

Korea Branch Office TEL: +82-2-528-0301 FAX: +82-2-528-0302

NEC Electron Devices European Operations <http://www.nec.de/>

TEL: +49-211-6503-101 FAX: +49-211-6503-487

California Eastern Laboratories, Inc. <http://www.cel.com/>

TEL: +1-408-988-3500 FAX: +1-408-988-0279

► **Technical issue**

NEC Compound Semiconductor Devices, Ltd. <http://www.csd-nec.com/>

Sales Engineering Group, Sales Division

E-mail: techinfo@csd-nec.com FAX: +81-44-435-1918