



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE1149 Integrated Circuit FM Tuning System

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Supply Voltage (Pin 14), V_{CC}	15V
Lamp Voltage, V_{LAMP}	20V
Lamp Current, I_{LAMP}	40mA
Power Dissipation, P_D	500mW
Operating Temperature Range ($V_{CC} = 12V$), T_{opr}	0 to $+60^\circ\text{C}$
Storage Temperature Range, T_{stg}	-55 to $+125^\circ\text{C}$

Electrical Characteristics: ($T_A = +25^\circ\text{C}$, $V_{CC} = 12V$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Lamp Voltage	V_{LAMP}	Voltage Gain from Terminal 1 to 13 is 35dB	-	10	16	mV
		Lamp Turn ON - $V_i = 10.7\text{Mhz}$ Lamp Turn OFF - $V_i = 10.7\text{Mhz}$ (Note 1)	6	10	-	mV
Tuning Meter Min. Operating Input Voltage		Voltage Gain from Terminal 1 to 13 is 35dB	-	7	-	mV
Tuning Meter Operating Range			-	30	-	dB
Center Meter Output Current		Meter Internal Input Resistance 20k Ω , Discriminator $V_i = \pm 0.5V$	40	60	75	μA
Muting On Output Voltage			1.8	23	-	V
Muting Off Output Voltage			-	0.2	0.6	V
Internal Power Dissipation	P_D	At Lamp ON	-	230	-	mW
		At Lamp OFF	-	150	-	mW

Pin Connection Diagram
(Front View)

