

PROVISIONAL



P16M40CT


16A Schottky Barrier Rectifier

Features

- ◆ Plastic material meets UL94V-0
- ◆ Metal silicon junction
- ◆ Very low forward voltage drop
- ◆ High current / High surge capability
- ◆ Guarding for over voltage protection
- ◆ Lead solderable per MIL-STD202,method 208 guaranteed
- ◆ Lead temperature for soldering purpose 250°C Max for 10 second
- ◆ Weight : 2.2 gram (approximately)

General Description

The P16M40CT schottky Rectifier has been designed for applications requiring low forward voltage drop and switching power supply, dc-dc converter, free-wheeling diode, battery charging, polarity protection application.



Absolute Maximum Ratings

Symbol	Parameter	Value	Units
V_{RRM}	Repetitive Peak Reverse Voltage	40	V
V_R	Maximum DC Reverse Voltage	40	V
$I_{F(AV)}$	Average Forward Current @ $T_C = 95^\circ C$ Per Diode Total Device	8 16	A A
I_{FSM}	Non-Repetitive Peak Surge Current (Surge applied at rated load conditions half sinewave,single phase, 60Hz)	250	A
E_{as}	Non-Repetitive Avalanche Energy @ $T_C=25^\circ C$, $V_{dd} = 15V$, $L=18\mu H$	6.0	mJ
T_J	Maximum Junction Temperature	- 65 ~ 125	°C
T_{STG}	Storage Temperature Range	- 65 ~ 150	°C

Thermal Characteristics

Symbol	Parameter	Value	Units
$R_{\theta JC}$	Maximum Thermal Resistance, Junction-to-Case (per diode)	2.5	°C/W

P16M40CT

Electrical Characteristics

Symbol	Parameter	Min	Typ	Max	Units
I_R	Reverse Leakage Current $V_R = V_{RRM}$ $T_C = 25 \text{ }^\circ\text{C}$ $T_C = 125 \text{ }^\circ\text{C}$	-	-	1 50	mA
V_F	Forward Voltage Drop $I_F = 8 \text{ A} \quad T_C = 25 \text{ }^\circ\text{C}$ $I_F = 8 \text{ A} \quad T_C = 125 \text{ }^\circ\text{C}$ $I_F = 16 \text{ A} \quad T_C = 25 \text{ }^\circ\text{C}$ $I_F = 16 \text{ A} \quad T_C = 125 \text{ }^\circ\text{C}$	-	-	0.55 0.50 0.70 0.62	V
C_T	Typical Junction Capacitance @ $f_T=1\text{MHz}$, $V_R=4\text{V}$, $T_j=25\text{ }^\circ\text{C}$			700	pF



Fig 1. VF-IF Characteristic




Fig 2. VR-IR Characteristic




Fig 3. Typical junction capacitance




Fig 4. Forward current derating curve




Fig 5. Maximum non-repetitive forward surge current per diode

