

M1 SERIES

P6DUI-XXXXXXZ 1KV ISOLATED 1W UNREGULATED DUAL SEPARATE OUTPUT DIP14

Available Inputs:

5, 12, and 24 VDC

Available Outputs:

(++) 3.3, 5, 7.2, 12, 15 and 18 VDC

Other specifications please enquire.

Electrical Specifications

(Typical at + 25° C, nominal input voltage, rated output current unless otherwise specified)

Input Specifications

Voltage range +/- 10 %
 Filter Capacitors

Isolation Specifications

Rated voltage 1000 VDC
 Leakage current 1 mA
 Resistance 10⁹ Ohm
 Capacitance 60 pF typ.

Output Specifications

Voltage accuracy +/- 5 %, max.
 Ripple and noise (at 20 MHz BW) 75 mV p-p, max.
 Short circuit protection Momentary
 Line voltage regulation +/- 1,2 % / 1,0 % of Vin
 Load voltage regulation +/- 8 %, load = 20 ~ 100 %
 Temperature coefficient +/- 0,02 % / °C

General Specifications

Efficiency 70 % to 85 %
 Switching frequency 125 KHz, typ.

Environmental Specifications

Operating temperature (ambient) - 40° C to + 85° C
 Storage temperature - 55 °C to + 125 °C
 Derating See graph
 Humidity Up to 90 %, non condensing
 Cooling Free air convection


Physical Characteristics

Dimensions DIP 20,32 x 10,16 x 6,85 mm
 0,80 x 0,40 x 0,77 inches
 Weight 2 g
 Case material Non conductive black plastic


Examples of Partnumbers/Modelcode

PART NO.	INPUT VOLTAGE (VDC)	INPUT CURRENT NO LOAD	INPUT CURRENT FULL LOAD	OUTPUT VOLTAGE (VDC)	OUTPUT CURRENT (max. mA)	EFFICIENCY FULL LOAD (% TYP.)
P6DUI-050505Z	5	16	277	5/5	100/100	72
P6DUI-050515Z	5	20	250	5/15	100/33	80
P6DUI-120505Z	12	11	119	5/5	100/100	70
P6DUI-120512Z	12	10	104	5/12	100/42	80
P6DUI-120515Z	12	13	106	5/15	100/33	78
P6DUI-240505Z	24	6	54	5/5	100/100	76

Dimensions



Derating Graph and Pinning



Specification can be changed without notice.

Copyright PEAK electronics GmbH