



CIRCUIT

OUTLINE DRAWING


Dimension(mm)

Approximate Weight : 500g

MAXIMUM RATINGS (T_c=25°C)

Item		Symbol	PHMB300A6		Unit
Collector-Emitter Voltage		V _{CEs}	600		V
Gate - Emitter Voltage		V _{GEs}	+/- 20		V
Collector Current	DC	I _C	300		A
	1 ms	I _{CP}	600		
Collector Power Dissipation		P _C	1040		W
Junction Temperature Range		T _j	-40 to +150		°C
Storage Temperature Range		T _{stg}	-40 to +125		°C
Isolation Voltage Terminal to Base AC, 1 min.)		V _{ISO}	2500		V
Mounting Torque	Module Base to Heatsink	F _{TOR}	3		N•m
	Bus Bar to Main Terminals		M4	1.4	
			M6	3	

ELECTRICAL CHARACTERISTICS (T_c=25°C)

Characteristic		Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Emitter Cut-Off Current		I _{CEs}	V _{CE} =600V, V _{GE} =0V	-	-	3.0	mA
Gate-Emitter Leakage Current		I _{GES}	V _{GE} =+/- 20V, V _{CE} =0V	-	-	1.0	μA
Collector-Emitter Saturation Voltage		V _{CE(sat)}	I _C =300A, V _{GE} =15V	-	2.1	2.6	V
Gate-Emitter Threshold Voltage		V _{GE(th)}	V _{CE} =5V, I _C =300mA	4.0	-	8.0	V
Input Capacitance		C _{ies}	V _{CE} =10V, V _{GE} =0V, f=1MHz	-	30,000	-	pF
Switching Time	Rise Time	t _r	V _{CC} = 300V R _L = 1 ohm R _G = 2 ohm V _{GE} = +/- 15V	-	0.2	0.4	μs
	Turn-on Time	t _{on}		-	0.4	0.75	
	Fall Time	t _f		-	0.2	0.35	
	Turn-off Time	t _{off}		-	0.6	0.8	

FREE WHEELING DIODES RATINGS & CHARACTERISTICS (T_c=25°C)

Item		Symbol	Rated Value		Unit
Forward Current	DC	I _F	300		A
	1 ms	I _{FM}	600		

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Peak Forward Voltage	V _F	I _F =300A, V _{GE} =0V	-	1.9	2.4	V
Reverse Recovery Time	t _{rr}	I _F =300A, V _{GE} =-10V, di/dt=300A/μs	-	0.15	0.25	μs

THERMAL CHARACTERISTICS

Characteristic		Symbol	Test Condition	Min.	Typ.	Max.	Unit
Thermal Impedance	IGBT	R _{th(j-c)}	Junction to Case	-	-	0.12	°C/W
	DIODE			-	-	0.24	

PHMB300A6

Fig.1- Output Characteristics (Typical)




Fig.2- Collector to Emitter On Voltage vs. Gate to Emitter Voltage (Typical)




Fig.3- Collector to Emitter On Voltage vs. Gate to Emitter Voltage (Typical)




Fig.4- Gate Charge vs. Collector to Emitter Voltage (Typical)




Fig.5- Capacitance vs. Collector to Emitter Voltage (Typical)





Fig.6- Collector Current vs. Switching Time (Typical)



PHMB300A6

Fig.7- Series Gate Impedance vs. Switching Time (Typical)




Fig.8- Forward Characteristics of Free Wheeling Diode (Typical)




Fig.9- Reverse Recovery Characteristics (Typical)




Fig.10- Reverse Bias Safe Operating Area (Typical)




Fig.11- Transient Thermal Impedance

