

STANDARD CAPACITANCE TVS COMPONENT**APPLICATIONS**

- ✓ Ethernet - 10/100/1000 Base T
- ✓ Cellular Phones
- ✓ Personal Digital Assistant (PDA)
- ✓ USB Interfaces

IEC COMPATIBILITY (EN61000-4)


- ✓ 61000-4-2 (ESD): Air - 15kV, Contact - 8kV
- ✓ 61000-4-4 (EFT): 40A - 5/50ns

FEATURES

- ✓ 250 Watts Peak Pulse Power per Line (tp=8/20μs)
- ✓ Cable Discharge Event (CDE) Protection
- ✓ ESD Protection > 25 kilovolts
- ✓ Unidirectional Configuration
- ✓ Protects One Unidirectional Line
- ✓ RoHS Compliant in Lead-Free Versions

MECHANICAL CHARACTERISTICS

- ✓ Molded EIAJ SC-79
- ✓ Weight 2 milligrams (Approximate)
- ✓ Available in Tin-Lead or Lead-Free Pure-Tin Plating
- ✓ Solder Reflow Temperature:
 - Tin-Lead - Sn/Pb, 85/15: 240-245°C
 - Pure-Tin - Sn, 100: 260-270°C
- ✓ Flammability Rating UL 94V-0
- ✓ 8mm Tape and Reel Per EIA Standard 481
- ✓ Device Marking: Marking Code & Polarity Band

**PIN CONFIGURATION**

DEVICE CHARACTERISTICS

MAXIMUM RATINGS @ 25°C Unless Otherwise Specified			
PARAMETER	SYMBOL	VALUE	UNITS
Peak Pulse Power (tp = 8/20µs) - See Figure 1	P _{PP}	250	Watts
Peak Pulse Current (tp = 8/20µs)	I _{PP}	16	A
Operating Temperature	T _J	-55°C to 150°C	°C
Storage Temperature	T _{STG}	-55°C to 150°C	°C
Soldering Temperature for 10 seconds	T _L	265°C	°C

ELECTRICAL CHARACTERISTICS PER LINE @ 25°C Unless Otherwise Specified								
PART NUMBER	DEVICE MARKING CODE	RATED STAND-OFF VOLTAGE	MINIMUM BREAKDOWN VOLTAGE	TYPICAL FORWARD VOLTAGE	MAXIMUM CLAMPING VOLTAGE (See Fig. 2)	MAXIMUM CLAMPING VOLTAGE (See Fig. 2)	MAXIMUM LEAKAGE CURRENT	TYPICAL CAPACITANCE
		V _{WM} VOLTS	@ 1mA V _(BR) VOLTS	@ 100mA V _F VOLTS	@ I _p = 5A V _C VOLTS	@ I _p = 16A V _C VOLTS	@ V _{WM} I _b µA	@ 0V, 1MHz C pF
PLW0501H	U5	5.0	6.0	0.8	9.8	12.5	5	120

FIGURE 1
PEAK PULSE POWER VS PULSE TIME





FIGURE 2
PULSE WAVE FORM




PACKAGE OUTLINE & DIMENSIONS

PACKAGE OUTLINE		SC79 PACKAGE			
		PACKAGE DIMENSIONS			
DIM	INCHES		MILLIMETERS		
	MIN	MAX	MIN	MAX	
A	0.043	0.049	1.10	1.30	
B	0.028	0.035	0.70	0.90	
C	0.059	0.066	1.50	1.70	
D	0.020	0.028	0.50	0.70	
E	0.003	0.008	0.08	0.20	
F	0.012 BSE		0.30 BSE		
MOUNTING PAD		NOTES			
		<p>NOTES</p> <ol style="list-style-type: none"> Controlling Dimensions in Millimeters. Dimensions are exclusive of mold flash and metal burrs. <p>TAPE & REEL ORDERING NOMENCLATURE</p> <ol style="list-style-type: none"> Surface mount product is taped and reeled in accordance with EIA-481. Suffix-T7 = 7 Inch Reel - 3,000 pieces per 8mm tape, i.e., <i>PLW0501H-T73</i>. Suffix-T13 = 13 Inch Reel - 10,000 pieces per 8mm tape, i.e., <i>PLW0501H-T13</i>. Suffix-LF = Lead-Free, Pure Tin Plating, i.e., <i>PLW0501H-LF-T73</i>. <p style="text-align: right;">Outline & Dimensions: Rev 2- 9/05, 06037</p>			

Tape & Reel Specifications (Dimensions in millimeters)

Reel Dia.	Tape Width	A0	B0	K0	D	E	F	W	P0	P2	P	tmax
178mm (7")	8mm	1.00 ± 0.10	1.95 ± 0.05	0.75 ± 0.05	1.50 ± 0.10	1.75 ± 0.10	3.50 ± 0.05	8.00 ± 0.30	4.00 ± 0.10	2.00 ± 0.05	4.00 ± 0.10	0.25



COPYRIGHT © ProTek Devices 2005

SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice (except JEDEC).

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice, and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance, ProTek assumes no responsibility with respect to the selection or specifications of such products.

ProTek Devices
 2929 South Fair Lane, Tempe, AZ 85282
 Tel: 602-431-8101 Fax: 602-431-2288
 E-Mail: sales@protekdevices.com
 Web Site: www.protekdevices.com