

Description

The S3001 is a monolithic integrated circuit, and suitable for 5-ch motor driver which driver focus actuator, tracking actuator, sled motor, spindle motor and tray motor of CDP & V-CD system.


Features

- 1ch(forward-reverse) control DC motor driver
- 4ch BTL(Balanced Transformerless) driver
- Built-in TSD (Thermal shutdown) circuit
- Built-in 5V regulator with an internal NPN TR
- Built-in mute circuit
- Built-in Tray motor speed control circuit
- Wide operating supply voltage range: 6.5V~13.2V


Ordering Information

| Type NO. | Marking | Package Code |
|----------|---------|--------------|
| S3001 | S3001 | SSOPH-28 |

BLOCK DIAGRAM



PIN CONNECTIONS



PIN DESCRIPTIONS

| NO | SYMBOL | I/O | DESCRIPTION | NO | SYMBOL | I/O | DESCRIPTION |
|----|--------|-----|------------------|----|--------|-----|---------------------------------------|
| 1 | DO1- | O | CH1 OUTPUT (-) | 15 | DO5+ | O | CH5 OUTPUT (+) |
| 2 | DO1+ | O | CH1 OUTPUT(+) | 16 | DO5- | O | CH5 OUTPUT (-) |
| 3 | IN1 | I | CH1 INPUT 1 | 17 | DO3- | O | CH3 OUTPUT (-) |
| 4 | IN1A | I | CH1 INPUT 2 | 18 | DO3+ | O | CH3 OUTPUT (+) |
| 5 | N / C | - | NO-CONNECTION | 19 | IN3 | I | CH3 INPUT |
| 6 | REO | O | REGULATOR OUTPUT | 20 | CTL | I | CH5 MOTOR SPEED CONTROL |
| 7 | MUTE | I | MUTE INPUT | 21 | VCC1 | I | SUPPLY VOLTAGE 1 (CH2,CH3,CH5) |
| 8 | SGND | - | SIGNAL GROUND | 22 | VCC2 | I | SUPPLY VOLTAGE 2 (CH1,CH4,SIGNAL,REG) |
| 9 | FWD | I | CH5 INPUT 1 | 23 | REF | I | CH BIAS INPUT |
| 10 | IN2 | I | CH2 INPUT | 24 | IN4A | I | CH4 INPUT 1 |
| 11 | DO2+ | O | CH2 OUTPUT (+) | 25 | IN4 | I | CH4 INPUT 2 |
| 12 | DO2- | O | CH2 OUTPUT (-) | 26 | DO4+ | O | CH4 OUTPUT (+) |
| 13 | PGND1 | - | POWER GROUND 1 | 27 | DO4- | O | CH4 OUTPUT (-) |
| 14 | REV | I | CH5 INPUT 2 | 28 | PGND2 | - | POWER GROUND 2 |


ABSOLUTE MAXIMUM RATINGS

| CHARACTERISTICS | SYMBOL | VALUE | UNIT |
|-----------------------|------------------|-----------------------|------|
| Supply voltage | V _{CC} | 15 | V |
| Power dissipation | P _d | 2.3 ^(Note) | W |
| Operating temperature | T _{opr} | -35 ~ +85 | °C |
| Storage temperature | T _{stg} | -55 ~ +150 | °C |
| Output current | I _o | 1.0 | A |

Note>

1. When mounted on 50mm × 50mm × 1mm PCB (Phenolic resin material).
2. Power dissipation reduces 18.4 mW/°C for using above Ta=25°C
3. Do not exceed Pd and SOA.

POWER DISSIPATION CURVE



PRECOMMENDED OPERATING CONDITIONS

| CHARACTERISTICS | SYMBOL | VALUE | UNIT |
|------------------|------------------|----------|------|
| Supply voltage 1 | V _{cc1} | 6.5~13.2 | V |
| Supply voltage 2 | V _{cc2} | 6.5~13.2 | V |

Electrical Characteristics

($T_a=25^{\circ}\text{C}$, $V_{CC1}=V_{CC2}=8\text{V}$, $R_L=8\Omega$, unless otherwise specified.)

| Characteristic | Symbol | Test Condition | Min. | Typ. | Max. | Unit |
|----------------------------|--------------------------|---|------|------|------|------|
| Quiescent circuit current | I_{CC} | - | - | 10 | - | mA |
| Mute on current | I_{mute} | $V_{\text{pin7}}=0$ | - | 2.5 | 5 | mA |
| Mute on voltage | V_{mon} | - | - | - | 0.5 | V |
| Mute off voltage | V_{moff} | - | 2 | - | - | V |
| [BTL DRIVE PART] | | | | | | |
| Output offset voltage | V_{oo} | $V_{\text{in}}=2.5\text{V}$ | -40 | - | +40 | mV |
| Maximum output voltage | V_{om} | $V_{CC1}=V_{CC2}=8\text{V}$, 8Ω | 4 | 5 | - | V |
| Closed-loop voltage gain | A_{vf} | $V_{\text{in}}=0.1\text{Vrms}$, $f=1\text{KHz}$ | 5 | 6.5 | 8 | dB |
| Ripple rejection ratio | RR | $V_{\text{in}}=0.1\text{Vrms}$, $f=120\text{Hz}$ | 50 | 60 | - | dB |
| Slew rate | SR | $V_{\text{out}}=4\text{Vp-p}$, square | - | 1.5 | - | V/us |
| [REGULATOR PART] | | | | | | |
| Output voltage | V_{reo} | $I_L=100\text{mA}$ | 4.7 | 5 | 5.3 | V |
| Load regulation 1 | $\Delta V_{\text{rl 1}}$ | $I_L=0\sim 100\text{mA}$ | -40 | - | 10 | mV |
| Load regulation 2 | $\Delta V_{\text{rl 2}}$ | $I_L=0\sim 200\text{mA}$ | -70 | - | 10 | mV |
| Line regulation | V_{CC} | $V_{CC}=6.5\text{V}\sim 12.5\text{V}$, $I_L=100\text{mA}$ | -20 | - | +60 | mV |
| [TRAY DRIVE PART] | | | | | | |
| Input high level voltage | V_{ih} | - | 2 | - | - | V |
| Input low level voltage | V_{il} | - | - | - | 0.5 | V |
| Output voltage | ΔV_{o} | $V_{CC}=8\text{V}$, $R_L=45\Omega$, $V_{\text{pin20}}=\text{open}$ | 2.5 | 3.1 | 3.8 | V |
| Output voltage regulation | V_{o} | $V_{CC}=8\text{V}$, $R_L=45\Omega$, $V_{\text{pin20}}=3.5\text{V}\sim 4.5\text{V}$ | 0.6 | 1 | 1.4 | V |
| Output offset voltage 1 | V_{oo1} | V_{pin9} , $V_{\text{pin14}}=5\text{V}$ | -40 | - | +40 | mV |
| Output offset voltage 2 | V_{oo2} | V_{pin9} , $V_{\text{pin14}}=0\text{V}$ | -40 | - | +40 | mV |

APPLICATION SUMMARY

- Reference & all mute

When you want to control output bias current of the S3001, use pin #23 as follows




Fig1.Reference & all mute function

| Pin#23 | Mute |
|------------|------|
| Above 1.0V | off |
| Below 1.0V | on |

As shown in figure 1, Pin#23 is a negative input of the comparator, and the other input is the 1.0V reference. If the voltage of the Pin#23 falls below 1.0V, TR Q1 will be turned on and the output bias current will be shut down

- Mute

When you want to control output bias current of the S3001, you can also use pin#7 as follows




Fig2. Mute function

| Pin#7 | Mute |
|-------|------|
| High | off |
| Low | on |

As shown in figure 2, Pin#7 is a base input of the TR Q2. If the voltage of the pin#7 is low or open, TR Q2 will be turned off and TR Q3 will be turned on, so the bias current will be shut down by TR Q3. If the voltage of the pin#7 is high, the bias circuit operates normally.

■ APPLICATION SUMMARY(Continued)

- Thermal Shutdown

The S3001 has a thermal protection against the abnormal operation, and the detailed operation of the TSD circuit is as follows




Fig3. Thermal shut down

| Temperature | Mute |
|-------------------|------|
| Above 175 °C | on |
| Falls below 150°C | off |

As shown in figure 3, TSD circuit controls the base of the TR Q4. If the junction temperature rises above 175°C TR Q4 will be turned on, and the bias current of the output drive circuit will be shut down (because of the negative temperature characteristic of the NPN transistor). And then temperature falls below 150°C, TR Q4 will be turned off. (hysteresis temperature is about to 25°C)

- BTL drive part (Focus, Tracking, Spindle, Sled drive park)

BTL drive part is composed of V-I converter, level shifter and output power amp.




Fig4. BTL drive part

-V-I converter converts voltage of the input pin into current

$$I_{conv} = \frac{V_{in} - V_{ref}}{10k}$$

*Vin=input voltage of the input pin (pin3,10,19,25)

*Vref=reference voltage (pin23)

The level shift changes the direction of the current(I_{conv}) as the same amount, and then supply it to the power AMP.

The resistor $R_a(10.6K)$ converts current into voltage with the DC offset of P_{ref} .

$$V_a = 10.6K \times \frac{V_{in} - V_{ref}}{10k} + P_{ref}$$
$$-V_a = -10.6K \times \frac{V_{in} - V_{ref}}{10k} + P_{ref} \quad \text{When } P_{ref} = \frac{V_{CC1} - V_{be}}{2}$$

The power amp has unity gain.

So the total differential voltage gain of the S3001 is as follows.

$$\text{Gain} = 20 \log \frac{\{[10.6k \times \frac{V_{in} - V_{ref}}{10k} + P_{ref}] - [(-)10.6k \times \frac{V_{in} - V_{ref}}{10k} + P_{ref}]\}}{V_{in} - V_{ref}}$$
$$= 20 \log 2 \times \frac{10.6K}{10K}$$
$$= 6.527 \text{dB}$$

If you want to reduce the total gain of the BTL drive part, use additional series resistor into the input pin(pin#3, 10, 19, 25)

You can also increase or decrease the voltage gain of the CH1, CH4 using adjustable pin(pin#4, pin24) by inserting an external series resistor.

■ APPLICATION SUMMARY(Continued)

- Tray motor drive part

CH5 is a forward-reverse control DC motor driver and it is composed of logic control part, level shifter, and output power




Fig5. Tray drive part

The forward and reverse rotation is controlled by pin9(fwd), pin14(rev) and the amplitude of the output voltage is controlled by pin20(CTL).

The output status due to the input conditions are as follows

| INPUT | | OUTPUT | | |
|-----------|------------|-------------|-------------|---------|
| FWD(PIN9) | REV(PIN14) | DO5+(PIN15) | DO5-(PIN16) | STATUS |
| High | High | Vp | Vp | Brake |
| High | Low | High | Low | Forward |
| Low | High | Low | High | Reverse |
| Low | Low | Vp | Vp | Brake |

■ APPLICATION SUMMARY(Continued)

- Tray motor speed control

The amplitude of the output voltage is controlled by pin20(CTL).




Fig6.Thay motor speed control

Normally, the differential output voltage is 3.1V when the pin20(CTL) is open.

If you want to control differential output voltage of the tray drive part, insert external resistor R and zener diode ZD as shown in figure 6.

Zener diode ZD is only needed when you want to obtain a precision output voltage, In other case you only insert an external resistor R.

- Regulator part

S3001 has a temperature independent voltage source internally.

So in the figure 7, the reference voltage (2.5V) is generated by the internal circuit (bandgab reference),




Fig7. Regulator


Because the power NPN TR Q5 is inserted internally, there is no need to attach an external active component.

The output voltage of the regulator is Calculated as follows


$$V_{re0} = (1 + \frac{3.3K}{3.3K}) \times 2.5 = 5V$$

And he capacitor 1uF is used as a ripple & noise eliminator and should have a good Temperature characteristics.

TEST CIRCUIT



TYPICAL APPLICATION CIRCUIT



INTERNAL CIRCUIT

| Pin no | Pin name | Internal circuit |
|--|--|------------------|
| <p>1,2, 11,12, 15,16 17,18 26,27</p> | <p>DO1- DO1+ DO2+ DO2- DO5+ DO5- DO3- DO3+ DO5+ DO5-</p> | |
| <p>3, 4, 10, 19, 23, 24, 25,</p> | <p>IN1 IN1A IN2 IN3 REF IN4A IN4</p> | |

INTERNAL CIRCUIT(Continued)

| Pin no | Pin name | Internal circuit |
|--------|------------|------------------|
| 6 | REO | |
| 7 | MUTE | |
| 9,14 | FWD REV | |

INTERNAL CIRCUIT(Continued)

| Pin no | Pin name | Internal circuit |
|--------|----------|------------------|
| 20 | CTL | |

Electrical Characteristic Curves

Fig. 1. VCC vs ICC




Fig. 2. VCC vs Imute




Fig. 3. VCC vs Avf




Fig. 4. VCC vs Vom




Fig. 5. IL vs Vcesat_upper





Fig. 6. IL vs Vcesat_lower



Electrical Characteristic Curves (Cont.)

Fig. 7. VCC vs Vreo




Fig. 8. IL vs Vreo




Fig. 9. VCC vs Vo




Fig. 10. Vctl vs Vo




Fig. 11. Temperature vs Icc





Fig. 12. Temperature vs Im



Electrical Characteristic Curves

Fig. 13. Temperature vs Avf




Fig. 14. Temperature vs Vom




Fig. 15. Temperature vs Vo







Fig. 16. Temperature vs Vreg



PACKAGE DIMENSION

unit : mm



These AUK products are intended for usage in general electronic equipments(Office and communication equipment, measuring equipment, domestic electrification, etc.).

Please make sure that you consult with us before you use these AUK products in equipments which require high quality and/or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, traffic signal, combustion central, all types of safety device, etc.).

AUK cannot accept liability to any damage which may occur in case these AUK products were used in the mentioned equipments without prior consultation with AUK.