

Descriptions

- Switching application
- Interface circuit and driver circuit application


Features

- With built-in bias resistors
- Simplify circuit design
- Reduce a quantity of parts and manufacturing process
- High packing density

Ordering Information

Type NO.	Marking	Package Code
SRC1219EF	RC	SOT-523F

Outline Dimensions

unit : mm


Absolute maximum ratings

(Ta=25°C)

Characteristic	Symbol	Ratings	Unit
Out Voltage	V _O	50	V
Input Voltage	V _I	20	V
Out Current	I _O	100	mA
Power Dissipation	P _D	150	mW
Junction Temperature	T _J	150	°C
Storage Temperature	T _{STG}	-55 ~ 150	°C

Electrical Characteristics

(Ta=25°C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Output Cut-off Current	I _{O(OFF)}	V _O =50V, V _I =0	-	-	500	nA
DC Current Gain	G _I	V _O =5V, I _O =10mA	30	-	-	-
Output Voltage	V _{O(ON)}	I _O =10mA, I _I =0.5mA	-	0.1	0.3	V
Input Voltage (ON)	V _{I(ON)}	V _O =0.3V, I _O =20mA	-	1.76	2.5	V
Input Voltage (OFF)	V _{I(OFF)}	V _O =5V, I _O =0.1mA	0.3	0.82	-	V
Transition Frequency	f _T [*]	V _O =10V, I _O =5mA	-	250	-	MHz
Input Current	I _I	V _I =5V	-	-	1.8	mA

*: Characteristic of Transistor Only

Electrical Characteristic Curves

Fig. 1 I_o - $V_{I(ON)}$




Fig. 2 I_o - $V_{I(OFF)}$




Fig. 3 G_I - I_o

