




1	2	3	4	5	6	7	8	9	10	11
FG	VSS	VDD	VCOULT	VEE	WR	RD	CE	C/D	HALT	RESET
12	13	14	15	16	17	18	19	20	21	22
D0	D1	D2	D3	D4	D5	D6	D7	NC	EL1	EL2

NOTE:

- | | |
|----------------------------|-----------------------------|
| 1. DISPLAY TYPE: | STN or FSTN |
| 2. VIEWING DIRECTION: | 6:00 or 12:00 |
| 3. POLARIZER MODE: | REFLECTIVE or TRANSFLECTIVE |
| 4. DRIVE METHOD: | 1/128 DUTY 1/12 BIAS |
| 5. LCD OPERATING VOLTAGE: | 15.0V |
| 6. OPERATING TEMP: | NORMAL or WIDE |
| 7. STORAGE TEMP: | NORMAL or WIDE |
| 8. CONTROLLER: | T6963C |
| 9. BACKLIGHT: | NONE, EL, or LED |
| 10. BEZEL IS TO BE PAINTED | BLACK |
| 11. UNMARKED TOLERANCE: | ±0.3MM |

DETAIL A:



 TIAN-MA MICROELECTRONICS CO. 6/F., CASTIC Building, Shennan Road, Central, Shenzhen, China.			
			TITLE: TM160128A
DRAWN BY:	CHECKED BY:	DWG NO: G-1	SCALE:
APPROVED BY:	CONFIRMED BY:	DWG NAME: TM160128AENG-1	UNIT: mm
		SHEET NO: 01	