



SEE DRAWING NO. VM-206C-M FOR STANDARD MATERIALS OF CONSTRUCTION.

VALVE SIZE	125 LB. MODEL NO.	250 LB. MODEL NO.	A	B	C	D	Y	INLET SIZE	AIR/VAC OUTLET	AIR RELEASE OUTLET	ORIFICE SIZE	
											150 P.S.I.	300 P.S.I.
6"	206C	256C	21"	20 1/4"	14"	10 7/8"	2 3/8"	6" FLG.	6" HOOD	1" NPT	3/8"	7/32"
8"	208C	258C	25"	23 1/2"	17"	11"	7/8"	8" FLG.	8" HOOD	1" NPT	3/8"	7/32"

- | | | | |
|---------------|--------------------|-------------------------|------------------------------|
| 1 BODY | 7 COVER BOLT | 15 CUSHION | 25 WASHER |
| 2 COVER | 8 RETAINING SCREW | 17 FLOAT RETAINER | 26 SEAT RETAINING SLEEVE |
| 3 LEVER FRAME | 8A RETAINING SCREW | 18 LOCK NUT | 27 WASHER (INTERNAL) 8" ONLY |
| 4 SEAT | 9 GUIDE BUSHING | 19 LINK | 28 PIPE PLUG |
| 4A SEAT | 10 FLOAT ARM | 21 LOCATING PIN | 30 WASHER |
| 5 FLOAT | 11 ORIFICE BUTTON | 22 ORIFICE BUTTON ARM | 34 LOCK WASHER |
| 5A FLOAT | 12 PIVOT PIN | 23 HOOD | |
| 6 GASKET | 13 RETAINING RING | 24 HOOD RETAINING SCREW | |

Revised 8-9-04

COMBINATION AIR VALVE (SINGLE BODY TYPE)

DATE 1-30-80



DRWG. NO. VM-206C