



NTC thermistors for temperature measurement

Miniature sensors
with bendable wires

Series/Type: B57867
Date: March 2006

Applications

- Heating systems
- Industrial electronics
- Automotive electronics

Features

- Fast response
- High measuring accuracy
- Different tolerances available
- Epoxy resin encapsulation
- Silver-plated nickel leads
- UL approval (E69802)

Options


Non-standard lead lengths

Delivery mode

Bulk

General technical data

| | | | | |
|-------------------------------|---------------|------------------|-----------------------|------|
| Climatic category | (IEC 60068-1) | | 55/155/56 | |
| Max. power | (at 25 °C) | P_{25} | 60 | mW |
| Resistance tolerance | | $\Delta R_R/R_R$ | $\pm 1, \pm 3, \pm 5$ | % |
| Rated temperature | | T_R | 25 | °C |
| Dissipation factor | (in air) | δ_{th} | approx. 1.5 | mW/K |
| Thermal cooling time constant | (in air) | τ_c | approx. 12 | s |
| Heat capacity | | C_{th} | approx. 18 | mJ/K |

Dimensional drawing


Dimensions in mm

Approx. weight 60 mg

Electrical specification and ordering codes

| R_{25} Ω | No. of R/T characteristic | $B_{25/100}$ K | Ordering code |
|---------------|------------------------------|-------------------|-----------------|
| 2 k | 1008 | $3560 \pm 1\%$ | B57867S0202+140 |
| 3 k | 8016 | $3988 \pm 1\%$ | B57867S0302+140 |
| 5 k | 8016 | $3988 \pm 1\%$ | B57867S0502+140 |
| 10 k | 8016 | $3988 \pm 1\%$ | B57867S0103+140 |
| 30 k | 8018 | $3964 \pm 1\%$ | B57867S0303+140 |
| 50 k | 2901 | $3760 \pm 1\%$ | B57867S0503+140 |
| 100 k | 2014 | $4540 \pm 1\%$ | B57867S0104+140 |

+ = Resistance tolerance

F = $\pm 1\%$

H = $\pm 3\%$

J = $\pm 5\%$

Reliability data

| Test | Standard | Test conditions | $\Delta R_{25}/R_{25}$ (typical) | Remarks |
|---------------------------------------|----------------|---|-------------------------------------|-------------------|
| Storage in dry heat | IEC 60068-2-2 | Storage at upper category temperature T: 155 °C t: 1000 h | < 2% | No visible damage |
| Storage in damp heat, steady state | IEC 60068-2-78 | Temperature of air: 40 °C Relative humidity of air: 93% Duration: 56 days | < 1% | No visible damage |
| Rapid temperature cycling | IEC 60068-2-14 | Lower test temperature: -55 °C Upper test temperature: 155 °C Number of cycles: 100 | < 1% | No visible damage |
| Long-term stability (empirical value) | | Temperature: 70 °C t: 10000 h | < 2% | No visible damage |

R/T characteristics

| B57867S0202F140 | | | | | | |
|------------------------|--|----------------------|----------------------|--------------------------------------|------------|------------|
| R/T No. | 1008 | | | | | |
| T (°C) | B _{25/100} = 3560 K, R ₂₅ = 2000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 1% | | | | | |
| | R _{noml} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -55.0 | 106210 | 100440 | 111970 | 5.4 | 0.9 | 6.1 |
| -50.0 | 78635 | 74654 | 82616 | 5.1 | 0.8 | 6.0 |
| -45.0 | 58650 | 55886 | 61415 | 4.7 | 0.8 | 5.8 |
| -40.0 | 44060 | 42131 | 45989 | 4.4 | 0.8 | 5.7 |
| -35.0 | 33333 | 31980 | 34686 | 4.1 | 0.7 | 5.5 |
| -30.0 | 25392 | 24439 | 26344 | 3.8 | 0.7 | 5.4 |
| -25.0 | 19450 | 18778 | 20122 | 3.5 | 0.7 | 5.2 |
| -20.0 | 15034 | 14557 | 15511 | 3.2 | 0.6 | 5.1 |
| -15.0 | 11671 | 11332 | 12009 | 2.9 | 0.6 | 4.9 |
| -10.0 | 9137 | 8896 | 9378 | 2.6 | 0.5 | 4.8 |
| -5.0 | 7210 | 7038 | 7382 | 2.4 | 0.5 | 4.7 |
| 0.0 | 5733 | 5610 | 5856 | 2.1 | 0.5 | 4.5 |
| 5.0 | 4581 | 4494 | 4669 | 1.9 | 0.4 | 4.4 |
| 10.0 | 3688 | 3625 | 3750 | 1.7 | 0.4 | 4.3 |
| 15.0 | 2984 | 2940 | 3028 | 1.5 | 0.4 | 4.1 |
| 20.0 | 2431 | 2400 | 2461 | 1.3 | 0.3 | 4.0 |
| 25.0 | 2000 | 1980 | 2020 | 1.0 | 0.3 | 3.9 |
| 30.0 | 1660 | 1639 | 1680 | 1.2 | 0.3 | 3.8 |
| 35.0 | 1373 | 1353 | 1392 | 1.4 | 0.4 | 3.7 |
| 40.0 | 1142 | 1124 | 1161 | 1.6 | 0.5 | 3.6 |
| 45.0 | 960.3 | 943.0 | 977.6 | 1.8 | 0.5 | 3.5 |
| 50.0 | 810.9 | 794.9 | 826.9 | 2.0 | 0.6 | 3.4 |
| 55.0 | 683.4 | 668.8 | 698.0 | 2.1 | 0.6 | 3.3 |
| 60.0 | 579.0 | 565.7 | 592.4 | 2.3 | 0.7 | 3.2 |
| 65.0 | 494.3 | 482.1 | 506.5 | 2.5 | 0.8 | 3.1 |
| 70.0 | 423.7 | 412.6 | 434.7 | 2.6 | 0.9 | 3.1 |
| 75.0 | 363.9 | 353.8 | 373.9 | 2.8 | 0.9 | 3.0 |
| 80.0 | 313.6 | 304.5 | 322.7 | 2.9 | 1.0 | 2.9 |
| 85.0 | 271.8 | 263.5 | 280.1 | 3.1 | 1.1 | 2.8 |
| 90.0 | 236.4 | 228.9 | 244.0 | 3.2 | 1.2 | 2.8 |
| 95.0 | 206.8 | 199.9 | 213.7 | 3.3 | 1.2 | 2.7 |
| 100.0 | 181.5 | 175.2 | 187.7 | 3.4 | 1.3 | 2.6 |
| 105.0 | 159.3 | 153.6 | 165.0 | 3.6 | 1.4 | 2.6 |
| 110.0 | 140.2 | 135.0 | 145.4 | 3.7 | 1.5 | 2.5 |
| 115.0 | 123.8 | 119.1 | 128.5 | 3.8 | 1.6 | 2.4 |
| 120.0 | 109.6 | 105.3 | 113.9 | 3.9 | 1.6 | 2.4 |
| 125.0 | 97.41 | 93.47 | 101.4 | 4.0 | 1.7 | 2.3 |
| 130.0 | 86.83 | 83.22 | 90.44 | 4.2 | 1.8 | 2.3 |
| 135.0 | 77.44 | 74.14 | 80.75 | 4.3 | 1.9 | 2.2 |

| B57867S0202F140 | | | | | | |
|------------------------|--|----------------------|----------------------|--------------------------------------|---------|---------|
| R/T No. | 1008 | | | | | |
| T (°C) | B _{25/100} = 3560 K, R ₂₅ = 2000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 1% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| 140.0 | 69.23 | 66.20 | 72.26 | 4.4 | 2.0 | 2.2 |
| 145.0 | 62.10 | 59.32 | 64.88 | 4.5 | 2.1 | 2.1 |
| 150.0 | 55.82 | 53.26 | 58.37 | 4.6 | 2.2 | 2.1 |
| 155.0 | 50.39 | 48.03 | 52.74 | 4.7 | 2.3 | 2.0 |

| B57867S0202H140 | | | | | | |
|------------------------|--|----------------------|----------------------|--------------------------------------|------------|------------|
| R/T No. | 1008 | | | | | |
| T (°C) | B _{25/100} = 3560 K, R ₂₅ = 2000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 3% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -55.0 | 106210 | 98317 | 114100 | 7.4 | 1.2 | 6.1 |
| -50.0 | 78635 | 73081 | 84189 | 7.1 | 1.2 | 6.0 |
| -45.0 | 58650 | 54713 | 62588 | 6.7 | 1.2 | 5.8 |
| -40.0 | 44060 | 41250 | 46871 | 6.4 | 1.1 | 5.7 |
| -35.0 | 33333 | 31313 | 35352 | 6.1 | 1.1 | 5.5 |
| -30.0 | 25392 | 23931 | 26852 | 5.8 | 1.1 | 5.4 |
| -25.0 | 19450 | 18389 | 20511 | 5.5 | 1.0 | 5.2 |
| -20.0 | 15034 | 14256 | 15812 | 5.2 | 1.0 | 5.1 |
| -15.0 | 11671 | 11099 | 12242 | 4.9 | 1.0 | 4.9 |
| -10.0 | 9137 | 8713 | 9561 | 4.6 | 1.0 | 4.8 |
| -5.0 | 7210 | 6894 | 7526 | 4.4 | 0.9 | 4.7 |
| 0.0 | 5733 | 5495 | 5970 | 4.1 | 0.9 | 4.5 |
| 5.0 | 4581 | 4402 | 4761 | 3.9 | 0.9 | 4.4 |
| 10.0 | 3688 | 3552 | 3823 | 3.7 | 0.9 | 4.3 |
| 15.0 | 2984 | 2881 | 3087 | 3.5 | 0.8 | 4.1 |
| 20.0 | 2431 | 2352 | 2510 | 3.3 | 0.8 | 4.0 |
| 25.0 | 2000 | 1940 | 2060 | 3.0 | 0.8 | 3.9 |
| 30.0 | 1660 | 1606 | 1713 | 3.2 | 0.9 | 3.8 |
| 35.0 | 1373 | 1326 | 1420 | 3.4 | 0.9 | 3.7 |
| 40.0 | 1142 | 1101 | 1183 | 3.6 | 1.0 | 3.6 |
| 45.0 | 960.3 | 923.8 | 996.8 | 3.8 | 1.1 | 3.5 |
| 50.0 | 810.9 | 778.7 | 843.1 | 4.0 | 1.2 | 3.4 |
| 55.0 | 683.4 | 655.1 | 711.7 | 4.1 | 1.2 | 3.3 |
| 60.0 | 579.0 | 554.1 | 604.0 | 4.3 | 1.3 | 3.2 |
| 65.0 | 494.3 | 472.2 | 516.3 | 4.5 | 1.4 | 3.1 |
| 70.0 | 423.7 | 404.1 | 443.2 | 4.6 | 1.5 | 3.1 |
| 75.0 | 363.9 | 346.5 | 381.2 | 4.8 | 1.6 | 3.0 |
| 80.0 | 313.6 | 298.2 | 329.0 | 4.9 | 1.7 | 2.9 |
| 85.0 | 271.8 | 258.1 | 285.6 | 5.1 | 1.8 | 2.8 |
| 90.0 | 236.4 | 224.2 | 248.7 | 5.2 | 1.9 | 2.8 |

| B57867S0202H140 | | | | | | |
|------------------------|---|--------------------------|--------------------------|-------------------------|-------------------------------|-----------------|
| R/T No. | 1008 | | | | | |
| T (°C) | $B_{25/100} = 3560 \text{ K}$, $R_{25} = 2000 \text{ } \Omega$, $T_R = 25 \text{ } ^\circ\text{C}$, $\Delta R_R/R_R = \pm 3\%$ | | | | | |
| | $R_{\text{nom}}[\Omega]$ | $R_{\text{min}}[\Omega]$ | $R_{\text{max}}[\Omega]$ | $\Delta R_R/R_R[\pm\%]$ | $\Delta T[\pm^\circ\text{C}]$ | $\alpha (\%/K)$ |
| 95.0 | 206.8 | 195.8 | 217.8 | 5.3 | 2.0 | 2.7 |
| 100.0 | 181.5 | 171.6 | 191.4 | 5.4 | 2.1 | 2.6 |
| 105.0 | 159.3 | 150.4 | 168.2 | 5.6 | 2.2 | 2.6 |
| 110.0 | 140.2 | 132.2 | 148.2 | 5.7 | 2.3 | 2.5 |
| 115.0 | 123.8 | 116.6 | 131.0 | 5.8 | 2.4 | 2.4 |
| 120.0 | 109.6 | 103.1 | 116.1 | 5.9 | 2.5 | 2.4 |
| 125.0 | 97.41 | 91.52 | 103.3 | 6.0 | 2.6 | 2.3 |
| 130.0 | 86.83 | 81.48 | 92.18 | 6.2 | 2.7 | 2.3 |
| 135.0 | 77.44 | 72.59 | 82.30 | 6.3 | 2.8 | 2.2 |
| 140.0 | 69.23 | 64.82 | 73.64 | 6.4 | 2.9 | 2.2 |
| 145.0 | 62.10 | 58.07 | 66.12 | 6.5 | 3.0 | 2.1 |
| 150.0 | 55.82 | 52.15 | 59.49 | 6.6 | 3.2 | 2.1 |
| 155.0 | 50.39 | 47.02 | 53.75 | 6.7 | 3.3 | 2.0 |

| B57867S0202J140 | | | | | | |
|------------------------|---|--------------------------|--------------------------|-------------------------|-------------------------------|-----------------|
| R/T No. | 1008 | | | | | |
| T (°C) | $B_{25/100} = 3560 \text{ K}$, $R_{25} = 2000 \text{ } \Omega$, $T_R = 25 \text{ } ^\circ\text{C}$, $\Delta R_R/R_R = \pm 5\%$ | | | | | |
| | $R_{\text{nom}}[\Omega]$ | $R_{\text{min}}[\Omega]$ | $R_{\text{max}}[\Omega]$ | $\Delta R_R/R_R[\pm\%]$ | $\Delta T[\pm^\circ\text{C}]$ | $\alpha (\%/K)$ |
| -55.0 | 106210 | 96193 | 116220 | 9.4 | 1.5 | 6.1 |
| -50.0 | 78635 | 71508 | 85762 | 9.1 | 1.5 | 6.0 |
| -45.0 | 58650 | 53540 | 63761 | 8.7 | 1.5 | 5.8 |
| -40.0 | 44060 | 40368 | 47752 | 8.4 | 1.5 | 5.7 |
| -35.0 | 33333 | 30647 | 36019 | 8.1 | 1.5 | 5.5 |
| -30.0 | 25392 | 23424 | 27360 | 7.8 | 1.4 | 5.4 |
| -25.0 | 19450 | 18000 | 20900 | 7.5 | 1.4 | 5.2 |
| -20.0 | 15034 | 13956 | 16112 | 7.2 | 1.4 | 5.1 |
| -15.0 | 11671 | 10865 | 12476 | 6.9 | 1.4 | 4.9 |
| -10.0 | 9137 | 8531 | 9744 | 6.6 | 1.4 | 4.8 |
| -5.0 | 7210 | 6750 | 7670 | 6.4 | 1.4 | 4.7 |
| 0.0 | 5733 | 5381 | 6085 | 6.1 | 1.4 | 4.5 |
| 5.0 | 4581 | 4311 | 4852 | 5.9 | 1.3 | 4.4 |
| 10.0 | 3688 | 3478 | 3897 | 5.7 | 1.3 | 4.3 |
| 15.0 | 2984 | 2821 | 3147 | 5.5 | 1.3 | 4.1 |
| 20.0 | 2431 | 2303 | 2559 | 5.3 | 1.3 | 4.0 |
| 25.0 | 2000 | 1900 | 2100 | 5.0 | 1.3 | 3.9 |
| 30.0 | 1660 | 1572 | 1747 | 5.2 | 1.4 | 3.8 |
| 35.0 | 1373 | 1298 | 1447 | 5.4 | 1.5 | 3.7 |
| 40.0 | 1142 | 1078 | 1206 | 5.6 | 1.6 | 3.6 |
| 45.0 | 960.3 | 904.6 | 1016 | 5.8 | 1.7 | 3.5 |

| B57867S0202J140 | | | | | | |
|------------------------|--|----------------------|----------------------|--------------------------------------|---------|---------|
| R/T No. | 1008 | | | | | |
| T (°C) | B _{25/100} = 3560 K, R ₂₅ = 2000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 5% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| 50.0 | 810.9 | 762.5 | 859.3 | 6.0 | 1.8 | 3.4 |
| 55.0 | 683.4 | 641.4 | 725.4 | 6.1 | 1.9 | 3.3 |
| 60.0 | 579.0 | 542.5 | 615.5 | 6.3 | 2.0 | 3.2 |
| 65.0 | 494.3 | 462.3 | 526.2 | 6.5 | 2.1 | 3.1 |
| 70.0 | 423.7 | 395.6 | 451.7 | 6.6 | 2.2 | 3.1 |
| 75.0 | 363.9 | 339.3 | 388.5 | 6.8 | 2.3 | 3.0 |
| 80.0 | 313.6 | 291.9 | 335.3 | 6.9 | 2.4 | 2.9 |
| 85.0 | 271.8 | 252.7 | 291.0 | 7.1 | 2.5 | 2.8 |
| 90.0 | 236.4 | 219.5 | 253.4 | 7.2 | 2.6 | 2.8 |
| 95.0 | 206.8 | 191.7 | 221.9 | 7.3 | 2.7 | 2.7 |
| 100.0 | 181.5 | 168.0 | 195.0 | 7.4 | 2.8 | 2.6 |
| 105.0 | 159.3 | 147.2 | 171.4 | 7.6 | 3.0 | 2.6 |
| 110.0 | 140.2 | 129.4 | 151.0 | 7.7 | 3.1 | 2.5 |
| 115.0 | 123.8 | 114.1 | 133.5 | 7.8 | 3.2 | 2.4 |
| 120.0 | 109.6 | 100.9 | 118.3 | 7.9 | 3.3 | 2.4 |
| 125.0 | 97.41 | 89.57 | 105.3 | 8.0 | 3.4 | 2.3 |
| 130.0 | 86.83 | 79.74 | 93.91 | 8.2 | 3.6 | 2.3 |
| 135.0 | 77.44 | 71.04 | 83.85 | 8.3 | 3.7 | 2.2 |
| 140.0 | 69.23 | 63.43 | 75.03 | 8.4 | 3.8 | 2.2 |
| 145.0 | 62.10 | 56.83 | 67.36 | 8.5 | 4.0 | 2.1 |
| 150.0 | 55.82 | 51.03 | 60.61 | 8.6 | 4.1 | 2.1 |
| 155.0 | 50.39 | 46.02 | 54.76 | 8.7 | 4.3 | 2.0 |

| B57867S0302F140 | | | | | | |
|------------------------|--|----------------------|----------------------|--------------------------------------|---------|---------|
| R/T No. | 8016 | | | | | |
| T (°C) | B _{25/100} = 3988 K, R ₂₅ = 3000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 1% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -55.0 | 288910 | 271710 | 306120 | 6.0 | 0.8 | 7.4 |
| -50.0 | 201030 | 189880 | 212180 | 5.5 | 0.8 | 7.1 |
| -45.0 | 141510 | 134210 | 148800 | 5.2 | 0.7 | 6.9 |
| -40.0 | 100950 | 96126 | 105770 | 4.8 | 0.7 | 6.7 |
| -35.0 | 72777 | 69560 | 75993 | 4.4 | 0.7 | 6.4 |
| -30.0 | 53100 | 50936 | 55264 | 4.1 | 0.7 | 6.2 |
| -25.0 | 39111 | 37646 | 40576 | 3.7 | 0.6 | 6.0 |
| -20.0 | 29121 | 28123 | 30119 | 3.4 | 0.6 | 5.8 |
| -15.0 | 21879 | 21196 | 22562 | 3.1 | 0.6 | 5.6 |
| -10.0 | 16599 | 16129 | 17069 | 2.8 | 0.5 | 5.4 |
| -5.0 | 12695 | 12371 | 13018 | 2.5 | 0.5 | 5.3 |
| 0.0 | 9795 | 9572 | 10018 | 2.3 | 0.4 | 5.1 |

| B57867S0302F140 | | | | | | |
|------------------------|--|---------------------------|---------------------------|-------------------------|-------------------------------|-----------------|
| R/T No. | 8016 | | | | | |
| T (°C) | $B_{25/100} = 3988 \text{ K}, R_{25} = 3000 \text{ } \Omega, T_R = 25 \text{ } ^\circ\text{C}, \Delta R_R/R_R = \pm 1\%$ | | | | | |
| | $R_{\text{nomL}}[\Omega]$ | $R_{\text{minL}}[\Omega]$ | $R_{\text{maxL}}[\Omega]$ | $\Delta R_R/R_R[\pm\%]$ | $\Delta T[\pm^\circ\text{C}]$ | $\alpha (\%/K)$ |
| 5.0 | 7616 | 7463 | 7769 | 2.0 | 0.4 | 5.0 |
| 10.0 | 5970 | 5865 | 6075 | 1.8 | 0.4 | 4.8 |
| 15.0 | 4712 | 4641 | 4784 | 1.5 | 0.3 | 4.7 |
| 20.0 | 3747 | 3699 | 3795 | 1.3 | 0.3 | 4.5 |
| 25.0 | 3000 | 2970 | 3030 | 1.0 | 0.2 | 4.4 |
| 30.0 | 2417 | 2386 | 2448 | 1.3 | 0.3 | 4.3 |
| 35.0 | 1959 | 1930 | 1988 | 1.5 | 0.4 | 4.1 |
| 40.0 | 1598 | 1571 | 1625 | 1.7 | 0.4 | 4.0 |
| 45.0 | 1311 | 1286 | 1335 | 1.9 | 0.5 | 3.9 |
| 50.0 | 1081 | 1058 | 1103 | 2.1 | 0.5 | 3.8 |
| 55.0 | 895.9 | 875.5 | 916.2 | 2.3 | 0.6 | 3.7 |
| 60.0 | 746.4 | 728.1 | 764.7 | 2.5 | 0.7 | 3.6 |
| 65.0 | 624.9 | 608.5 | 641.4 | 2.6 | 0.8 | 3.5 |
| 70.0 | 525.6 | 510.9 | 540.3 | 2.8 | 0.8 | 3.4 |
| 75.0 | 444.4 | 431.2 | 457.6 | 3.0 | 0.9 | 3.3 |
| 80.0 | 377.4 | 365.6 | 389.2 | 3.1 | 1.0 | 3.2 |
| 85.0 | 321.7 | 311.1 | 332.3 | 3.3 | 1.0 | 3.2 |
| 90.0 | 275.3 | 265.8 | 284.8 | 3.4 | 1.1 | 3.1 |
| 95.0 | 236.6 | 228.1 | 245.1 | 3.6 | 1.2 | 3.0 |
| 100.0 | 204.0 | 196.4 | 211.6 | 3.7 | 1.3 | 2.9 |
| 105.0 | 176.6 | 169.7 | 183.4 | 3.9 | 1.4 | 2.9 |
| 110.0 | 153.4 | 147.2 | 159.5 | 4.0 | 1.4 | 2.8 |
| 115.0 | 133.6 | 128.1 | 139.2 | 4.2 | 1.5 | 2.7 |
| 120.0 | 116.8 | 111.8 | 121.8 | 4.3 | 1.6 | 2.7 |
| 125.0 | 102.5 | 97.99 | 107.0 | 4.4 | 1.7 | 2.6 |
| 130.0 | 90.27 | 86.18 | 94.36 | 4.5 | 1.8 | 2.5 |
| 135.0 | 79.63 | 75.93 | 83.34 | 4.7 | 1.9 | 2.5 |
| 140.0 | 70.44 | 67.08 | 73.80 | 4.8 | 2.0 | 2.4 |
| 145.0 | 62.50 | 59.44 | 65.55 | 4.9 | 2.1 | 2.4 |
| 150.0 | 55.59 | 52.81 | 58.37 | 5.0 | 2.2 | 2.3 |
| 155.0 | 49.60 | 47.07 | 52.14 | 5.1 | 2.3 | 2.3 |

| B57867S0302H140 | | | | | | |
|------------------------|--|---------------------------|---------------------------|-------------------------|-------------------------------|-----------------|
| R/T No. | 8016 | | | | | |
| T (°C) | $B_{25/100} = 3988 \text{ K}, R_{25} = 3000 \text{ } \Omega, T_R = 25 \text{ } ^\circ\text{C}, \Delta R_R/R_R = \pm 3\%$ | | | | | |
| | $R_{\text{nomL}}[\Omega]$ | $R_{\text{minL}}[\Omega]$ | $R_{\text{maxL}}[\Omega]$ | $\Delta R_R/R_R[\pm\%]$ | $\Delta T[\pm^\circ\text{C}]$ | $\alpha (\%/K)$ |
| -55.0 | 288910 | 265930 | 311900 | 8.0 | 1.1 | 7.4 |
| -50.0 | 201030 | 185860 | 216200 | 7.5 | 1.1 | 7.1 |
| -45.0 | 141510 | 131380 | 151630 | 7.2 | 1.0 | 6.9 |

| B57867S0302H140 | | | | | | |
|------------------------|--|----------------------|----------------------|--------------------------------------|------------|------------|
| R/T No. | 8016 | | | | | |
| T (°C) | B _{25/100} = 3988 K, R ₂₅ = 3000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 3% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -40.0 | 100950 | 94107 | 107790 | 6.8 | 1.0 | 6.7 |
| -35.0 | 72777 | 68105 | 77449 | 6.4 | 1.0 | 6.4 |
| -30.0 | 53100 | 49874 | 56326 | 6.1 | 1.0 | 6.2 |
| -25.0 | 39111 | 36864 | 41358 | 5.7 | 1.0 | 6.0 |
| -20.0 | 29121 | 27540 | 30702 | 5.4 | 0.9 | 5.8 |
| -15.0 | 21879 | 20758 | 22999 | 5.1 | 0.9 | 5.6 |
| -10.0 | 16599 | 15797 | 17401 | 4.8 | 0.9 | 5.4 |
| -5.0 | 12695 | 12117 | 13272 | 4.5 | 0.9 | 5.3 |
| 0.0 | 9795 | 9376 | 10214 | 4.3 | 0.8 | 5.1 |
| 5.0 | 7616 | 7311 | 7922 | 4.0 | 0.8 | 5.0 |
| 10.0 | 5970 | 5746 | 6194 | 3.8 | 0.8 | 4.8 |
| 15.0 | 4712 | 4547 | 4878 | 3.5 | 0.8 | 4.7 |
| 20.0 | 3747 | 3624 | 3870 | 3.3 | 0.7 | 4.5 |
| 25.0 | 3000 | 2910 | 3090 | 3.0 | 0.7 | 4.4 |
| 30.0 | 2417 | 2338 | 2496 | 3.3 | 0.8 | 4.3 |
| 35.0 | 1959 | 1891 | 2028 | 3.5 | 0.8 | 4.1 |
| 40.0 | 1598 | 1539 | 1657 | 3.7 | 0.9 | 4.0 |
| 45.0 | 1311 | 1260 | 1362 | 3.9 | 1.0 | 3.9 |
| 50.0 | 1081 | 1037 | 1125 | 4.1 | 1.1 | 3.8 |
| 55.0 | 895.9 | 857.6 | 934.1 | 4.3 | 1.2 | 3.7 |
| 60.0 | 746.4 | 713.1 | 779.7 | 4.5 | 1.2 | 3.6 |
| 65.0 | 624.9 | 596.0 | 653.9 | 4.6 | 1.3 | 3.5 |
| 70.0 | 525.6 | 500.3 | 550.9 | 4.8 | 1.4 | 3.4 |
| 75.0 | 444.4 | 422.3 | 466.5 | 5.0 | 1.5 | 3.3 |
| 80.0 | 377.4 | 358.0 | 396.8 | 5.1 | 1.6 | 3.2 |
| 85.0 | 321.7 | 304.7 | 338.7 | 5.3 | 1.7 | 3.2 |
| 90.0 | 275.3 | 260.3 | 290.3 | 5.4 | 1.8 | 3.1 |
| 95.0 | 236.6 | 223.3 | 249.8 | 5.6 | 1.9 | 3.0 |
| 100.0 | 204.0 | 192.3 | 215.7 | 5.7 | 2.0 | 2.9 |
| 105.0 | 176.6 | 166.2 | 187.0 | 5.9 | 2.1 | 2.9 |
| 110.0 | 153.4 | 144.1 | 162.6 | 6.0 | 2.2 | 2.8 |
| 115.0 | 133.6 | 125.4 | 141.8 | 6.2 | 2.3 | 2.7 |
| 120.0 | 116.8 | 109.5 | 124.1 | 6.3 | 2.4 | 2.7 |
| 125.0 | 102.5 | 95.94 | 109.1 | 6.4 | 2.5 | 2.6 |
| 130.0 | 90.27 | 84.37 | 96.17 | 6.5 | 2.6 | 2.5 |
| 135.0 | 79.63 | 74.33 | 84.93 | 6.7 | 2.7 | 2.5 |
| 140.0 | 70.44 | 65.67 | 75.21 | 6.8 | 2.8 | 2.4 |
| 145.0 | 62.50 | 58.19 | 66.80 | 6.9 | 2.9 | 2.4 |
| 150.0 | 55.59 | 51.70 | 59.48 | 7.0 | 3.0 | 2.3 |
| 155.0 | 49.60 | 46.08 | 53.13 | 7.1 | 3.1 | 2.3 |

| B57867S0302J140 | | | | | | |
|------------------------|--|----------------------|----------------------|--------------------------------------|------------|------------|
| R/T No. | 8016 | | | | | |
| T (°C) | B _{25/100} = 3988 K, R ₂₅ = 3000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 5% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -55.0 | 288910 | 260150 | 317680 | 10.0 | 1.3 | 7.4 |
| -50.0 | 201030 | 181840 | 220220 | 9.5 | 1.3 | 7.1 |
| -45.0 | 141510 | 128550 | 154460 | 9.2 | 1.3 | 6.9 |
| -40.0 | 100950 | 92088 | 109810 | 8.8 | 1.3 | 6.7 |
| -35.0 | 72777 | 66649 | 78905 | 8.4 | 1.3 | 6.4 |
| -30.0 | 53100 | 48812 | 57388 | 8.1 | 1.3 | 6.2 |
| -25.0 | 39111 | 36082 | 42140 | 7.7 | 1.3 | 6.0 |
| -20.0 | 29121 | 26958 | 31284 | 7.4 | 1.3 | 5.8 |
| -15.0 | 21879 | 20320 | 23437 | 7.1 | 1.3 | 5.6 |
| -10.0 | 16599 | 15465 | 17733 | 6.8 | 1.3 | 5.4 |
| -5.0 | 12695 | 11863 | 13526 | 6.5 | 1.2 | 5.3 |
| 0.0 | 9795 | 9180 | 10410 | 6.3 | 1.2 | 5.1 |
| 5.0 | 7616 | 7158 | 8074 | 6.0 | 1.2 | 5.0 |
| 10.0 | 5970 | 5626 | 6314 | 5.8 | 1.2 | 4.8 |
| 15.0 | 4712 | 4452 | 4972 | 5.5 | 1.2 | 4.7 |
| 20.0 | 3747 | 3549 | 3945 | 5.3 | 1.2 | 4.5 |
| 25.0 | 3000 | 2850 | 3150 | 5.0 | 1.1 | 4.4 |
| 30.0 | 2417 | 2290 | 2544 | 5.3 | 1.2 | 4.3 |
| 35.0 | 1959 | 1852 | 2067 | 5.5 | 1.3 | 4.1 |
| 40.0 | 1598 | 1507 | 1689 | 5.7 | 1.4 | 4.0 |
| 45.0 | 1311 | 1233 | 1388 | 5.9 | 1.5 | 3.9 |
| 50.0 | 1081 | 1015 | 1147 | 6.1 | 1.6 | 3.8 |
| 55.0 | 895.9 | 839.7 | 952.1 | 6.3 | 1.7 | 3.7 |
| 60.0 | 746.4 | 698.2 | 794.6 | 6.5 | 1.8 | 3.6 |
| 65.0 | 624.9 | 583.5 | 666.4 | 6.6 | 1.9 | 3.5 |
| 70.0 | 525.6 | 489.8 | 561.4 | 6.8 | 2.0 | 3.4 |
| 75.0 | 444.4 | 413.4 | 475.4 | 7.0 | 2.1 | 3.3 |
| 80.0 | 377.4 | 350.5 | 404.3 | 7.1 | 2.2 | 3.2 |
| 85.0 | 321.7 | 298.2 | 345.2 | 7.3 | 2.3 | 3.2 |
| 90.0 | 275.3 | 254.8 | 295.8 | 7.4 | 2.4 | 3.1 |
| 95.0 | 236.6 | 218.6 | 254.5 | 7.6 | 2.5 | 3.0 |
| 100.0 | 204.0 | 188.2 | 219.8 | 7.7 | 2.6 | 2.9 |
| 105.0 | 176.6 | 162.7 | 190.5 | 7.9 | 2.8 | 2.9 |
| 110.0 | 153.4 | 141.1 | 165.7 | 8.0 | 2.9 | 2.8 |
| 115.0 | 133.6 | 122.7 | 144.5 | 8.2 | 3.0 | 2.7 |
| 120.0 | 116.8 | 107.1 | 126.5 | 8.3 | 3.1 | 2.7 |
| 125.0 | 102.5 | 93.89 | 111.1 | 8.4 | 3.2 | 2.6 |
| 130.0 | 90.27 | 82.57 | 97.97 | 8.5 | 3.4 | 2.5 |
| 135.0 | 79.63 | 72.74 | 86.52 | 8.7 | 3.5 | 2.5 |

| B57867S0302J140 | | | | | | |
|------------------------|--|----------------------|----------------------|--------------------------------------|---------|---------|
| R/T No. | 8016 | | | | | |
| T (°C) | B _{25/100} = 3988 K, R ₂₅ = 3000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 5% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| 140.0 | 70.44 | 64.26 | 76.62 | 8.8 | 3.6 | 2.4 |
| 145.0 | 62.50 | 56.94 | 68.05 | 8.9 | 3.8 | 2.4 |
| 150.0 | 55.59 | 50.59 | 60.59 | 9.0 | 3.9 | 2.3 |
| 155.0 | 49.60 | 45.08 | 54.12 | 9.1 | 4.0 | 2.3 |

| B57867S0502F140 | | | | | | |
|------------------------|--|----------------------|----------------------|--------------------------------------|------------|------------|
| R/T No. | 8016 | | | | | |
| T (°C) | B _{25/100} = 3988 K, R ₂₅ = 5000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 1% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -55.0 | 481520 | 452850 | 510200 | 6.0 | 0.8 | 7.4 |
| -50.0 | 335050 | 316470 | 353630 | 5.5 | 0.8 | 7.1 |
| -45.0 | 235840 | 223690 | 248000 | 5.2 | 0.7 | 6.9 |
| -40.0 | 168250 | 160210 | 176290 | 4.8 | 0.7 | 6.7 |
| -35.0 | 121300 | 115930 | 126660 | 4.4 | 0.7 | 6.4 |
| -30.0 | 88500 | 84893 | 92107 | 4.1 | 0.7 | 6.2 |
| -25.0 | 65185 | 62744 | 67626 | 3.7 | 0.6 | 6.0 |
| -20.0 | 48535 | 46871 | 50199 | 3.4 | 0.6 | 5.8 |
| -15.0 | 36465 | 35326 | 37603 | 3.1 | 0.6 | 5.6 |
| -10.0 | 27665 | 26882 | 28448 | 2.8 | 0.5 | 5.4 |
| -5.0 | 21158 | 20619 | 21696 | 2.5 | 0.5 | 5.3 |
| 0.0 | 16325 | 15954 | 16696 | 2.3 | 0.4 | 5.1 |
| 5.0 | 12694 | 12438 | 12949 | 2.0 | 0.4 | 5.0 |
| 10.0 | 9950 | 9775 | 10125 | 1.8 | 0.4 | 4.8 |
| 15.0 | 7854 | 7735 | 7973 | 1.5 | 0.3 | 4.7 |
| 20.0 | 6245 | 6165 | 6325 | 1.3 | 0.3 | 4.5 |
| 25.0 | 5000 | 4950 | 5050 | 1.0 | 0.2 | 4.4 |
| 30.0 | 4029 | 3977 | 4080 | 1.3 | 0.3 | 4.3 |
| 35.0 | 3266 | 3217 | 3314 | 1.5 | 0.4 | 4.1 |
| 40.0 | 2664 | 2618 | 2709 | 1.7 | 0.4 | 4.0 |
| 45.0 | 2184 | 2143 | 2226 | 1.9 | 0.5 | 3.9 |
| 50.0 | 1802 | 1764 | 1839 | 2.1 | 0.5 | 3.8 |
| 55.0 | 1493 | 1459 | 1527 | 2.3 | 0.6 | 3.7 |
| 60.0 | 1244 | 1213 | 1275 | 2.5 | 0.7 | 3.6 |
| 65.0 | 1042 | 1014 | 1069 | 2.6 | 0.8 | 3.5 |
| 70.0 | 876.0 | 851.4 | 900.6 | 2.8 | 0.8 | 3.4 |
| 75.0 | 740.7 | 718.7 | 762.7 | 3.0 | 0.9 | 3.3 |
| 80.0 | 629.0 | 609.3 | 648.7 | 3.1 | 1.0 | 3.2 |
| 85.0 | 536.2 | 518.5 | 553.8 | 3.3 | 1.0 | 3.2 |
| 90.0 | 458.8 | 443.0 | 474.7 | 3.4 | 1.1 | 3.1 |

| B57867S0502F140 | | | | | | |
|------------------------|---|--------------------------|--------------------------|-------------------------|--------------------------|-----------------|
| R/T No. | 8016 | | | | | |
| T (°C) | $B_{25/100} = 3988 \text{ K}$, $R_{25} = 5000 \Omega$, $T_R = 25 \text{ °C}$, $\Delta R_R/R_R = \pm 1\%$ | | | | | |
| | $R_{\text{nom}}[\Omega]$ | $R_{\text{min}}[\Omega]$ | $R_{\text{max}}[\Omega]$ | $\Delta R_R/R_R[\pm\%]$ | $\Delta T[\pm\text{°C}]$ | $\alpha (\%/K)$ |
| 95.0 | 394.3 | 380.1 | 408.4 | 3.6 | 1.2 | 3.0 |
| 100.0 | 340.0 | 327.3 | 352.7 | 3.7 | 1.3 | 2.9 |
| 105.0 | 294.3 | 282.9 | 305.7 | 3.9 | 1.4 | 2.9 |
| 110.0 | 255.6 | 245.3 | 265.9 | 4.0 | 1.4 | 2.8 |
| 115.0 | 222.7 | 213.5 | 231.9 | 4.2 | 1.5 | 2.7 |
| 120.0 | 194.7 | 186.3 | 203.0 | 4.3 | 1.6 | 2.7 |
| 125.0 | 170.9 | 163.3 | 178.4 | 4.4 | 1.7 | 2.6 |
| 130.0 | 150.5 | 143.6 | 157.3 | 4.5 | 1.8 | 2.5 |
| 135.0 | 132.7 | 126.5 | 138.9 | 4.7 | 1.9 | 2.5 |
| 140.0 | 117.4 | 111.8 | 123.0 | 4.8 | 2.0 | 2.4 |
| 145.0 | 104.2 | 99.07 | 109.3 | 4.9 | 2.1 | 2.4 |
| 150.0 | 92.65 | 88.02 | 97.28 | 5.0 | 2.2 | 2.3 |
| 155.0 | 82.67 | 78.45 | 86.90 | 5.1 | 2.3 | 2.3 |

| B57867S0502H140 | | | | | | |
|------------------------|---|--------------------------|--------------------------|-------------------------|--------------------------|-----------------|
| R/T No. | 8016 | | | | | |
| T (°C) | $B_{25/100} = 3988 \text{ K}$, $R_{25} = 5000 \Omega$, $T_R = 25 \text{ °C}$, $\Delta R_R/R_R = \pm 3\%$ | | | | | |
| | $R_{\text{nom}}[\Omega]$ | $R_{\text{min}}[\Omega]$ | $R_{\text{max}}[\Omega]$ | $\Delta R_R/R_R[\pm\%]$ | $\Delta T[\pm\text{°C}]$ | $\alpha (\%/K)$ |
| -55.0 | 481520 | 443220 | 519830 | 8.0 | 1.1 | 7.4 |
| -50.0 | 335050 | 309770 | 360330 | 7.5 | 1.1 | 7.1 |
| -45.0 | 235840 | 218970 | 252720 | 7.2 | 1.0 | 6.9 |
| -40.0 | 168250 | 156840 | 179660 | 6.8 | 1.0 | 6.7 |
| -35.0 | 121300 | 113510 | 129080 | 6.4 | 1.0 | 6.4 |
| -30.0 | 88500 | 83123 | 93877 | 6.1 | 1.0 | 6.2 |
| -25.0 | 65185 | 61440 | 68930 | 5.7 | 1.0 | 6.0 |
| -20.0 | 48535 | 45901 | 51169 | 5.4 | 0.9 | 5.8 |
| -15.0 | 36465 | 34597 | 38332 | 5.1 | 0.9 | 5.6 |
| -10.0 | 27665 | 26329 | 29001 | 4.8 | 0.9 | 5.4 |
| -5.0 | 21158 | 20196 | 22119 | 4.5 | 0.9 | 5.3 |
| 0.0 | 16325 | 15627 | 17023 | 4.3 | 0.8 | 5.1 |
| 5.0 | 12694 | 12185 | 13203 | 4.0 | 0.8 | 5.0 |
| 10.0 | 9950 | 9576 | 10324 | 3.8 | 0.8 | 4.8 |
| 15.0 | 7854 | 7578 | 8130 | 3.5 | 0.8 | 4.7 |
| 20.0 | 6245 | 6040 | 6450 | 3.3 | 0.7 | 4.5 |
| 25.0 | 5000 | 4850 | 5150 | 3.0 | 0.7 | 4.4 |
| 30.0 | 4029 | 3897 | 4160 | 3.3 | 0.8 | 4.3 |
| 35.0 | 3266 | 3152 | 3379 | 3.5 | 0.8 | 4.1 |
| 40.0 | 2664 | 2565 | 2762 | 3.7 | 0.9 | 4.0 |
| 45.0 | 2184 | 2099 | 2269 | 3.9 | 1.0 | 3.9 |

| B57867S0502H140 | | | | | | |
|------------------------|--|----------------------|----------------------|--------------------------------------|---------|---------|
| R/T No. | 8016 | | | | | |
| T (°C) | B _{25/100} = 3988 K, R ₂₅ = 5000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 3% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| 50.0 | 1802 | 1728 | 1875 | 4.1 | 1.1 | 3.8 |
| 55.0 | 1493 | 1429 | 1557 | 4.3 | 1.2 | 3.7 |
| 60.0 | 1244 | 1189 | 1299 | 4.5 | 1.2 | 3.6 |
| 65.0 | 1042 | 993.3 | 1090 | 4.6 | 1.3 | 3.5 |
| 70.0 | 876.0 | 833.9 | 918.1 | 4.8 | 1.4 | 3.4 |
| 75.0 | 740.7 | 703.9 | 777.5 | 5.0 | 1.5 | 3.3 |
| 80.0 | 629.0 | 596.7 | 661.3 | 5.1 | 1.6 | 3.2 |
| 85.0 | 536.2 | 507.8 | 564.5 | 5.3 | 1.7 | 3.2 |
| 90.0 | 458.8 | 433.9 | 483.8 | 5.4 | 1.8 | 3.1 |
| 95.0 | 394.3 | 372.2 | 416.3 | 5.6 | 1.9 | 3.0 |
| 100.0 | 340.0 | 320.5 | 359.5 | 5.7 | 2.0 | 2.9 |
| 105.0 | 294.3 | 277.0 | 311.6 | 5.9 | 2.1 | 2.9 |
| 110.0 | 255.6 | 240.2 | 271.0 | 6.0 | 2.2 | 2.8 |
| 115.0 | 222.7 | 209.0 | 236.4 | 6.2 | 2.3 | 2.7 |
| 120.0 | 194.7 | 182.4 | 206.9 | 6.3 | 2.4 | 2.7 |
| 125.0 | 170.9 | 159.9 | 181.8 | 6.4 | 2.5 | 2.6 |
| 130.0 | 150.5 | 140.6 | 160.3 | 6.5 | 2.6 | 2.5 |
| 135.0 | 132.7 | 123.9 | 141.6 | 6.7 | 2.7 | 2.5 |
| 140.0 | 117.4 | 109.4 | 125.4 | 6.8 | 2.8 | 2.4 |
| 145.0 | 104.2 | 96.99 | 111.3 | 6.9 | 2.9 | 2.4 |
| 150.0 | 92.65 | 86.16 | 99.14 | 7.0 | 3.0 | 2.3 |
| 155.0 | 82.67 | 76.79 | 88.55 | 7.1 | 3.1 | 2.3 |

| B57867S0502J140 | | | | | | |
|------------------------|--|----------------------|----------------------|--------------------------------------|---------|---------|
| R/T No. | 8016 | | | | | |
| T (°C) | B _{25/100} = 3988 K, R ₂₅ = 5000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 5% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -55.0 | 481520 | 433590 | 529460 | 10.0 | 1.3 | 7.4 |
| -50.0 | 335050 | 303070 | 367030 | 9.5 | 1.3 | 7.1 |
| -45.0 | 235840 | 214260 | 257430 | 9.2 | 1.3 | 6.9 |
| -40.0 | 168250 | 153480 | 183020 | 8.8 | 1.3 | 6.7 |
| -35.0 | 121300 | 111080 | 131510 | 8.4 | 1.3 | 6.4 |
| -30.0 | 88500 | 81353 | 95647 | 8.1 | 1.3 | 6.2 |
| -25.0 | 65185 | 60136 | 70234 | 7.7 | 1.3 | 6.0 |
| -20.0 | 48535 | 44930 | 52140 | 7.4 | 1.3 | 5.8 |
| -15.0 | 36465 | 33867 | 39062 | 7.1 | 1.3 | 5.6 |
| -10.0 | 27665 | 25776 | 29554 | 6.8 | 1.3 | 5.4 |
| -5.0 | 21158 | 19772 | 22543 | 6.5 | 1.2 | 5.3 |
| 0.0 | 16325 | 15301 | 17349 | 6.3 | 1.2 | 5.1 |

| B57867S0502J140 | | | | | | |
|------------------------|---|--------------------------|--------------------------|-------------------------|-------------------------------|-----------------|
| R/T No. | 8016 | | | | | |
| T (°C) | $B_{25/100} = 3988 \text{ K}$, $R_{25} = 5000 \text{ } \Omega$, $T_R = 25 \text{ } ^\circ\text{C}$, $\Delta R_R/R_R = \pm 5\%$ | | | | | |
| | $R_{\text{nom}}[\Omega]$ | $R_{\text{min}}[\Omega]$ | $R_{\text{max}}[\Omega]$ | $\Delta R_R/R_R[\pm\%]$ | $\Delta T[\pm^\circ\text{C}]$ | $\alpha (\%/K)$ |
| 5.0 | 12694 | 11931 | 13457 | 6.0 | 1.2 | 5.0 |
| 10.0 | 9950 | 9377 | 10523 | 5.8 | 1.2 | 4.8 |
| 15.0 | 7854 | 7421 | 8287 | 5.5 | 1.2 | 4.7 |
| 20.0 | 6245 | 5915 | 6575 | 5.3 | 1.2 | 4.5 |
| 25.0 | 5000 | 4750 | 5250 | 5.0 | 1.1 | 4.4 |
| 30.0 | 4029 | 3816 | 4241 | 5.3 | 1.2 | 4.3 |
| 35.0 | 3266 | 3087 | 3445 | 5.5 | 1.3 | 4.1 |
| 40.0 | 2664 | 2512 | 2815 | 5.7 | 1.4 | 4.0 |
| 45.0 | 2184 | 2056 | 2313 | 5.9 | 1.5 | 3.9 |
| 50.0 | 1802 | 1692 | 1911 | 6.1 | 1.6 | 3.8 |
| 55.0 | 1493 | 1399 | 1587 | 6.3 | 1.7 | 3.7 |
| 60.0 | 1244 | 1164 | 1324 | 6.5 | 1.8 | 3.6 |
| 65.0 | 1042 | 972.4 | 1111 | 6.6 | 1.9 | 3.5 |
| 70.0 | 876.0 | 816.4 | 935.6 | 6.8 | 2.0 | 3.4 |
| 75.0 | 740.7 | 689.1 | 792.3 | 7.0 | 2.1 | 3.3 |
| 80.0 | 629.0 | 584.1 | 673.9 | 7.1 | 2.2 | 3.2 |
| 85.0 | 536.2 | 497.1 | 575.3 | 7.3 | 2.3 | 3.2 |
| 90.0 | 458.8 | 424.7 | 493.0 | 7.4 | 2.4 | 3.1 |
| 95.0 | 394.3 | 364.3 | 424.2 | 7.6 | 2.5 | 3.0 |
| 100.0 | 340.0 | 313.7 | 366.3 | 7.7 | 2.6 | 2.9 |
| 105.0 | 294.3 | 271.1 | 317.5 | 7.9 | 2.8 | 2.9 |
| 110.0 | 255.6 | 235.1 | 276.1 | 8.0 | 2.9 | 2.8 |
| 115.0 | 222.7 | 204.6 | 240.9 | 8.2 | 3.0 | 2.7 |
| 120.0 | 194.7 | 178.5 | 210.8 | 8.3 | 3.1 | 2.7 |
| 125.0 | 170.9 | 156.5 | 185.2 | 8.4 | 3.2 | 2.6 |
| 130.0 | 150.5 | 137.6 | 163.3 | 8.5 | 3.4 | 2.5 |
| 135.0 | 132.7 | 121.2 | 144.2 | 8.7 | 3.5 | 2.5 |
| 140.0 | 117.4 | 107.1 | 127.7 | 8.8 | 3.6 | 2.4 |
| 145.0 | 104.2 | 94.90 | 113.4 | 8.9 | 3.8 | 2.4 |
| 150.0 | 92.65 | 84.31 | 101.0 | 9.0 | 3.9 | 2.3 |
| 155.0 | 82.67 | 75.14 | 90.21 | 9.1 | 4.0 | 2.3 |

| B57867S0103F140 | | | | | | |
|------------------------|--|--------------------------|--------------------------|-------------------------|-------------------------------|-----------------|
| R/T No. | 8016 | | | | | |
| T (°C) | $B_{25/100} = 3988 \text{ K}$, $R_{25} = 10000 \text{ } \Omega$, $T_R = 25 \text{ } ^\circ\text{C}$, $\Delta R_R/R_R = \pm 1\%$ | | | | | |
| | $R_{\text{nom}}[\Omega]$ | $R_{\text{min}}[\Omega]$ | $R_{\text{max}}[\Omega]$ | $\Delta R_R/R_R[\pm\%]$ | $\Delta T[\pm^\circ\text{C}]$ | $\alpha (\%/K)$ |
| -55.0 | 963050 | 905700 | 1020400 | 6.0 | 0.8 | 7.4 |
| -50.0 | 670100 | 632940 | 707260 | 5.5 | 0.8 | 7.1 |
| -45.0 | 471690 | 447380 | 496000 | 5.2 | 0.7 | 6.9 |

| B57867S0103F140 | | | | | | |
|------------------------|---|----------------------|----------------------|--------------------------------------|------------|------------|
| R/T No. | 8016 | | | | | |
| T (°C) | B _{25/100} = 3988 K, R ₂₅ = 10000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 1% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -40.0 | 336500 | 320420 | 352580 | 4.8 | 0.7 | 6.7 |
| -35.0 | 242590 | 231870 | 253310 | 4.4 | 0.7 | 6.4 |
| -30.0 | 177000 | 169790 | 184210 | 4.1 | 0.7 | 6.2 |
| -25.0 | 130370 | 125490 | 135250 | 3.7 | 0.6 | 6.0 |
| -20.0 | 97070 | 93743 | 100400 | 3.4 | 0.6 | 5.8 |
| -15.0 | 72929 | 70652 | 75206 | 3.1 | 0.6 | 5.6 |
| -10.0 | 55330 | 53765 | 56895 | 2.8 | 0.5 | 5.4 |
| -5.0 | 42315 | 41237 | 43393 | 2.5 | 0.5 | 5.3 |
| 0.0 | 32650 | 31907 | 33393 | 2.3 | 0.4 | 5.1 |
| 5.0 | 25388 | 24877 | 25898 | 2.0 | 0.4 | 5.0 |
| 10.0 | 19900 | 19550 | 20250 | 1.8 | 0.4 | 4.8 |
| 15.0 | 15708 | 15470 | 15946 | 1.5 | 0.3 | 4.7 |
| 20.0 | 12490 | 12330 | 12650 | 1.3 | 0.3 | 4.5 |
| 25.0 | 10000 | 9900 | 10100 | 1.0 | 0.2 | 4.4 |
| 30.0 | 8057 | 7955 | 8159 | 1.3 | 0.3 | 4.3 |
| 35.0 | 6531 | 6434 | 6628 | 1.5 | 0.4 | 4.1 |
| 40.0 | 5327 | 5237 | 5417 | 1.7 | 0.4 | 4.0 |
| 45.0 | 4369 | 4286 | 4451 | 1.9 | 0.5 | 3.9 |
| 50.0 | 3603 | 3528 | 3678 | 2.1 | 0.5 | 3.8 |
| 55.0 | 2986 | 2918 | 3054 | 2.3 | 0.6 | 3.7 |
| 60.0 | 2488 | 2427 | 2549 | 2.5 | 0.7 | 3.6 |
| 65.0 | 2083 | 2028 | 2138 | 2.6 | 0.8 | 3.5 |
| 70.0 | 1752 | 1703 | 1801 | 2.8 | 0.8 | 3.4 |
| 75.0 | 1481 | 1437 | 1525 | 3.0 | 0.9 | 3.3 |
| 80.0 | 1258 | 1219 | 1297 | 3.1 | 1.0 | 3.2 |
| 85.0 | 1072 | 1037 | 1108 | 3.3 | 1.0 | 3.2 |
| 90.0 | 917.7 | 886.1 | 949.3 | 3.4 | 1.1 | 3.1 |
| 95.0 | 788.5 | 760.2 | 816.9 | 3.6 | 1.2 | 3.0 |
| 100.0 | 680.0 | 654.6 | 705.4 | 3.7 | 1.3 | 2.9 |
| 105.0 | 588.6 | 565.8 | 611.4 | 3.9 | 1.4 | 2.9 |
| 110.0 | 511.2 | 490.7 | 531.7 | 4.0 | 1.4 | 2.8 |
| 115.0 | 445.4 | 426.9 | 463.9 | 4.2 | 1.5 | 2.7 |
| 120.0 | 389.3 | 372.6 | 406.0 | 4.3 | 1.6 | 2.7 |
| 125.0 | 341.7 | 326.6 | 356.8 | 4.4 | 1.7 | 2.6 |
| 130.0 | 300.9 | 287.3 | 314.5 | 4.5 | 1.8 | 2.5 |
| 135.0 | 265.4 | 253.1 | 277.8 | 4.7 | 1.9 | 2.5 |
| 140.0 | 234.8 | 223.6 | 246.0 | 4.8 | 2.0 | 2.4 |
| 145.0 | 208.3 | 198.1 | 218.5 | 4.9 | 2.1 | 2.4 |
| 150.0 | 185.3 | 176.0 | 194.6 | 5.0 | 2.2 | 2.3 |
| 155.0 | 165.3 | 156.9 | 173.8 | 5.1 | 2.3 | 2.3 |

| B57867S0103H140 | | | | | | |
|------------------------|--|-------------------|-------------------|-------------------------|-------------------------------|-----------------|
| R/T No. | 8016 | | | | | |
| T (°C) | $B_{25/100} = 3988 \text{ K}$, $R_{25} = 10000 \text{ } \Omega$, $T_R = 25 \text{ } ^\circ\text{C}$, $\Delta R_R/R_R = \pm 3\%$ | | | | | |
| | $R_{nom}[\Omega]$ | $R_{min}[\Omega]$ | $R_{max}[\Omega]$ | $\Delta R_R/R_R[\pm\%]$ | $\Delta T[\pm^\circ\text{C}]$ | $\alpha (\%/K)$ |
| -55.0 | 963050 | 886440 | 1039700 | 8.0 | 1.1 | 7.4 |
| -50.0 | 670100 | 619540 | 720660 | 7.5 | 1.1 | 7.1 |
| -45.0 | 471690 | 437940 | 505430 | 7.2 | 1.0 | 6.9 |
| -40.0 | 336500 | 313690 | 359310 | 6.8 | 1.0 | 6.7 |
| -35.0 | 242590 | 227020 | 258160 | 6.4 | 1.0 | 6.4 |
| -30.0 | 177000 | 166250 | 187750 | 6.1 | 1.0 | 6.2 |
| -25.0 | 130370 | 122880 | 137860 | 5.7 | 1.0 | 6.0 |
| -20.0 | 97070 | 91801 | 102340 | 5.4 | 0.9 | 5.8 |
| -15.0 | 72929 | 69193 | 76665 | 5.1 | 0.9 | 5.6 |
| -10.0 | 55330 | 52658 | 58002 | 4.8 | 0.9 | 5.4 |
| -5.0 | 42315 | 40391 | 44239 | 4.5 | 0.9 | 5.3 |
| 0.0 | 32650 | 31254 | 34046 | 4.3 | 0.8 | 5.1 |
| 5.0 | 25388 | 24369 | 26406 | 4.0 | 0.8 | 5.0 |
| 10.0 | 19900 | 19152 | 20648 | 3.8 | 0.8 | 4.8 |
| 15.0 | 15708 | 15156 | 16260 | 3.5 | 0.8 | 4.7 |
| 20.0 | 12490 | 12081 | 12899 | 3.3 | 0.7 | 4.5 |
| 25.0 | 10000 | 9700 | 10300 | 3.0 | 0.7 | 4.4 |
| 30.0 | 8057 | 7793 | 8321 | 3.3 | 0.8 | 4.3 |
| 35.0 | 6531 | 6304 | 6759 | 3.5 | 0.8 | 4.1 |
| 40.0 | 5327 | 5130 | 5524 | 3.7 | 0.9 | 4.0 |
| 45.0 | 4369 | 4199 | 4539 | 3.9 | 1.0 | 3.9 |
| 50.0 | 3603 | 3456 | 3750 | 4.1 | 1.1 | 3.8 |
| 55.0 | 2986 | 2859 | 3114 | 4.3 | 1.2 | 3.7 |
| 60.0 | 2488 | 2377 | 2599 | 4.5 | 1.2 | 3.6 |
| 65.0 | 2083 | 1987 | 2180 | 4.6 | 1.3 | 3.5 |
| 70.0 | 1752 | 1668 | 1836 | 4.8 | 1.4 | 3.4 |
| 75.0 | 1481 | 1408 | 1555 | 5.0 | 1.5 | 3.3 |
| 80.0 | 1258 | 1193 | 1323 | 5.1 | 1.6 | 3.2 |
| 85.0 | 1072 | 1016 | 1129 | 5.3 | 1.7 | 3.2 |
| 90.0 | 917.7 | 867.7 | 967.7 | 5.4 | 1.8 | 3.1 |
| 95.0 | 788.5 | 744.4 | 832.6 | 5.6 | 1.9 | 3.0 |
| 100.0 | 680.0 | 641.0 | 719.0 | 5.7 | 2.0 | 2.9 |
| 105.0 | 588.6 | 554.0 | 623.2 | 5.9 | 2.1 | 2.9 |
| 110.0 | 511.2 | 480.4 | 542.0 | 6.0 | 2.2 | 2.8 |
| 115.0 | 445.4 | 418.0 | 472.8 | 6.2 | 2.3 | 2.7 |
| 120.0 | 389.3 | 364.8 | 413.8 | 6.3 | 2.4 | 2.7 |
| 125.0 | 341.7 | 319.8 | 363.6 | 6.4 | 2.5 | 2.6 |
| 130.0 | 300.9 | 281.2 | 320.6 | 6.5 | 2.6 | 2.5 |
| 135.0 | 265.4 | 247.8 | 283.1 | 6.7 | 2.7 | 2.5 |

| B57867S0103H140 | | | | | | |
|------------------------|---|----------------------|----------------------|--------------------------------------|---------|---------|
| R/T No. | 8016 | | | | | |
| T (°C) | B _{25/100} = 3988 K, R ₂₅ = 10000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 3% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| 140.0 | 234.8 | 218.9 | 250.7 | 6.8 | 2.8 | 2.4 |
| 145.0 | 208.3 | 194.0 | 222.7 | 6.9 | 2.9 | 2.4 |
| 150.0 | 185.3 | 172.3 | 198.3 | 7.0 | 3.0 | 2.3 |
| 155.0 | 165.3 | 153.6 | 177.1 | 7.1 | 3.1 | 2.3 |

| B57867S0103J140 | | | | | | |
|------------------------|---|----------------------|----------------------|--------------------------------------|------------|------------|
| R/T No. | 8016 | | | | | |
| T (°C) | B _{25/100} = 3988 K, R ₂₅ = 10000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 5% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -55.0 | 963050 | 867180 | 1058900 | 10.0 | 1.3 | 7.4 |
| -50.0 | 670100 | 606140 | 734070 | 9.5 | 1.3 | 7.1 |
| -45.0 | 471690 | 428510 | 514870 | 9.2 | 1.3 | 6.9 |
| -40.0 | 336500 | 306960 | 366040 | 8.8 | 1.3 | 6.7 |
| -35.0 | 242590 | 222160 | 263020 | 8.4 | 1.3 | 6.4 |
| -30.0 | 177000 | 162710 | 191290 | 8.1 | 1.3 | 6.2 |
| -25.0 | 130370 | 120270 | 140470 | 7.7 | 1.3 | 6.0 |
| -20.0 | 97070 | 89860 | 104280 | 7.4 | 1.3 | 5.8 |
| -15.0 | 72929 | 67735 | 78124 | 7.1 | 1.3 | 5.6 |
| -10.0 | 55330 | 51551 | 59108 | 6.8 | 1.3 | 5.4 |
| -5.0 | 42315 | 39545 | 45085 | 6.5 | 1.2 | 5.3 |
| 0.0 | 32650 | 30601 | 34699 | 6.3 | 1.2 | 5.1 |
| 5.0 | 25388 | 23861 | 26914 | 6.0 | 1.2 | 5.0 |
| 10.0 | 19900 | 18754 | 21046 | 5.8 | 1.2 | 4.8 |
| 15.0 | 15708 | 14842 | 16574 | 5.5 | 1.2 | 4.7 |
| 20.0 | 12490 | 11831 | 13149 | 5.3 | 1.2 | 4.5 |
| 25.0 | 10000 | 9500 | 10500 | 5.0 | 1.1 | 4.4 |
| 30.0 | 8057 | 7632 | 8482 | 5.3 | 1.2 | 4.3 |
| 35.0 | 6531 | 6173 | 6889 | 5.5 | 1.3 | 4.1 |
| 40.0 | 5327 | 5024 | 5630 | 5.7 | 1.4 | 4.0 |
| 45.0 | 4369 | 4111 | 4626 | 5.9 | 1.5 | 3.9 |
| 50.0 | 3603 | 3384 | 3822 | 6.1 | 1.6 | 3.8 |
| 55.0 | 2986 | 2799 | 3174 | 6.3 | 1.7 | 3.7 |
| 60.0 | 2488 | 2327 | 2649 | 6.5 | 1.8 | 3.6 |
| 65.0 | 2083 | 1945 | 2221 | 6.6 | 1.9 | 3.5 |
| 70.0 | 1752 | 1633 | 1871 | 6.8 | 2.0 | 3.4 |
| 75.0 | 1481 | 1378 | 1585 | 7.0 | 2.1 | 3.3 |
| 80.0 | 1258 | 1168 | 1348 | 7.1 | 2.2 | 3.2 |
| 85.0 | 1072 | 994.2 | 1151 | 7.3 | 2.3 | 3.2 |
| 90.0 | 917.7 | 849.4 | 986.0 | 7.4 | 2.4 | 3.1 |

| B57867S0103J140 | | | | | | |
|------------------------|--|--------------------------|--------------------------|-------------------------|-------------------------------|-----------------|
| R/T No. | 8016 | | | | | |
| T (°C) | $B_{25/100} = 3988 \text{ K}$, $R_{25} = 10000 \text{ } \Omega$, $T_R = 25 \text{ } ^\circ\text{C}$, $\Delta R_R/R_R = \pm 5\%$ | | | | | |
| | $R_{\text{nom}}[\Omega]$ | $R_{\text{min}}[\Omega]$ | $R_{\text{max}}[\Omega]$ | $\Delta R_R/R_R[\pm\%]$ | $\Delta T[\pm^\circ\text{C}]$ | $\alpha (\%/K)$ |
| 95.0 | 788.5 | 728.6 | 848.4 | 7.6 | 2.5 | 3.0 |
| 100.0 | 680.0 | 627.4 | 732.6 | 7.7 | 2.6 | 2.9 |
| 105.0 | 588.6 | 542.2 | 635.0 | 7.9 | 2.8 | 2.9 |
| 110.0 | 511.2 | 470.2 | 552.2 | 8.0 | 2.9 | 2.8 |
| 115.0 | 445.4 | 409.1 | 481.7 | 8.2 | 3.0 | 2.7 |
| 120.0 | 389.3 | 357.1 | 421.5 | 8.3 | 3.1 | 2.7 |
| 125.0 | 341.7 | 313.0 | 370.4 | 8.4 | 3.2 | 2.6 |
| 130.0 | 300.9 | 275.2 | 326.6 | 8.5 | 3.4 | 2.5 |
| 135.0 | 265.4 | 242.5 | 288.4 | 8.7 | 3.5 | 2.5 |
| 140.0 | 234.8 | 214.2 | 255.4 | 8.8 | 3.6 | 2.4 |
| 145.0 | 208.3 | 189.8 | 226.8 | 8.9 | 3.8 | 2.4 |
| 150.0 | 185.3 | 168.6 | 202.0 | 9.0 | 3.9 | 2.3 |
| 155.0 | 165.3 | 150.3 | 180.4 | 9.1 | 4.0 | 2.3 |

| B57867S0303F140 | | | | | | |
|------------------------|--|--------------------------|--------------------------|-------------------------|-------------------------------|-----------------|
| R/T No. | 8018 | | | | | |
| T (°C) | $B_{25/100} = 3964 \text{ K}$, $R_{25} = 30000 \text{ } \Omega$, $T_R = 25 \text{ } ^\circ\text{C}$, $\Delta R_R/R_R = \pm 1\%$ | | | | | |
| | $R_{\text{nom}}[\Omega]$ | $R_{\text{min}}[\Omega]$ | $R_{\text{max}}[\Omega]$ | $\Delta R_R/R_R[\pm\%]$ | $\Delta T[\pm^\circ\text{C}]$ | $\alpha (\%/K)$ |
| -55.0 | 2472200 | 2325700 | 2618700 | 5.9 | 0.8 | 7.0 |
| -50.0 | 1750300 | 1653700 | 1846900 | 5.5 | 0.8 | 6.8 |
| -45.0 | 1253200 | 1189000 | 1317500 | 5.1 | 0.8 | 6.6 |
| -40.0 | 907060 | 863910 | 950200 | 4.8 | 0.7 | 6.4 |
| -35.0 | 663280 | 634100 | 692460 | 4.4 | 0.7 | 6.2 |
| -30.0 | 489810 | 469940 | 509680 | 4.1 | 0.7 | 6.0 |
| -25.0 | 365130 | 351510 | 378740 | 3.7 | 0.6 | 5.8 |
| -20.0 | 274640 | 265270 | 284020 | 3.4 | 0.6 | 5.6 |
| -15.0 | 208370 | 201890 | 214850 | 3.1 | 0.6 | 5.4 |
| -10.0 | 159410 | 154910 | 163900 | 2.8 | 0.5 | 5.3 |
| -5.0 | 122920 | 119800 | 126030 | 2.5 | 0.5 | 5.1 |
| 0.0 | 95501 | 93336 | 97666 | 2.3 | 0.5 | 5.0 |
| 5.0 | 74745 | 73245 | 76244 | 2.0 | 0.4 | 4.8 |
| 10.0 | 58911 | 57877 | 59944 | 1.8 | 0.4 | 4.7 |
| 15.0 | 46745 | 46038 | 47451 | 1.5 | 0.3 | 4.6 |
| 20.0 | 37332 | 36855 | 37808 | 1.3 | 0.3 | 4.4 |
| 25.0 | 30000 | 29700 | 30300 | 1.0 | 0.2 | 4.3 |
| 30.0 | 24253 | 23945 | 24561 | 1.3 | 0.3 | 4.2 |
| 35.0 | 19720 | 19428 | 20012 | 1.5 | 0.4 | 4.1 |
| 40.0 | 16123 | 15851 | 16395 | 1.7 | 0.4 | 4.0 |
| 45.0 | 13252 | 13002 | 13502 | 1.9 | 0.5 | 3.9 |

| B57867S0303F140 | | | | | | |
|------------------------|---|-----------------------|-----------------------|--------------------------------------|---------|---------|
| R/T No. | 8018 | | | | | |
| T (°C) | B _{25/100} = 3964 K, R ₂₅ = 30000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 1% | | | | | |
| | R _{noml} [Ω] | R _{minl} [Ω] | R _{maxl} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| 50.0 | 10949 | 10721 | 11177 | 2.1 | 0.6 | 3.8 |
| 55.0 | 9091 | 8885 | 9297 | 2.3 | 0.6 | 3.7 |
| 60.0 | 7584 | 7399 | 7770 | 2.4 | 0.7 | 3.6 |
| 65.0 | 6356 | 6189 | 6523 | 2.6 | 0.8 | 3.5 |
| 70.0 | 5351 | 5201 | 5500 | 2.8 | 0.8 | 3.4 |
| 75.0 | 4524 | 4390 | 4657 | 3.0 | 0.9 | 3.3 |
| 80.0 | 3840 | 3720 | 3960 | 3.1 | 1.0 | 3.2 |
| 85.0 | 3273 | 3166 | 3380 | 3.3 | 1.0 | 3.2 |
| 90.0 | 2800 | 2704 | 2896 | 3.4 | 1.1 | 3.1 |
| 95.0 | 2405 | 2319 | 2491 | 3.6 | 1.2 | 3.0 |
| 100.0 | 2073 | 1995 | 2150 | 3.7 | 1.3 | 2.9 |
| 105.0 | 1792 | 1723 | 1862 | 3.9 | 1.3 | 2.9 |
| 110.0 | 1555 | 1493 | 1618 | 4.0 | 1.4 | 2.8 |
| 115.0 | 1354 | 1298 | 1410 | 4.1 | 1.5 | 2.7 |
| 120.0 | 1182 | 1132 | 1233 | 4.3 | 1.6 | 2.7 |
| 125.0 | 1036 | 990.3 | 1081 | 4.4 | 1.7 | 2.6 |
| 130.0 | 910.0 | 868.9 | 951.0 | 4.5 | 1.8 | 2.6 |
| 135.0 | 801.7 | 764.6 | 838.9 | 4.6 | 1.8 | 2.5 |
| 140.0 | 708.3 | 674.6 | 741.9 | 4.8 | 1.9 | 2.5 |
| 145.0 | 627.4 | 596.9 | 658.0 | 4.9 | 2.0 | 2.4 |
| 150.0 | 557.2 | 529.5 | 585.0 | 5.0 | 2.1 | 2.3 |
| 155.0 | 496.1 | 470.9 | 521.4 | 5.1 | 2.2 | 2.3 |

| B57867S0303H140 | | | | | | |
|------------------------|---|-----------------------|-----------------------|--------------------------------------|---------|---------|
| R/T No. | 8018 | | | | | |
| T (°C) | B _{25/100} = 3964 K, R ₂₅ = 30000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 3% | | | | | |
| | R _{noml} [Ω] | R _{minl} [Ω] | R _{maxl} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -55.0 | 2472200 | 2276300 | 2668200 | 7.9 | 1.1 | 7.0 |
| -50.0 | 1750300 | 1618700 | 1881900 | 7.5 | 1.1 | 6.8 |
| -45.0 | 1253200 | 1163900 | 1342600 | 7.1 | 1.1 | 6.6 |
| -40.0 | 907060 | 845770 | 968340 | 6.8 | 1.1 | 6.4 |
| -35.0 | 663280 | 620830 | 705730 | 6.4 | 1.0 | 6.2 |
| -30.0 | 489810 | 460140 | 519480 | 6.1 | 1.0 | 6.0 |
| -25.0 | 365130 | 344210 | 386040 | 5.7 | 1.0 | 5.8 |
| -20.0 | 274640 | 259780 | 289510 | 5.4 | 1.0 | 5.6 |
| -15.0 | 208370 | 197730 | 219020 | 5.1 | 0.9 | 5.4 |
| -10.0 | 159410 | 151720 | 167090 | 4.8 | 0.9 | 5.3 |
| -5.0 | 122920 | 117340 | 128490 | 4.5 | 0.9 | 5.1 |
| 0.0 | 95501 | 91426 | 99576 | 4.3 | 0.9 | 5.0 |

| B57867S0303H140 | | | | | | |
|------------------------|---|----------------------|----------------------|--------------------------------------|------------|------------|
| R/T No. | 8018 | | | | | |
| T (°C) | B _{25/100} = 3964 K, R ₂₅ = 30000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 3% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| 5.0 | 74745 | 71750 | 77739 | 4.0 | 0.8 | 4.8 |
| 10.0 | 58911 | 56699 | 61122 | 3.8 | 0.8 | 4.7 |
| 15.0 | 46745 | 45103 | 48386 | 3.5 | 0.8 | 4.6 |
| 20.0 | 37332 | 36108 | 38555 | 3.3 | 0.7 | 4.4 |
| 25.0 | 30000 | 29100 | 30900 | 3.0 | 0.7 | 4.3 |
| 30.0 | 24253 | 23460 | 25046 | 3.3 | 0.8 | 4.2 |
| 35.0 | 19720 | 19033 | 20406 | 3.5 | 0.9 | 4.1 |
| 40.0 | 16123 | 15528 | 16717 | 3.7 | 0.9 | 4.0 |
| 45.0 | 13252 | 12737 | 13767 | 3.9 | 1.0 | 3.9 |
| 50.0 | 10949 | 10503 | 11396 | 4.1 | 1.1 | 3.8 |
| 55.0 | 9091 | 8703 | 9479 | 4.3 | 1.2 | 3.7 |
| 60.0 | 7584 | 7247 | 7921 | 4.4 | 1.2 | 3.6 |
| 65.0 | 6356 | 6062 | 6650 | 4.6 | 1.3 | 3.5 |
| 70.0 | 5351 | 5094 | 5607 | 4.8 | 1.4 | 3.4 |
| 75.0 | 4524 | 4299 | 4748 | 5.0 | 1.5 | 3.3 |
| 80.0 | 3840 | 3643 | 4037 | 5.1 | 1.6 | 3.2 |
| 85.0 | 3273 | 3100 | 3446 | 5.3 | 1.7 | 3.2 |
| 90.0 | 2800 | 2648 | 2952 | 5.4 | 1.8 | 3.1 |
| 95.0 | 2405 | 2271 | 2539 | 5.6 | 1.9 | 3.0 |
| 100.0 | 2073 | 1954 | 2191 | 5.7 | 1.9 | 2.9 |
| 105.0 | 1792 | 1687 | 1897 | 5.9 | 2.0 | 2.9 |
| 110.0 | 1555 | 1462 | 1649 | 6.0 | 2.1 | 2.8 |
| 115.0 | 1354 | 1271 | 1437 | 6.1 | 2.2 | 2.7 |
| 120.0 | 1182 | 1108 | 1257 | 6.3 | 2.3 | 2.7 |
| 125.0 | 1036 | 969.6 | 1102 | 6.4 | 2.4 | 2.6 |
| 130.0 | 910.0 | 850.7 | 969.2 | 6.5 | 2.5 | 2.6 |
| 135.0 | 801.7 | 748.5 | 854.9 | 6.6 | 2.6 | 2.5 |
| 140.0 | 708.3 | 660.5 | 756.1 | 6.8 | 2.8 | 2.5 |
| 145.0 | 627.4 | 584.4 | 670.5 | 6.9 | 2.9 | 2.4 |
| 150.0 | 557.2 | 518.4 | 596.1 | 7.0 | 3.0 | 2.3 |
| 155.0 | 496.1 | 461.0 | 531.3 | 7.1 | 3.1 | 2.3 |

| B57867S0303J140 | | | | | | |
|------------------------|---|----------------------|----------------------|--------------------------------------|---------|---------|
| R/T No. | 8018 | | | | | |
| T (°C) | B _{25/100} = 3964 K, R ₂₅ = 30000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 5% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -55.0 | 2472200 | 2226900 | 2717600 | 9.9 | 1.4 | 7.0 |
| -50.0 | 1750300 | 1583700 | 1916900 | 9.5 | 1.4 | 6.8 |
| -45.0 | 1253200 | 1138800 | 1367700 | 9.1 | 1.4 | 6.6 |

| B57867S0303J140 | | | | | | |
|------------------------|---|----------------------|----------------------|--------------------------------------|------------|------------|
| R/T No. | 8018 | | | | | |
| T (°C) | B _{25/100} = 3964 K, R ₂₅ = 30000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 5% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -40.0 | 907060 | 827630 | 986480 | 8.8 | 1.4 | 6.4 |
| -35.0 | 663280 | 607570 | 718990 | 8.4 | 1.4 | 6.2 |
| -30.0 | 489810 | 450340 | 529280 | 8.1 | 1.4 | 6.0 |
| -25.0 | 365130 | 336910 | 393350 | 7.7 | 1.3 | 5.8 |
| -20.0 | 274640 | 254280 | 295000 | 7.4 | 1.3 | 5.6 |
| -15.0 | 208370 | 193560 | 223190 | 7.1 | 1.3 | 5.4 |
| -10.0 | 159410 | 148540 | 170270 | 6.8 | 1.3 | 5.3 |
| -5.0 | 122920 | 114880 | 130950 | 6.5 | 1.3 | 5.1 |
| 0.0 | 95501 | 89516 | 101490 | 6.3 | 1.3 | 5.0 |
| 5.0 | 74745 | 70255 | 79234 | 6.0 | 1.2 | 4.8 |
| 10.0 | 58911 | 55521 | 62301 | 5.8 | 1.2 | 4.7 |
| 15.0 | 46745 | 44168 | 49321 | 5.5 | 1.2 | 4.6 |
| 20.0 | 37332 | 35362 | 39302 | 5.3 | 1.2 | 4.4 |
| 25.0 | 30000 | 28500 | 31500 | 5.0 | 1.2 | 4.3 |
| 30.0 | 24253 | 22975 | 25531 | 5.3 | 1.3 | 4.2 |
| 35.0 | 19720 | 18639 | 20801 | 5.5 | 1.3 | 4.1 |
| 40.0 | 16123 | 15206 | 17040 | 5.7 | 1.4 | 4.0 |
| 45.0 | 13252 | 12472 | 14032 | 5.9 | 1.5 | 3.9 |
| 50.0 | 10949 | 10284 | 11615 | 6.1 | 1.6 | 3.8 |
| 55.0 | 9091 | 8521 | 9660 | 6.3 | 1.7 | 3.7 |
| 60.0 | 7584 | 7095 | 8073 | 6.4 | 1.8 | 3.6 |
| 65.0 | 6356 | 5935 | 6777 | 6.6 | 1.9 | 3.5 |
| 70.0 | 5351 | 4987 | 5714 | 6.8 | 2.0 | 3.4 |
| 75.0 | 4524 | 4209 | 4838 | 7.0 | 2.1 | 3.3 |
| 80.0 | 3840 | 3567 | 4114 | 7.1 | 2.2 | 3.2 |
| 85.0 | 3273 | 3035 | 3511 | 7.3 | 2.3 | 3.2 |
| 90.0 | 2800 | 2592 | 3008 | 7.4 | 2.4 | 3.1 |
| 95.0 | 2405 | 2223 | 2587 | 7.6 | 2.5 | 3.0 |
| 100.0 | 2073 | 1912 | 2233 | 7.7 | 2.6 | 2.9 |
| 105.0 | 1792 | 1651 | 1933 | 7.9 | 2.7 | 2.9 |
| 110.0 | 1555 | 1431 | 1680 | 8.0 | 2.9 | 2.8 |
| 115.0 | 1354 | 1244 | 1464 | 8.1 | 3.0 | 2.7 |
| 120.0 | 1182 | 1085 | 1280 | 8.3 | 3.1 | 2.7 |
| 125.0 | 1036 | 948.9 | 1123 | 8.4 | 3.2 | 2.6 |
| 130.0 | 910.0 | 832.5 | 987.4 | 8.5 | 3.3 | 2.6 |
| 135.0 | 801.7 | 732.5 | 870.9 | 8.6 | 3.4 | 2.5 |
| 140.0 | 708.3 | 646.3 | 770.3 | 8.8 | 3.6 | 2.5 |
| 145.0 | 627.4 | 571.8 | 683.1 | 8.9 | 3.7 | 2.4 |
| 150.0 | 557.2 | 507.2 | 607.3 | 9.0 | 3.8 | 2.3 |
| 155.0 | 496.1 | 451.1 | 541.2 | 9.1 | 4.0 | 2.3 |

| B57867S0503F140 | | | | | | |
|------------------------|---|----------------------|----------------------|--------------------------------------|------------|------------|
| R/T No. | 2901 | | | | | |
| T (°C) | B _{25/100} = 3760 K, R ₂₅ = 50000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 1% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -55.0 | 3198400 | 3016900 | 3379900 | 5.7 | 0.9 | 6.4 |
| -50.0 | 2308900 | 2186800 | 2431000 | 5.3 | 0.8 | 6.3 |
| -45.0 | 1686900 | 1603900 | 1769900 | 4.9 | 0.8 | 6.1 |
| -40.0 | 1246300 | 1189400 | 1303200 | 4.6 | 0.8 | 6.0 |
| -35.0 | 930550 | 891210 | 969890 | 4.2 | 0.7 | 5.8 |
| -30.0 | 701670 | 674280 | 729050 | 3.9 | 0.7 | 5.6 |
| -25.0 | 533960 | 514780 | 553130 | 3.6 | 0.7 | 5.5 |
| -20.0 | 409900 | 396410 | 423390 | 3.3 | 0.6 | 5.3 |
| -15.0 | 315620 | 306130 | 325100 | 3.0 | 0.6 | 5.1 |
| -10.0 | 245070 | 238390 | 251750 | 2.7 | 0.5 | 5.0 |
| -5.0 | 191050 | 186350 | 195750 | 2.5 | 0.5 | 4.9 |
| 0.0 | 150140 | 146830 | 153450 | 2.2 | 0.5 | 4.7 |
| 5.0 | 119010 | 116680 | 121340 | 2.0 | 0.4 | 4.6 |
| 10.0 | 94998 | 93366 | 96630 | 1.7 | 0.4 | 4.5 |
| 15.0 | 76284 | 75149 | 77418 | 1.5 | 0.3 | 4.3 |
| 20.0 | 61651 | 60871 | 62431 | 1.3 | 0.3 | 4.2 |
| 25.0 | 50000 | 49500 | 50500 | 1.0 | 0.2 | 4.1 |
| 30.0 | 40839 | 40326 | 41353 | 1.3 | 0.3 | 4.0 |
| 35.0 | 33583 | 33093 | 34073 | 1.5 | 0.4 | 3.9 |
| 40.0 | 27764 | 27304 | 28223 | 1.7 | 0.4 | 3.8 |
| 45.0 | 23048 | 22623 | 23472 | 1.8 | 0.5 | 3.7 |
| 50.0 | 19229 | 18840 | 19619 | 2.0 | 0.6 | 3.6 |
| 55.0 | 16092 | 15737 | 16446 | 2.2 | 0.6 | 3.5 |
| 60.0 | 13534 | 13213 | 13856 | 2.4 | 0.7 | 3.4 |
| 65.0 | 11453 | 11162 | 11745 | 2.5 | 0.8 | 3.3 |
| 70.0 | 9734 | 9471 | 9997 | 2.7 | 0.8 | 3.2 |
| 75.0 | 8304 | 8066 | 8541 | 2.9 | 0.9 | 3.2 |
| 80.0 | 7111 | 6896 | 7325 | 3.0 | 1.0 | 3.1 |
| 85.0 | 6109 | 5916 | 6302 | 3.2 | 1.1 | 3.0 |
| 90.0 | 5267 | 5092 | 5441 | 3.3 | 1.1 | 2.9 |
| 95.0 | 4562 | 4404 | 4719 | 3.4 | 1.2 | 2.9 |
| 100.0 | 3964 | 3822 | 4106 | 3.6 | 1.3 | 2.8 |
| 105.0 | 3453 | 3325 | 3582 | 3.7 | 1.4 | 2.7 |
| 110.0 | 3017 | 2901 | 3133 | 3.8 | 1.4 | 2.7 |
| 115.0 | 2644 | 2539 | 2749 | 4.0 | 1.5 | 2.6 |
| 120.0 | 2324 | 2229 | 2419 | 4.1 | 1.6 | 2.6 |
| 125.0 | 2049 | 1963 | 2136 | 4.2 | 1.7 | 2.5 |
| 130.0 | 1812 | 1733 | 1890 | 4.3 | 1.8 | 2.4 |
| 135.0 | 1605 | 1534 | 1676 | 4.4 | 1.9 | 2.4 |

| B57867S0503F140 | | | | | | |
|------------------------|---|----------------------|----------------------|--------------------------------------|---------|---------|
| R/T No. | 2901 | | | | | |
| T (°C) | B _{25/100} = 3760 K, R ₂₅ = 50000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 1% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| 140.0 | 1425 | 1360 | 1490 | 4.6 | 1.9 | 2.3 |
| 145.0 | 1269 | 1209 | 1328 | 4.7 | 2.0 | 2.3 |
| 150.0 | 1132 | 1078 | 1186 | 4.8 | 2.1 | 2.3 |
| 155.0 | 1012 | 962.2 | 1061 | 4.9 | 2.2 | 2.2 |

| B57867S0503H140 | | | | | | |
|------------------------|---|----------------------|----------------------|--------------------------------------|------------|------------|
| R/T No. | 2901 | | | | | |
| T (°C) | B _{25/100} = 3760 K, R ₂₅ = 50000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 3% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -55.0 | 3198400 | 2953000 | 3443900 | 7.7 | 1.2 | 6.4 |
| -50.0 | 2308900 | 2140600 | 2477200 | 7.3 | 1.2 | 6.3 |
| -45.0 | 1686900 | 1570200 | 1803600 | 6.9 | 1.1 | 6.1 |
| -40.0 | 1246300 | 1164500 | 1328200 | 6.6 | 1.1 | 6.0 |
| -35.0 | 930550 | 872600 | 988500 | 6.2 | 1.1 | 5.8 |
| -30.0 | 701670 | 660250 | 743080 | 5.9 | 1.1 | 5.6 |
| -25.0 | 533960 | 504110 | 563810 | 5.6 | 1.0 | 5.5 |
| -20.0 | 409900 | 388210 | 431590 | 5.3 | 1.0 | 5.3 |
| -15.0 | 315620 | 299820 | 331410 | 5.0 | 1.0 | 5.1 |
| -10.0 | 245070 | 233480 | 256650 | 4.7 | 0.9 | 5.0 |
| -5.0 | 191050 | 182530 | 199570 | 4.5 | 0.9 | 4.9 |
| 0.0 | 150140 | 143820 | 156450 | 4.2 | 0.9 | 4.7 |
| 5.0 | 119010 | 114300 | 123720 | 4.0 | 0.9 | 4.6 |
| 10.0 | 94998 | 91466 | 98530 | 3.7 | 0.8 | 4.5 |
| 15.0 | 76284 | 73623 | 78944 | 3.5 | 0.8 | 4.3 |
| 20.0 | 61651 | 59638 | 63664 | 3.3 | 0.8 | 4.2 |
| 25.0 | 50000 | 48500 | 51500 | 3.0 | 0.7 | 4.1 |
| 30.0 | 40839 | 39509 | 42170 | 3.3 | 0.8 | 4.0 |
| 35.0 | 33583 | 32421 | 34745 | 3.5 | 0.9 | 3.9 |
| 40.0 | 27764 | 26749 | 28778 | 3.7 | 1.0 | 3.8 |
| 45.0 | 23048 | 22162 | 23933 | 3.8 | 1.0 | 3.7 |
| 50.0 | 19229 | 18455 | 20003 | 4.0 | 1.1 | 3.6 |
| 55.0 | 16092 | 15416 | 16768 | 4.2 | 1.2 | 3.5 |
| 60.0 | 13534 | 12942 | 14126 | 4.4 | 1.3 | 3.4 |
| 65.0 | 11453 | 10933 | 11974 | 4.5 | 1.4 | 3.3 |
| 70.0 | 9734 | 9276 | 10192 | 4.7 | 1.5 | 3.2 |
| 75.0 | 8304 | 7900 | 8707 | 4.9 | 1.5 | 3.2 |
| 80.0 | 7111 | 6754 | 7467 | 5.0 | 1.6 | 3.1 |
| 85.0 | 6109 | 5793 | 6424 | 5.2 | 1.7 | 3.0 |
| 90.0 | 5267 | 4987 | 5546 | 5.3 | 1.8 | 2.9 |

| B57867S0503H140 | | | | | | |
|------------------------|---|----------------------|----------------------|--------------------------------------|---------|---------|
| R/T No. | 2901 | | | | | |
| T (°C) | B _{25/100} = 3760 K, R ₂₅ = 50000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 3% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| 95.0 | 4562 | 4313 | 4810 | 5.4 | 1.9 | 2.9 |
| 100.0 | 3964 | 3743 | 4186 | 5.6 | 2.0 | 2.8 |
| 105.0 | 3453 | 3256 | 3651 | 5.7 | 2.1 | 2.7 |
| 110.0 | 3017 | 2841 | 3193 | 5.8 | 2.2 | 2.7 |
| 115.0 | 2644 | 2486 | 2802 | 6.0 | 2.3 | 2.6 |
| 120.0 | 2324 | 2182 | 2466 | 6.1 | 2.4 | 2.6 |
| 125.0 | 2049 | 1922 | 2177 | 6.2 | 2.5 | 2.5 |
| 130.0 | 1812 | 1697 | 1926 | 6.3 | 2.6 | 2.4 |
| 135.0 | 1605 | 1502 | 1709 | 6.4 | 2.7 | 2.4 |
| 140.0 | 1425 | 1332 | 1519 | 6.6 | 2.8 | 2.3 |
| 145.0 | 1269 | 1184 | 1353 | 6.7 | 2.9 | 2.3 |
| 150.0 | 1132 | 1055 | 1208 | 6.8 | 3.0 | 2.3 |
| 155.0 | 1012 | 942.0 | 1081 | 6.9 | 3.1 | 2.2 |

| B57867S0503J140 | | | | | | |
|------------------------|---|----------------------|----------------------|--------------------------------------|------------|------------|
| R/T No. | 2901 | | | | | |
| T (°C) | B _{25/100} = 3760 K, R ₂₅ = 50000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 5% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -55.0 | 3198400 | 2889000 | 3507900 | 9.7 | 1.5 | 6.4 |
| -50.0 | 2308900 | 2094500 | 2523400 | 9.3 | 1.5 | 6.3 |
| -45.0 | 1686900 | 1536400 | 1837300 | 8.9 | 1.5 | 6.1 |
| -40.0 | 1246300 | 1139600 | 1353100 | 8.6 | 1.4 | 6.0 |
| -35.0 | 930550 | 853990 | 1007100 | 8.2 | 1.4 | 5.8 |
| -30.0 | 701670 | 646220 | 757120 | 7.9 | 1.4 | 5.6 |
| -25.0 | 533960 | 493430 | 574490 | 7.6 | 1.4 | 5.5 |
| -20.0 | 409900 | 380010 | 439790 | 7.3 | 1.4 | 5.3 |
| -15.0 | 315620 | 293510 | 337720 | 7.0 | 1.4 | 5.1 |
| -10.0 | 245070 | 228580 | 261560 | 6.7 | 1.3 | 5.0 |
| -5.0 | 191050 | 178710 | 203390 | 6.5 | 1.3 | 4.9 |
| 0.0 | 150140 | 140820 | 159450 | 6.2 | 1.3 | 4.7 |
| 5.0 | 119010 | 111920 | 126100 | 6.0 | 1.3 | 4.6 |
| 10.0 | 94998 | 89566 | 100430 | 5.7 | 1.3 | 4.5 |
| 15.0 | 76284 | 72097 | 80470 | 5.5 | 1.3 | 4.3 |
| 20.0 | 61651 | 58405 | 64897 | 5.3 | 1.3 | 4.2 |
| 25.0 | 50000 | 47500 | 52500 | 5.0 | 1.2 | 4.1 |
| 30.0 | 40839 | 38692 | 42987 | 5.3 | 1.3 | 4.0 |
| 35.0 | 33583 | 31750 | 35417 | 5.5 | 1.4 | 3.9 |
| 40.0 | 27764 | 26194 | 29333 | 5.7 | 1.5 | 3.8 |
| 45.0 | 23048 | 21701 | 24394 | 5.8 | 1.6 | 3.7 |

| B57867S0503J140 | | | | | | |
|------------------------|---|----------------------|----------------------|--------------------------------------|---------|---------|
| R/T No. | 2901 | | | | | |
| T (°C) | B _{25/100} = 3760 K, R ₂₅ = 50000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 5% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| 50.0 | 19229 | 18071 | 20388 | 6.0 | 1.7 | 3.6 |
| 55.0 | 16092 | 15094 | 17090 | 6.2 | 1.8 | 3.5 |
| 60.0 | 13534 | 12671 | 14397 | 6.4 | 1.9 | 3.4 |
| 65.0 | 11453 | 10704 | 12203 | 6.5 | 2.0 | 3.3 |
| 70.0 | 9734 | 9082 | 10387 | 6.7 | 2.1 | 3.2 |
| 75.0 | 8304 | 7734 | 8873 | 6.9 | 2.2 | 3.2 |
| 80.0 | 7111 | 6612 | 7609 | 7.0 | 2.3 | 3.1 |
| 85.0 | 6109 | 5671 | 6546 | 7.2 | 2.4 | 3.0 |
| 90.0 | 5267 | 4882 | 5651 | 7.3 | 2.5 | 2.9 |
| 95.0 | 4562 | 4222 | 4901 | 7.4 | 2.6 | 2.9 |
| 100.0 | 3964 | 3664 | 4265 | 7.6 | 2.7 | 2.8 |
| 105.0 | 3453 | 3187 | 3720 | 7.7 | 2.8 | 2.7 |
| 110.0 | 3017 | 2780 | 3254 | 7.8 | 2.9 | 2.7 |
| 115.0 | 2644 | 2433 | 2855 | 8.0 | 3.0 | 2.6 |
| 120.0 | 2324 | 2136 | 2512 | 8.1 | 3.2 | 2.6 |
| 125.0 | 2049 | 1881 | 2218 | 8.2 | 3.3 | 2.5 |
| 130.0 | 1812 | 1661 | 1963 | 8.3 | 3.4 | 2.4 |
| 135.0 | 1605 | 1469 | 1741 | 8.4 | 3.5 | 2.4 |
| 140.0 | 1425 | 1303 | 1548 | 8.6 | 3.6 | 2.3 |
| 145.0 | 1269 | 1159 | 1379 | 8.7 | 3.8 | 2.3 |
| 150.0 | 1132 | 1032 | 1231 | 8.8 | 3.9 | 2.3 |
| 155.0 | 1012 | 921.7 | 1101 | 8.9 | 4.0 | 2.2 |

| B57867S0104F140 | | | | | | |
|------------------------|--|----------------------|----------------------|--------------------------------------|---------|---------|
| R/T No. | 2014 | | | | | |
| T (°C) | B _{25/100} = 4540 K, R ₂₅ = 100000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 1% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -55.0 | 14200000 | 13258000 | 15142000 | 6.6 | 0.8 | 7.8 |
| -50.0 | 9661500 | 9065600 | 10257000 | 6.2 | 0.8 | 7.6 |
| -45.0 | 6656200 | 6275300 | 7037000 | 5.7 | 0.8 | 7.3 |
| -40.0 | 4640000 | 4394300 | 4885700 | 5.3 | 0.7 | 7.1 |
| -35.0 | 3270800 | 3111000 | 3430600 | 4.9 | 0.7 | 6.9 |
| -30.0 | 2330200 | 2225500 | 2435000 | 4.5 | 0.7 | 6.7 |
| -25.0 | 1677000 | 1607900 | 1746100 | 4.1 | 0.6 | 6.5 |
| -20.0 | 1218600 | 1172800 | 1264400 | 3.8 | 0.6 | 6.3 |
| -15.0 | 893700 | 863230 | 924170 | 3.4 | 0.6 | 6.1 |
| -10.0 | 661250 | 640920 | 681590 | 3.1 | 0.5 | 5.9 |
| -5.0 | 493420 | 479840 | 507010 | 2.8 | 0.5 | 5.8 |
| 0.0 | 371200 | 362130 | 380270 | 2.4 | 0.4 | 5.6 |

| B57867S0104F140 | | | | | | |
|------------------------|--|--------------------|--------------------|-------------------------|-------------------------------|-----------------|
| R/T No. | 2014 | | | | | |
| T (°C) | $B_{25/100} = 4540 \text{ K}, R_{25} = 100000 \text{ } \Omega, T_R = 25 \text{ } ^\circ\text{C}, \Delta R_R/R_R = \pm 1\%$ | | | | | |
| | $R_{nomL}[\Omega]$ | $R_{minL}[\Omega]$ | $R_{maxL}[\Omega]$ | $\Delta R_R/R_R[\pm\%]$ | $\Delta T[\pm^\circ\text{C}]$ | $\alpha (\%/K)$ |
| 5.0 | 281450 | 275410 | 287480 | 2.1 | 0.4 | 5.5 |
| 10.0 | 215000 | 211010 | 219000 | 1.9 | 0.3 | 5.3 |
| 15.0 | 165440 | 162830 | 168050 | 1.6 | 0.3 | 5.2 |
| 20.0 | 128190 | 126510 | 129870 | 1.3 | 0.3 | 5.0 |
| 25.0 | 100000 | 99000 | 101000 | 1.0 | 0.2 | 4.9 |
| 30.0 | 78514 | 77493 | 79536 | 1.3 | 0.3 | 4.8 |
| 35.0 | 62031 | 61073 | 62989 | 1.5 | 0.3 | 4.7 |
| 40.0 | 49304 | 48427 | 50181 | 1.8 | 0.4 | 4.5 |
| 45.0 | 39417 | 38626 | 40208 | 2.0 | 0.5 | 4.4 |
| 50.0 | 31690 | 30984 | 32396 | 2.2 | 0.5 | 4.3 |
| 55.0 | 25616 | 24990 | 26242 | 2.4 | 0.6 | 4.2 |
| 60.0 | 20815 | 20263 | 21367 | 2.6 | 0.6 | 4.1 |
| 65.0 | 17000 | 16515 | 17484 | 2.9 | 0.7 | 4.0 |
| 70.0 | 13952 | 13527 | 14377 | 3.0 | 0.8 | 3.9 |
| 75.0 | 11505 | 11132 | 11877 | 3.2 | 0.8 | 3.8 |
| 80.0 | 9530 | 9204 | 9856 | 3.4 | 0.9 | 3.7 |
| 85.0 | 7930 | 7644 | 8215 | 3.6 | 1.0 | 3.6 |
| 90.0 | 6626 | 6376 | 6876 | 3.8 | 1.1 | 3.5 |
| 95.0 | 5560 | 5341 | 5779 | 3.9 | 1.1 | 3.5 |
| 100.0 | 4684 | 4492 | 4877 | 4.1 | 1.2 | 3.4 |
| 105.0 | 3962 | 3793 | 4131 | 4.3 | 1.3 | 3.3 |
| 110.0 | 3363 | 3214 | 3512 | 4.4 | 1.4 | 3.2 |
| 115.0 | 2866 | 2735 | 2997 | 4.6 | 1.4 | 3.2 |
| 120.0 | 2451 | 2335 | 2566 | 4.7 | 1.5 | 3.1 |
| 125.0 | 2103 | 2000 | 2205 | 4.9 | 1.6 | 3.0 |
| 130.0 | 1810 | 1719 | 1901 | 5.0 | 1.7 | 3.0 |
| 135.0 | 1563 | 1483 | 1644 | 5.2 | 1.8 | 2.9 |
| 140.0 | 1354 | 1283 | 1426 | 5.3 | 1.9 | 2.8 |
| 145.0 | 1177 | 1113 | 1241 | 5.4 | 2.0 | 2.8 |
| 150.0 | 1026 | 968.9 | 1083 | 5.5 | 2.0 | 2.7 |
| 155.0 | 896.6 | 845.7 | 947.5 | 5.7 | 2.1 | 2.7 |

| B57867S0104H140 | | | | | | |
|------------------------|--|--------------------|--------------------|-------------------------|-------------------------------|-----------------|
| R/T No. | 2014 | | | | | |
| T (°C) | $B_{25/100} = 4540 \text{ K}, R_{25} = 100000 \text{ } \Omega, T_R = 25 \text{ } ^\circ\text{C}, \Delta R_R/R_R = \pm 3\%$ | | | | | |
| | $R_{nomL}[\Omega]$ | $R_{minL}[\Omega]$ | $R_{maxL}[\Omega]$ | $\Delta R_R/R_R[\pm\%]$ | $\Delta T[\pm^\circ\text{C}]$ | $\alpha (\%/K)$ |
| -55.0 | 14200000 | 12974000 | 15426000 | 8.6 | 1.1 | 7.8 |
| -50.0 | 9661500 | 8872400 | 10451000 | 8.2 | 1.1 | 7.6 |
| -45.0 | 6656200 | 6142200 | 7170200 | 7.7 | 1.1 | 7.3 |

| B57867S0104H140 | | | | | | |
|------------------------|--|----------------------|----------------------|--------------------------------------|------------|------------|
| R/T No. | 2014 | | | | | |
| T (°C) | B _{25/100} = 4540 K, R ₂₅ = 100000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 3% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| -40.0 | 4640000 | 4301500 | 4978500 | 7.3 | 1.0 | 7.1 |
| -35.0 | 3270800 | 3045600 | 3496000 | 6.9 | 1.0 | 6.9 |
| -30.0 | 2330200 | 2178900 | 2481600 | 6.5 | 1.0 | 6.7 |
| -25.0 | 1677000 | 1574400 | 1779600 | 6.1 | 0.9 | 6.5 |
| -20.0 | 1218600 | 1148400 | 1288700 | 5.8 | 0.9 | 6.3 |
| -15.0 | 893700 | 845360 | 942050 | 5.4 | 0.9 | 6.1 |
| -10.0 | 661250 | 627690 | 694810 | 5.1 | 0.9 | 5.9 |
| -5.0 | 493420 | 469970 | 516880 | 4.8 | 0.8 | 5.8 |
| 0.0 | 371200 | 354710 | 387700 | 4.4 | 0.8 | 5.6 |
| 5.0 | 281450 | 269780 | 293110 | 4.1 | 0.8 | 5.5 |
| 10.0 | 215000 | 206710 | 223300 | 3.9 | 0.7 | 5.3 |
| 15.0 | 165440 | 159520 | 171360 | 3.6 | 0.7 | 5.2 |
| 20.0 | 128190 | 123950 | 132440 | 3.3 | 0.7 | 5.0 |
| 25.0 | 100000 | 97000 | 103000 | 3.0 | 0.6 | 4.9 |
| 30.0 | 78514 | 75922 | 81106 | 3.3 | 0.7 | 4.8 |
| 35.0 | 62031 | 59832 | 64229 | 3.5 | 0.8 | 4.7 |
| 40.0 | 49304 | 47441 | 51168 | 3.8 | 0.8 | 4.5 |
| 45.0 | 39417 | 37837 | 40996 | 4.0 | 0.9 | 4.4 |
| 50.0 | 31690 | 30350 | 33030 | 4.2 | 1.0 | 4.3 |
| 55.0 | 25616 | 24478 | 26754 | 4.4 | 1.1 | 4.2 |
| 60.0 | 20815 | 19847 | 21783 | 4.6 | 1.1 | 4.1 |
| 65.0 | 17000 | 16175 | 17824 | 4.9 | 1.2 | 4.0 |
| 70.0 | 13952 | 13248 | 14656 | 5.0 | 1.3 | 3.9 |
| 75.0 | 11505 | 10902 | 12107 | 5.2 | 1.4 | 3.8 |
| 80.0 | 9530 | 9013 | 10047 | 5.4 | 1.5 | 3.7 |
| 85.0 | 7930 | 7486 | 8374 | 5.6 | 1.5 | 3.6 |
| 90.0 | 6626 | 6244 | 7009 | 5.8 | 1.6 | 3.5 |
| 95.0 | 5560 | 5230 | 5891 | 5.9 | 1.7 | 3.5 |
| 100.0 | 4684 | 4398 | 4971 | 6.1 | 1.8 | 3.4 |
| 105.0 | 3962 | 3713 | 4210 | 6.3 | 1.9 | 3.3 |
| 110.0 | 3363 | 3147 | 3580 | 6.4 | 2.0 | 3.2 |
| 115.0 | 2866 | 2677 | 3054 | 6.6 | 2.1 | 3.2 |
| 120.0 | 2451 | 2286 | 2615 | 6.7 | 2.2 | 3.1 |
| 125.0 | 2103 | 1958 | 2247 | 6.9 | 2.3 | 3.0 |
| 130.0 | 1810 | 1683 | 1937 | 7.0 | 2.4 | 3.0 |
| 135.0 | 1563 | 1451 | 1675 | 7.2 | 2.5 | 2.9 |
| 140.0 | 1354 | 1256 | 1453 | 7.3 | 2.6 | 2.8 |
| 145.0 | 1177 | 1090 | 1264 | 7.4 | 2.7 | 2.8 |
| 150.0 | 1026 | 948.4 | 1103 | 7.5 | 2.8 | 2.7 |
| 155.0 | 896.6 | 827.8 | 965.4 | 7.7 | 2.9 | 2.7 |

| B57867S0104J140 | | | | | | |
|------------------------|--|---------------------|---------------------|-------------------------|-------------------------------|-----------------|
| R/T No. | 2014 | | | | | |
| T (°C) | $B_{25/100} = 4540 \text{ K}, R_{25} = 100000 \text{ } \Omega, T_R = 25 \text{ } ^\circ\text{C}, \Delta R_R/R_R = \pm 5\%$ | | | | | |
| | $R_{nom}[\Omega]$ | $R_{min}[\Omega]$ | $R_{max}[\Omega]$ | $\Delta R_R/R_R[\pm\%]$ | $\Delta T[\pm^\circ\text{C}]$ | $\alpha (\%/K)$ |
| -55.0 | 14200000 | 12690000 | 15710000 | 10.6 | 1.4 | 7.8 |
| -50.0 | 9661500 | 8679100 | 10644000 | 10.2 | 1.3 | 7.6 |
| -45.0 | 6656200 | 6009100 | 7303300 | 9.7 | 1.3 | 7.3 |
| -40.0 | 4640000 | 4208700 | 5071300 | 9.3 | 1.3 | 7.1 |
| -35.0 | 3270800 | 2980100 | 3561500 | 8.9 | 1.3 | 6.9 |
| -30.0 | 2330200 | 2132300 | 2528200 | 8.5 | 1.3 | 6.7 |
| -25.0 | 1677000 | 1540900 | 1813100 | 8.1 | 1.3 | 6.5 |
| -20.0 | 1218600 | 1124100 | 1313100 | 7.8 | 1.2 | 6.3 |
| -15.0 | 893700 | 827490 | 959920 | 7.4 | 1.2 | 6.1 |
| -10.0 | 661250 | 614470 | 708040 | 7.1 | 1.2 | 5.9 |
| -5.0 | 493420 | 460100 | 526750 | 6.8 | 1.2 | 5.8 |
| 0.0 | 371200 | 347280 | 395120 | 6.4 | 1.1 | 5.6 |
| 5.0 | 281450 | 264150 | 298740 | 6.1 | 1.1 | 5.5 |
| 10.0 | 215000 | 202410 | 227600 | 5.9 | 1.1 | 5.3 |
| 15.0 | 165440 | 156210 | 174670 | 5.6 | 1.1 | 5.2 |
| 20.0 | 128190 | 121390 | 135000 | 5.3 | 1.1 | 5.0 |
| 25.0 | 100000 | 95000 | 105000 | 5.0 | 1.0 | 4.9 |
| 30.0 | 78514 | 74352 | 82676 | 5.3 | 1.1 | 4.8 |
| 35.0 | 62031 | 58592 | 65470 | 5.5 | 1.2 | 4.7 |
| 40.0 | 49304 | 46455 | 52154 | 5.8 | 1.3 | 4.5 |
| 45.0 | 39417 | 37049 | 41785 | 6.0 | 1.4 | 4.4 |
| 50.0 | 31690 | 29716 | 33663 | 6.2 | 1.4 | 4.3 |
| 55.0 | 25616 | 23966 | 27266 | 6.4 | 1.5 | 4.2 |
| 60.0 | 20815 | 19431 | 22199 | 6.6 | 1.6 | 4.1 |
| 65.0 | 17000 | 15835 | 18164 | 6.9 | 1.7 | 4.0 |
| 70.0 | 13952 | 12969 | 14935 | 7.0 | 1.8 | 3.9 |
| 75.0 | 11505 | 10672 | 12337 | 7.2 | 1.9 | 3.8 |
| 80.0 | 9530 | 8823 | 10237 | 7.4 | 2.0 | 3.7 |
| 85.0 | 7930 | 7327 | 8532 | 7.6 | 2.1 | 3.6 |
| 90.0 | 6626 | 6111 | 7141 | 7.8 | 2.2 | 3.5 |
| 95.0 | 5560 | 5118 | 6002 | 7.9 | 2.3 | 3.5 |
| 100.0 | 4684 | 4304 | 5064 | 8.1 | 2.4 | 3.4 |
| 105.0 | 3962 | 3634 | 4289 | 8.3 | 2.5 | 3.3 |
| 110.0 | 3363 | 3080 | 3647 | 8.4 | 2.6 | 3.2 |
| 115.0 | 2866 | 2620 | 3112 | 8.6 | 2.7 | 3.2 |
| 120.0 | 2451 | 2237 | 2664 | 8.7 | 2.8 | 3.1 |
| 125.0 | 2103 | 1916 | 2289 | 8.9 | 2.9 | 3.0 |
| 130.0 | 1810 | 1647 | 1973 | 9.0 | 3.0 | 3.0 |
| 135.0 | 1563 | 1420 | 1706 | 9.2 | 3.2 | 2.9 |

| B57867S0104J140 | | | | | | |
|------------------------|--|----------------------|----------------------|--------------------------------------|---------|---------|
| R/T No. | 2014 | | | | | |
| T (°C) | B _{25/100} = 4540 K, R ₂₅ = 100000 Ω, T _R = 25 °C, ΔR _R /R _R = ± 5% | | | | | |
| | R _{nom} [Ω] | R _{min} [Ω] | R _{max} [Ω] | ΔR _R /R _R [±%] | ΔT[±°C] | α (%/K) |
| 140.0 | 1354 | 1229 | 1480 | 9.3 | 3.3 | 2.8 |
| 145.0 | 1177 | 1066 | 1288 | 9.4 | 3.4 | 2.8 |
| 150.0 | 1026 | 927.8 | 1124 | 9.5 | 3.5 | 2.7 |
| 155.0 | 896.6 | 809.9 | 983.3 | 9.7 | 3.6 | 2.7 |

Cautions and warnings

General

See "Important notes" at the end of this document.

Storage

- Store thermistors only in original packaging. Do not open the package before storage.
- Storage conditions in original packaging: storage temperature $-25\text{ °C} \dots +45\text{ °C}$, relative humidity $\leq 75\%$ annual mean, maximum 95%, dew precipitation is inadmissible.
- Do not store SMDs where they are exposed to heat or direct sunlight. Otherwise, the packing material may be deformed or SMDs may stick together, causing problems during mounting.
- Avoid contamination of thermistors surface during storage, handling and processing.
- Avoid storage of thermistor in harmful environments like corrosive gases (SO_x, Cl etc).
- After opening the factory seals, such as polyvinyl-sealed packages, use the SMDs as soon as possible.
- Solder thermistors after shipment from EPCOS within the time specified:
SMDs: 12 months
Leaded components: 24 months

Handling

- NTC thermistors must not be dropped. Chip-offs must not be caused during handling of NTCs.
- Components must not be touched with bare hands. Gloves are recommended.
- Avoid contamination of thermistor surface during handling.

Soldering

- Use resin-type flux or non-activated flux.
- Insufficient preheating may cause ceramic cracks.
- Rapid cooling by dipping in solvent is not recommended.
- Complete removal of flux is recommended.

Mounting

- When NTC thermistors are encapsulated with sealing material or overmolded with plastic material, the precautions given in chapter "Mounting instructions", "Sealing, potting and overmolding" must be observed.
- Electrode must not be scratched before/during/after the mounting process.
- Contacts and housings used for assembly with thermistor have to be clean before mounting.
- During operation, the thermistor's surface temperature can be very high (ICL). Ensure that adjacent components are placed at a sufficient distance from the thermistor to allow for proper cooling of the thermistors.
- Ensure that adjacent materials are designed for operation at temperatures comparable to the surface temperature of the thermistor. Be sure that surrounding parts and materials can withstand this temperature.
- Make sure that thermistors (ICLs) are adequately ventilated to avoid overheating.
- Avoid contamination of thermistor surface during processing.

Operation

- Use thermistors only within the specified operating temperature range.
- Use thermistors only within the specified voltage and current ranges (ICLs).
- Environmental conditions must not harm the thermistors. Use thermistors only in normal atmospheric conditions.
- Contact of NTC thermistors with any liquids and solvents should be prevented. It must be ensured that no water enters the NTC thermistor (e.g. through plug terminals). For measurement purposes (checking the specified resistance vs. temperature), the component must not be immersed in water but in suitable liquids (e.g. Galden).
- Avoid dewing and condensation.
- Be sure to provide an appropriate fail-safe function to prevent secondary product damage caused by malfunction (e.g. use VDR for limitation of overvoltage condition).

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of passive electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of a passive electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of a passive electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as “hazardous”)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order.
We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the “General Terms of Delivery for Products and Services in the Electrical Industry” published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, EPCOS-JONES, Baoke, CeraDiode, CSSP, MLSC, PhaseCap, PhaseMod, SIFI, SIKOREL, SilverCap, SIMID, SIOV, SIP5D, SIP5K, UltraCap, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.