




Description



Mechanical Dimensions



BAS19...21

Features

- PLANAR PROCESS
- 200 mW POWER DISSIPATION
- INDUSTRY STANDARD SOT-23 PACKAGE
- MEETS UL SPECIFICATION 94V-0

	<i>BAS19...21</i>			Units
	BAS19	BAS20	BAS21	
Maximum Ratings				
Peak Repetitive Reverse Voltage... V_{RRM}	120	200	250	Volts
Continuous Reverse Voltage... V_R	100	150	200	Volts
Average Forward Rectified Current... $I_{F(AV)}$		200		mAmps
Non-Repetitive Peak Forward Current... I_{FSM}				Amps
$t = 1\mu s$		2.5		
$t = 1s$		0.5		
Repetitive Peak Forward Current... I_{FRM}		625		mAmps
Forward Current (DC)... I_F		200		mAmps
Junction Temperature... T_J		150		°C
Storage Temperature Range... T_{STRG}		-55 to 150		°C
Power Dissipation... P_D		250		mWatts
Electrical Characteristics				
Maximum Forward Voltage... V_F				Volts
$I_F = 100\text{ mA}$		1.0		
$I_F = 200\text{ mA}$		1.25		
Maximum Reverse Current @ Rated V_R ... I_R				nAmps
$T_J = 25^\circ C$		100		
$T_J = 150^\circ C$		100		μ Amps
Maximum Reverse Recovery Time... t_{RR}		75		ns
Typical Differential Resistance @ $I_F = 10\text{mA}$... R_{DIFF}		5.0		Ω