

Surface mount diode

Schottky barrier rectifiers diodes

SK 32...SK 310

Forward Current: 3 A

Reverse Voltage: 20 to 100 V

Features

- Max. solder temperature: 260°C
- Plastic material has UL classification 94V-0

Mechanical Data

- Plastic case SMC / DO-214AB
- Weight approx.: 0,21 g
- Terminals: plated terminals solderable per MIL-STD-750
- Mounting position: any
- Standard packaging: 3000 pieces per reel

1) Max. temperature of the terminals $T_T = 100^\circ\text{C}$

2) $I_F = 3 \text{ A}$, $T_J = 25^\circ\text{C}$

3) $T_A = 25^\circ\text{C}$

4) Mounted on P.C. board with 50 mm² copper pads at each terminal

Type	Polarity color band	Repetitive peak reverse voltage V_{RRM} V	Surge peak reverse voltage V_{RSM} V	Maximum forward voltage $T_j = 25^\circ\text{C}$ $I_F = 3 \text{ A}$	Maximum reverse recovery time $I_F = -A$ $I_R = -A$ $I_{RR} = -A$ t_{rr} ns
SK 32	-	20	20	0,5	-
SK 33	-	30	30	0,5	-
SK 34	-	40	40	0,5	-
SK 35	-	50	50	0,75	-
SK 36	-	60	60	0,75	-
SK 38	-	80	80	0,85	-
SK 310	-	100	100	0,85	-

Absolute Maximum Ratings

$T_A = 25^\circ\text{C}$, unless otherwise specified



Symbol	Conditions	Values	Units
I_{FAV}	Max. averaged fwd. current, R-load, $T_T = 100^\circ\text{C}$	3	A
I_{FRM}	Repetitive peak forward current $f > 15 \text{ Hz}^1)$	20	A
I_{FSM}	Peak fwd. surge current 50 Hz half sinus-wave ³⁾	100	A
I_{Ft}	Rating for fusing, $t < 10 \text{ ms}^3)$	50	A ² s
R_{thA}	Max. thermal resistance junction to ambient ⁴⁾	50	K/W
R_{thT}	Max. thermal resistance junction to terminals	10	K/W
T_j	Operating junction temperature	-50...+150	°C
T_s	Storage temperature	-50...+150	°C

Characteristics

$T_A = 25^\circ\text{C}$, unless otherwise specified

Symbol	Conditions	Values	Units
I_R	Maximum leakage current, $T_j = 25^\circ\text{C}$; $V_R = V_{RRM}$ $T_j = 100^\circ\text{C}$; $V_R = V_{RRM}$	<0,5 <20,0	mA mA
C_J	Typical junction capacitance (at MHz and applied reverse voltage of V)	-	pF
Q_{rr}	Reverse recovery charge ($U_R = V$; $I_F = A$; $dI_F/dt = A/\text{ms}$)	-	μC
E_{RSM}	Non repetitive peak reverse avalanche energy ($I_R = \text{mA}$; $T_j = {}^\circ\text{C}$; inductive load switched off)	-	mJ

Dimensions in mm



case: SMC / DO-214AB

SK 32 ... SK 310




Fig. 1 Forward characteristic (typical values)




Fig. 2 Rated forward current vs. temp. of the terminals ⁴⁾