



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE1451 Integrated Circuit 2-Channel, Low Noise, Equalizer Amp

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Supply Voltage, V_{CC}	36V
Power Dissipation, P_D	350mW
Operating Temperature Range, T_{opr}	-20° to +80°C
Storage Temperature Range, T_{stg}	-40° to +125°C

Electrical Characteristics: ($T_A = +25^\circ\text{C}$, $V_{CC} = 30\text{V}$, $R_L = 47\text{k}\Omega$, $f = 1\text{kHz}$, unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Circuit Current	I_{CC}		-	7	10	mA
Voltage Gain	V_G		38	40	42	dB
Output Voltage Gain	V_{GO}		85	89	-	dB
Output Voltage	V_O	THD = 0.1%	6	8	-	V
Total Harmonic Distortion	THD	$V_O = 2\text{V}$	-	0.05	0.1	%
Input Resistance	r_i		-	200	-	$\text{k}\Omega$
Input Voltage	V_{IN}	$R_g = 2.3\text{k}\Omega$, RIAA	-	1	2	μV

Pin Connection Diagram

