


# US 3A ... US 3S



## Surface mount diode

## Ultrafast silicon rectifier diodes

### US 3A...US 3S

Forward Current: 3 A

Reverse Voltage: 50 to 1200 V

### Features

- Max. solder temperature: 260°C
- Plastic material has UL classification 94V-0

### Mechanical Data

- Plastic case: SMC / DO214AB
- Weight approx.: 0,12 g
- Terminals: plated terminals solderable per MIL-STD-750
- Mounting position: any
- Standard packaging: 3000 pieces per reel

1) Max. temperature of the terminals  $T_T = 100^\circ\text{C}$

2)  $I_F = 3\text{ A}$ ,  $T_j = 25^\circ\text{C}$

3)  $T_A = 25^\circ\text{C}$

4) Mounted on P.C. board with 50 mm<sup>2</sup> copper pads at each terminal

Type	Polarity color band	Repetitive peak reverse voltage $V_{RRM}$ V	Surge peak reverse voltage $V_{RSM}$ V	Maximum forward voltage $T_j = 25^\circ\text{C}$ $I_F = 3\text{ A}$ $V_F^{(2)}$ V	Maximum reverse recovery time $I_F = 0,5\text{ A}$ $I_R = 1\text{ A}$ $I_{RR} = 0,25\text{ A}$ $t_{rr}$ ns
US 3A	-	50	50	1	50
US 3B	-	100	100	1	50
US 3D	-	200	200	1	50
US 3G	-	400	400	1,25	50
US 3J	-	600	600	1,7	75
US 3K	-	800	800	1,7	75
US 3M	-	1000	1000	1,7	75
US 3S	-	1200	1200	1,7	75

### Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ , unless otherwise specified

Symbol	Conditions	Values	Units
$I_{FAV}$	Max. averaged fwd. current, R-load, $T_T = 100^\circ\text{C}$	3	A
$I_{FRM}$	Repetitive peak forward current ( $f > 15\text{ Hz}^1$ )	15	A
$I_{FSM}$	Peak fwd. surge current 50 Hz half sinus-wave <sup>3)</sup>	100	A
$I^2t$	Rating for fusing, $t < 10\text{ ms}^3$ )	50	A <sup>2</sup> s
$R_{thA}$	Max. thermal resistance junction to ambient <sup>4)</sup>	50	K/W
$R_{thT}$	Max. thermal resistance junction to terminals	10	K/W
$T_j$	Operating junction temperature	-50...+150	°C
$T_s$	Storage temperature	-50...+150	°C

### Characteristics $T_A = 25^\circ\text{C}$ , unless otherwise specified

Symbol	Conditions	Values	Units
$I_R$	Maximum leakage current, $T_j = 25^\circ\text{C}$ ; $V_R = V_{RRM}$ $T_j = 100^\circ\text{C}$ ; $V_R = V_{RRM}$	<10 <300	$\mu\text{A}$ $\mu\text{A}$
$C_j$	Typical junction capacitance (at MHz and applied reverse voltage of V)	-	pF
$Q_{rr}$	Reverse recovery charge ( $U_R = V$ ; $I_F = A$ ; $dI_F/dt = A/ms$ )	-	$\mu\text{C}$
$E_{RSM}$	Non repetitive peak reverse avalanche energy ( $I_R = mA$ ; $T_j = ^\circ\text{C}$ ; inductive load switched off)	-	mJ

