


## HIGH VOLTAGE SCHOTTKY BARRIER DIODE

### ■ Outline drawings, mm




### ■ Features

- High voltage
- Low VF
- Super high speed switching
- High reliability by planer design

### ■ Applications

- High speed switching

### ■ Marking



### ■ Maximum ratings and characteristics

- Absolute maximum ratings (Tc=25°C Unless otherwise specified )

Item	Symbol	Conditions	Rating	Unit
Repetitive peak reverse voltage	V <sub>RRM</sub>		200	V
Average forward current	I <sub>FAV</sub>	Square wave duty=1/2 T <sub>i</sub> =122°C	3.0	A
Non-repetitive forward surge current	I <sub>FSM</sub>	Sine wave 10ms, 1shot	80	A
Operating junction temperature	T <sub>j</sub>		150	°C
Storage temperature	T <sub>stg</sub>		-40 to +150	°C







- Electrical characteristics (Tc=25°C Unless otherwise specified )

Item	Symbol	Conditions	Max.	Unit
Forward voltage	V <sub>F</sub>	I <sub>FM</sub> =3.0A	1.25	V
Reverse current	I <sub>R</sub>	V <sub>R</sub> =V <sub>RRM</sub>	150	μA

- Mechanical characteristics

Approximate mass	1.2	g
------------------	-----	---

## ■ Characteristics



$\lambda$ : Conduction angle of forward current for each rectifier element

