



TO-92



Pin Definition:

1. Emitter
2. Collector
3. Base

SOT-89



Pin Definition:

1. Base
2. Collector
3. Emitter

PRODUCT SUMMARY

BV_{CBO}	-50V
BV_{CEO}	-50V
I_C	-3A
V_{CE(SAT)}	-0.5V @ I _C / I _B = -2A / -200mA

Features

- Low V_{CE(SAT)} -0.25 @ I_C / I_B = 2A / 200mA (Typ.)
- Complementary part with TSD882S

Structure

- Epitaxial Planar Type
- PNP Silicon Transistor

Ordering Information

Part No.	Package	Packing
TSD772SCT B0	TO-92	1Kpcs / Bulk
TSD772SCT A3	TO-92	2Kpcs / Ammo
TSD772SCY RM	SOT-89	1Kpcs / 7" Reel

Absolute Maximum Rating (Ta = 25°C unless otherwise noted)

Parameter	Symbol	Limit	Unit
Collector-Base Voltage	V _{CBO}	-50	V
Collector-Emitter Voltage	V _{CEO}	-50	V
Emitter-Base Voltage	V _{EBO}	-5	V
Collector Current	DC	-3	A
	Pulse	-7 (note)	
Collector Power Dissipation	SOT-89	0.75	W
	TO-92	0.625	
Operating Junction Temperature	T _J	+150	°C
Operating Junction and Storage Temperature Range	T _{STG}	- 55 to +150	°C

Note: Single pulse, Pw≤350us, Duty≤2%

Electrical Specifications (Ta = 25°C unless otherwise noted)

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Collector-Base Breakdown Voltage	I _C = -50uA, I _E = 0	BV _{CBO}	-50	--	--	V
Collector-Emitter Breakdown Voltage	I _C = -1mA, I _B = 0	BV _{CEO}	-50	--	--	V
Emitter-Base Breakdown Voltage	I _E = -50uA, I _C = 0	BV _{EBO}	-5	--	--	V
Collector Cutoff Current	V _{CB} = -30V, I _E = 0	I _{CBO}	--	--	-1	uA
Emitter Cutoff Current	V _{EB} = 3V, I _C = 0	I _{EBO}	--	--	-1	uA
Collector-Emitter Saturation Voltage	I _C / I _B = -2A / -200mA	*V _{CE(SAT)}	--	-0.3	-0.5	V
Base-Emitter Saturation Voltage	I _C / I _B = -2A / -200mA	*V _{BE(SAT)}	--	-1	-2	V
DC Current Transfer Ratio	V _{CE} = -2V, I _C = -1A	*h _{FE}	100	--	500	
Transition Frequency	V _{CE} = -5V, I _C = -100mA, f = 100MHz	f _T	--	80	--	MHz
Output Capacitance	V _{CB} = -10V, f = 1MHz	Cob	--	55	--	pF

* Pulse Test: Pulse Width ≤380uS, Duty Cycle ≤2%

Electrical Characteristics Curve (Ta = 25°C, unless otherwise noted)

Figure 1. DC Current Gain




Figure 2. Vce(sat) v.s. Ic




Figure 3. Vbe(sat) v.s. Ic






Figure 4. Power Derating Curve




TO-92 Mechanical Drawing



TO-92 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.30	4.70	0.169	0.185
B	4.30	4.70	0.169	0.185
C	14.30(typ)		0.563(typ)	
D	0.43	0.49	0.017	0.019
E	2.19	2.81	0.086	0.111
F	3.30	3.70	0.130	0.146
G	2.42	2.66	0.095	0.105
H	0.37	0.43	0.015	0.017

SOT-89 Mechanical Drawing



SOT-89 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.40	4.60	0.173	0.181
B	1.50	1.7	0.059	0.070
C	2.30	2.60	0.090	0.102
D	0.40	0.52	0.016	0.020
E	1.50	1.50	0.059	0.059
F	3.00	3.00	0.118	0.118
G	0.89	1.20	0.035	0.047
H	4.05	4.25	0.159	0.167
I	1.4	1.6	0.055	0.068
J	0.35	0.44	0.014	0.017

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.