

Part Number: NT03 22291

Ordering Different Lead Types:

Inside Kinked Leads	Use -A after Ametherm's part #
Outside Kinked Leads	Use -B after Ametherm's part #

For example: to order an inside kinked lead use part number NT03 22291-A



Electrical Specifications:

Zero-Power Resistance @25°C	2.20KΩ ± 10%
R@0°C/R@50°C	9.11 ± 2%
R@25°C/R@125°C	29.27 ± 2%
Beta	3950 ± 2%
Temp Coefficient of Resistance @ 25°C	-4.40 %/°C
Operating Temperature Range	-50°C/150°C
Maximum Permissible Power (W)	0.45W
Dissipation Constant (mW/°C)	3.5mW/°C
Thermal Time Constant	10 seconds

Mechanical Specifications:

D	2.92 ± 0.4 mm
T	2.92 ± 0.4 mm
Lead Diameter	0.5 ± 0.2 mm
S	3.0 mm Nom
L	40.0 ± 4.0 mm
Straight Leads	Standard

Revision Date: March 19, 2003

Ametherm, Inc. 3111 N. Deer Run Road #4 Carson City, NV 89701
 Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670

www.ametherm.com



DATA SHEET

Part Number: NT03 22291

Resistance Temperature Curve:

Temperature	R@T/R@25°C
-50	66.97
-45	47.25
-40	33.74
-35	24.37
-30	17.80
-25	13.13
-20	9.776
-15	7.348
-10	5.570
-5	4.257
0	3.279
5	2.550
10	1.998
15	1.576
20	1.252
25	1.000
30	0.8038
35	0.6499
40	0.5282
45	0.4316
50	0.3545
55	0.2949
60	0.2465
65	0.2070
70	0.1747
75	0.1481
80	0.1261
85	0.1077
90	0.09243
95	0.07961
100	0.06881
105	0.05977
110	0.05210
115	0.04560
120	0.04005
125	0.03529
130	0.03119
135	0.02766
140	0.02460
145	0.02194
150	0.01963

Ametherm, Inc. 3111 N. Deer Run Road #4 Carson City, NV 89701
Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670

www.ametherm.com