

High Current, Surface Mount Inductor



FEATURES

- High energy storage
- Low resistance
- Tape and reel packaging for automatic handling
- 100 % lead (Pb)-free and RoHS compliant


RoHS
COMPLIANT

ELECTRICAL SPECIFICATIONS

Inductance Range: 1.0 H to 1000 μ H, tested at 1.0 Vrms

Inductance Tolerance: 20 %, tighter tolerances available upon request

Operating Temperature: - 40 °C to + 125 °C

Resistance to Solder Heat: 260 °C for 10 seconds

MATERIALS

Core: Ferrite

Wire: Enamelled copper wire Base: LCP

Terminal: Nickel bronze

Adhesive: Epoxy resin

STANDARD ELECTRICAL SPECIFICATIONS					
INDUCTANCE (μ H)	TOLERANCE	TEST FREQUENCY L (kHz)	DCR MAXIMUM (Ohms)	Isat (Amps)	Irms (Amps)
1.0	$\pm 20\%$	100	0.009	9.0	6.8
1.5	$\pm 20\%$	100	0.010	8.0	6.4
2.2	$\pm 20\%$	100	0.012	7.0	6.1
3.3	$\pm 20\%$	100	0.015	6.4	5.4
4.7	$\pm 20\%$	100	0.018	5.4	4.8
6.8	$\pm 20\%$	100	0.027	4.6	4.4
10	$\pm 20\%$	100	0.038	3.8	3.9
15	$\pm 20\%$	100	0.046	3.0	3.1
22	$\pm 20\%$	100	0.085	2.6	2.7
33	$\pm 20\%$	100	0.10	2.0	2.1
47	$\pm 20\%$	100	0.14	1.6	1.8
68	$\pm 20\%$	100	0.20	1.4	1.5
100	$\pm 20\%$	100	0.28	1.2	1.3
150	$\pm 20\%$	100	0.40	1.0	1.0
220	$\pm 20\%$	100	0.61	0.8	0.8
330	$\pm 20\%$	100	1.02	0.6	0.6
470	$\pm 20\%$	100	1.27	0.5	0.5
680	$\pm 20\%$	100	2.02	0.4	0.4
1000	$\pm 20\%$	100	3.00	0.3	0.3

Inductance drop = 10 % typ. at Isat

 Δ GT = 15°C typ. at Irms

DIMENSIONS in inches [millimeters]								
A (Max.)	B (Max.)	D (Max.)	E	F	G	H	I	J
0.510 [12.95]	0.370 [9.40]	0.205 [5.21]	0.100 [2.54]	0.100 [2.54]	0.300 [7.62]	0.115 [2.92]	0.290 [7.37]	0.110 [2.79]

DESCRIPTION				
IDC-5020 MODEL	10 μH INDUCTANCE VALUE	$\pm 20\%$ INDUCTANCE TOLERANCE	ER PACKAGE CODE	e3 JEDEC LEAD (Pb)-FREE STANDARD
GLOBAL PART NUMBER				
I D C PRODUCT FAMILY	5 0 2 0 SIZE	E R PACKAGE CODE	1 0 0 INDUCTANCE VALUE	M TOL.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.