



Features

User controls and interfaces:

- Simple menu-guided operation using front panel mounted pushbuttons and an LCD
- User-selectable alarm parameters
- Data logging of last 40 events
- SNMP interface adapter available
- RS232 interface and Form "C" dry alarm contacts
- Compatible with PowCom™ PC-based software

Intelligent battery management:

- Temperature compensation with programmable compensation factor
- Automatic and manual load testing
- Battery voltage and symmetry monitoring
- Remaining battery capacity measurement
- Low voltage disconnect

Description

The PCU10 provides monitoring and control for the PPS 10, 11, and 13 power systems. These hot-swappable controller modules supervise AC inputs, output voltages and currents, rectifier performance, battery condition, and breaker status. Visual notification of an alarm condition is provided with an LED. A description of the exact alarm condition is provided through an LCD. Additionally, four Form "C" contacts are provided to indicate a failure.

Input

Voltage	18-72V DC
Current	<200 mA at 48V, <400 mA at 24V

Interface

Display	2x16 character LCD
Communications	RS232 serial interface for remote control from a PC with PowCom software.
Indications	Green LED - Power ON Yellow LED - System warning Red LED - System alarm
Controls	Four pushbutton controls allow menu navigation

Alarms

Alarm History	The last 40 events are saved and include a time and date stamp.	
Alarm Contacts	Four potential free change over alarm contacts. Two open collector outputs for LVD.	
Alarms	High DC Voltage	1*
	Low DC Voltage	1*
	Load/ Battery Disc.	1*
	Battery Fuse Failure	1*
	DC Fuse Failure	1*
	Module Failure	2*
	Urgent Module Failure	1*
	Main AC Failure	3*
	Battery Failure	4*
	Symmetry Failure	4*
	High Temperature	4*
	High Load	2*
<p>* All alarms are indicated using an LED and displayed in the LCD. The numbers represent an example of alarm routing: 1) Urgent alarm, 2) Service alarm, 3) Main AC failure, 4) Battery related failure Alarms are configurable by changing the EPROM</p>		

Other Technical Data

Dimensions (WxHxD)	62 x 262 x 232mm (2.4 x 10.3 x 9.1in)	
Weight	0.5kg (1.1 lb.)	
Operating Temperature	-25 to +55 °C	
Storage Temperature	-50 to +85 °C	
Environment	Storage:	ETS 300 019-2-1
	Transport:	ETS 300 019-2-2
	Operation:	ETS 300 019-2-3

Battery Management

Battery Disconnection	An optional feature that allows voltage disconnection of batteries.
Boost Charging	Manual time controlled or automatic boost charging with adjustable time and voltage levels.
Battery Test	Automatic or manual testing of batteries up to four times per year. Variables include: test duration, end voltage, Ah, and allowable symmetry variation.
Symmetry Measurement	Optional tool that measures batteries for early detection of thermal runaway. Allows for separate measurements of up to three parallel battery branches, each divided into four blocks.
Temperature Compensation Charging	Allows continuous adjustment of output voltage according to battery temperature. Feature includes adjustable compensation factor and separate thresholds for alarms.
Load Shedding (PLD)	Optional feature that allows voltage or time controlled disconnection of non-essential load.

NUCLEAR AND MEDICAL APPLICATIONS - Power-One products are not designed, intended for use in, or authorized for use as critical components in life support systems, equipment used in hazardous environments, or nuclear control systems without the express written consent of the respective divisional president of Power-One, Inc.

TECHNICAL REVISIONS - The appearance of products, including safety agency certifications pictured on labels, may change depending on the date manufactured. Specifications are subject to change without notice.