

SIKOREL® 125

Long-life grade capacitors



KAL0574-T

Applications

- High-reliability equipment in automotive power electronics, e.g. integrated starter alternator
- Applications with highest ripple current load at high frequencies

Features

- Outstanding ripple current capability
- Optimized for high frequencies
- Optimized design for bottom cooling
- Low profile
- Vibration resistance 30 g upon request
- Stud mounting upon request
- Shelf life up to 10 years
- All-welded construction ensures reliable electrical contact

Construction

- Charge-discharge proof, polar
- Aluminum case without insulating sleeve (for bottom cooling)
- Poles with screw terminal connections
- Mounting with ring clips or clamps


Specifications and characteristics in brief

Rated voltage U_R	25 ... 63 VDC	
Surge voltage U_S	$1,15 \cdot U_R$	
Rated capacitance C_R	3 900 to 20 000 μ F	
Capacitance tolerance	$\pm 20 \% \triangleq M$	
Leakage current I_L (5 min, 20 °C)	$I_L \leq 0,3 \mu\text{A} \cdot \left(\frac{C_R}{\mu\text{F}} \cdot \frac{U_R}{\text{V}}\right)^{0,7} + 4 \mu\text{A}$	
Self-inductance ESL	Approx. 13 nH	
Useful life 125 °C, U_R ; I_{-R} 85 °C, U_R ; I_{-max} 40 °C, U_R ; $3,4 \cdot I_{-R}$	> 2 500 h > 15 000 h >200 000 h	Requirements: $\Delta C/C \leq \pm 45 \%$ of initial value $ESR \leq 3$ times initial specified limit $I_L \leq$ initial specified limit Failure percentage: $\leq 1 \%$ Failure rate: ≤ 20 fit ($\leq 20 \cdot 10^{-9}/\text{h}$) (for definition "fit", refer to chapter "Quality", page 62)
Voltage endurance test 125 °C; U_R ; I_{-R}	2 000 h	Post test requirements: $\Delta C/C \leq \pm 15 \%$ of initial value $ESR \leq 1,3$ times initial specified limit $I_L \leq$ initial specified limit
Vibration resistance	To IEC 60068-2-6, test Fc: displacement amplitude 0,75 mm, frequency range 10 to 55 Hz, acceleration max. 10 g, duration 3×2 h Vibration resistance up to 30 g upon request	
IEC climatic category	To IEC 60068-1: 55/125/56 (– 55 °C/+ 125 °C/56 days damp heat test)	
Detail specifications	Similar to CECC 30301-803, CECC 30301-807	
Sectional specification	IEC 60384-4	

Ripple current capability

Due to the ripple current capability of the contact elements, the following current upper limits must not be exceeded:

$$I_{-max} = 50 \text{ A}$$

In case of additional thermal cooling:


$$I_{-max} = 55 \text{ A}$$



B41754

Automotive – 125 °C

Dimensional drawing



Positive pole marking: +

KAL0824-B-E

Stud mounting upon request

Dimensions, weights and packing units

Terminal	Dimensions (mm)						Approx. weight (g)	Packing unit pieces
	$d +0/-0,4$	$l \pm 0,8$	$l_1 \pm 0,8$	$l_3 +0,2/-1$	$d_2 \pm 0,2$	$a +0,2/-0,4$		
M 5	50,9	39,5	46,1	7,0	8,2	22,2	115	22
M 5	50,9	49,5	56,1	7,0	8,2	22,2	135	22

For ecological reasons the packing is pure cardboard.

Accessories

The following items are included in the delivery package, but are not fastened to the capacitors:

	Thread	Toothed washers	Screws/Nuts	Maximum torque
For terminals	M 5	A 5,1 DIN 6797	Cylinder-head screw M 5 × 8 DIN 84-4.8	2 Nm
	M 6	A 6,4 DIN 6797	Cylinder-head screw M 6 × 12 DIN 85-4.8	2,5 Nm

The following must be ordered separately:

Ring clips

B44030 (cf. page 169)

Insulating parts

B44020 (cf. page 166)


Overview of available types

U_R (VDC)	25	40	55	63
C_R (μ F)	Case dimensions $d \times l$ (mm)			
3 900				50,9 × 39,5
4 700			50,9 × 39,5	
6 000				50,9 × 49,5
7 500		50,9 × 39,5	50,9 × 49,5	
12 000	50,9 × 39,5	50,9 × 49,5		
20 000	50,9 × 49,5			

Case dimensions and ordering codes

U_R VDC	C_R μ F	Case dimensions $d \times l$ mm	Ordering code
25	12 000	50,9 × 39,5	B41754A5129M000
	20 000	50,9 × 49,5	B41754A5209M000
40	7 500	50,9 × 39,5	B41754A7758M000
	12 000	50,9 × 49,5	B41754A7129M000
55	4 700	50,9 × 39,5	B41754A0478M000
	7 500	50,9 × 49,5	B41754A0758M000
63	3 900	50,9 × 39,5	B41754A8398M000
	6 000	50,9 × 49,5	B41754A8608M000


B41754
Automotive – 125 °C
Technical data


C_R	ESR_{typ} 100 Hz 20 °C mΩ	ESR_{max} 100 Hz 20 °C mΩ	ESR_{max} 100 Hz -40 °C mΩ	ESR_{max} 10 kHz 20 °C mΩ	Z_{max} 10 kHz 20 °C mΩ	$I_{\sim max(B)}$ 10 kHz 85 °C A	$I_{\sim max(B)}$ 10 kHz 105 °C A	$I_{\sim R}$ 10 kHz 125 °C A	$I_{\sim R(B)}$ 10 kHz 125 °C A
25 VDC									
12 000	21	36	234	27	28	50 ¹⁾	50 ¹⁾	7,6	20
20 000	14	24	156	18	19	50 ¹⁾	50 ¹⁾	8,5	21
40 VDC									
7 500	21	36	234	27	28	50 ¹⁾	50 ¹⁾	7,6	20
12 000	15	25	162	18	19	50 ¹⁾	50 ¹⁾	8,5	21
55 VDC									
4 700	23	39	234	28	30	50 ¹⁾	50 ¹⁾	7,6	20
7 500	17	29	174	23	24	50 ¹⁾	50 ¹⁾	8,5	21
63 VDC									
3 900	23	39	234	28	30	50 ¹⁾	50 ¹⁾	7,6	20
6 000	17	29	174	23	24	50 ¹⁾	50 ¹⁾	8,5	21

1) Max. 50 A due to max. terminal load
55 A in case of additional terminal cooling



Useful life

depending on ambient temperature T_A (for natural cooling) and versus temperature of case base T_B (for base cooling) under ripple current operating conditions at U_{R1} ¹⁾




Depending on ambient temperature T_A (for natural cooling) and versus temperature of case base T_B (for base cooling) under ripple current operating conditions at U_{op} ¹⁾

$U_R = 25 V: U_{op} \leq 22 V$

$U_R = 55 V: U_{op} \leq 48 V$

$U_R = 40 V: U_{op} \leq 35 V$

$U_R = 63 V: U_{op} \leq 55 V$



3500 h rated service life at 125 °C;
up to 500 h (accumulated) operating at 150 °C in discontinuous operation


1) Refer to page 40 for an explanation on how to interpret the useful life graphs.




B41754

Automotive – 125 °C

Frequency factor of permissible ripple current I_{\sim} versus frequency f




Frequency characteristics of ESR typical behavior



Impedance Z

at different temperatures T

Typical behavior for 3900 μ F/63 V



Herausgegeben von EPCOS AG

Unternehmenskommunikation, Postfach 80 17 09, 81617 München, DEUTSCHLAND

☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Vervielfältigung, Veröffentlichung, Verbreitung und Verwertung dieser Broschüre und ihres Inhalts ohne ausdrückliche Genehmigung der EPCOS AG nicht gestattet.

Bestellungen unterliegen den vom ZVEI empfohlenen Allgemeinen Lieferbedingungen für Erzeugnisse und Leistungen der Elektroindustrie, soweit nichts anderes vereinbart wird.

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen Vertrieb der EPCOS AG oder an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer Erfordernisse Gefahrstoffe enthalten. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft einzuholen.

Published by EPCOS AG

Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY

☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.