






ADSL LINE TRANSFORMER

For Use with Texas Instruments Chipset



-  Matched to Texas Instruments TNETD4500C CO chipsets
-  Designed to meet IEC950 supplementary insulation requirements for working voltages up to 250 Vrms
-  Excellent THD Performance
-  Industry standard surface mount footprint

Electrical Specifications @ 25°C — Operating Temperature -40°C to 85°C

Part Number	Turns Ratio (Line:Chip)	OCL Primary ($\mu\text{H} \pm 6\%$)	Leakage Inductance ($\mu\text{H} \text{ MAX}$)	DCR Primary (1-3 & 2-4) ($\Omega \text{ MAX}$)	DCR Secondary (10-8 & 9-7) ($\Omega \text{ MAX}$)	Isolation Voltage (Vrms)	THD @ 100kHz, 5.0 Vp-p (dB MIN)
B2243 ¹	2 : 1	400	5.0	0.5	0.3	1500	-80
B2133 ²	2 : 1	75	5.0	0.5	0.3	1500	-80

NOTE: Optional Tape & Reel packaging can be ordered for either part by adding a "T" suffix to the part number (ex: B2243T).



¹ B2243 is designed for ADSL over POTS applications where THS6012/72 Line Drivers and Active termination is used.

² B2133 is designed for ADSL over ISDN applications where THS6012/72 Line Drivers and Active termination is used.

Mechanical

Schematic

B2243/B2133



Weight6.2 grams
 Tape and Reel150/reel
 Tray60/tray

Dimensions: Inches
 mm
 Unless otherwise specified,
 all tolerances are $\pm \frac{.010}{0,25}$

For More Information :

UNITED STATES (Worldwide)	UNITED KINGDOM (Northern Europe)	FRANCE (Southern Europe)	SINGAPORE (Southern Asia)	TAIWAN, R.O.C. (Northern Asia)	HONG KONG (China/Hong Kong)	DISTRIBUTOR
12220 World Trade Drive San Diego, CA 92128 U.S.A. http://www.pulseeng.com TEL: 858 674 8100 FAX: 858 674 8262	1 & 2 Huxley Road The Surrey Research Park Guildford, Surrey GU2 5RE United Kingdom TEL: 44 1483 401700 FAX: 44 1483 401701	Zone Industrielle F-39270 Orgelet France TEL: 33 3 84 35 04 04 FAX: 33 3 84 25 46 41	150 Kampong Ampat #07-01/02 KA Centre Singapore 368324 TEL: 65 6287 8998 FAX: 65 6280 0080	3F-4, No. 81, Sec. 1 HsinTai Wu Road Hsi-Chih, Taipei Hsien Taiwan, R.O.C. Tel: 886 2 2698 0228 FAX: 886 2 2698 0948	9/F, Phase 2, Tai Sang Shatin Warehouse Centre 6 Wong Chuk Yeung Street Fotan, Shatin, Hong Kong TEL: 852 2788 6588 FAX: 852 2776 1055	

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.