

Inductors

Commercial, Molded, Shielded, Miniature



FEATURES

- Flame retardant coating
- Electromagnetic shield
- Small package for a shielded inductor
- Epoxy molded construction provides superior moisture protection
- Precision performance, excellent reliability, sturdy construction



RoHS
COMPLIANT

ELECTRICAL SPECIFICATIONS

Inductance Tolerance: ± 10 % standard. ± 5 % available
Insulation Resistance: 1000 Megohm minimum per MIL-STD-202, Method 302, Test Condition B

Dielectric Withstanding Voltage: 200 VAC per MIL-STD-202, Method 301 (sea level).

Percent Coupling: 3 % maximum per MIL-PRF-15305
Operating Temperature Range: - 55 °C to + 105 °C

STANDARD ELECTRICAL SPECIFICATIONS							
IND. (µH)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF- [*] RESONANT FREQ. MIN. (MHz)	DCR MAX. (Ohms)	RATED ^{**} DC CURRENT (mA)	
0.10	± 10 %	54	25.0	490.0	0.10	670	IRON CORE
0.12	± 10 %	52	25.0	430.0	0.11	635	
0.15	± 10 %	50	25.0	415.0	0.12	610	
0.18	± 10 %	49	25.0	375.0	0.13	585	
0.22	± 10 %	47	25.0	330.0	0.15	545	
0.27	± 10 %	46	25.0	300.0	0.16	530	
0.33	± 10 %	44	25.0	260.0	0.18	495	
0.39	± 10 %	42	25.0	230.0	0.19	485	
0.47	± 10 %	41	25.0	220.0	0.21	460	
0.56	± 10 %	41	25.0	210.0	0.23	440	
0.68	± 10 %	39	25.0	180.0	0.24	430	
0.82	± 10 %	38	25.0	165.0	0.27	405	
1.0	± 10 %	37	25.0	150.0	0.30	385	
1.2	± 10 %	40	7.9	130.0	0.73	247	IRON CORE
1.5	± 10 %	41	7.9	115.0	0.86	228	
1.8	± 10 %	43	7.9	105.0	0.95	217	
2.2	± 10 %	45	7.9	95.0	1.1	202	
2.7	± 10 %	48	7.9	90.0	1.2	193	
3.3	± 10 %	49	7.9	80.0	1.3	185	
3.9	± 10 %	50	7.9	75.0	1.5	173	
4.7	± 10 %	53	7.9	70.0	2.4	136	
5.6	± 10 %	54	7.9	60.0	2.9	124	
6.8	± 10 %	55	7.9	55.0	3.2	118	
8.2	± 10 %	55	7.9	53.0	3.6	111	
10.0	± 10 %	57	7.9	50.0	4.0	106	
12.0	± 10 %	36	2.5	35.0	3.0	122	
15.0	± 10 %	38	2.5	30.0	3.4	115	
18.0	± 10 %	40	2.5	26.0	3.8	108	
22.0	± 10 %	40	2.5	24.0	4.9	96	
27.0	± 10 %	40	2.5	21.0	5.8	88	
33.0	± 10 %	41	2.5	20.0	6.5	83	
39.0	± 10 %	42	2.5	19.0	7.9	75	
47.0	± 10 %	44	2.5	16.0	9.3	69	
56.0	± 10 %	44	2.5	15.0	11.0	64	
68.0	± 10 %	45	2.5	13.0	12.0	61	
82.0	± 10 %	45	2.5	11.0	13.0	59	
100.0	± 10 %	40	2.5	10.5	16.8	51	

* Measured with full length lead. ** **Rated DC Current:** Based on the maximum temperature rise not to exceed 15 °C at + 90 °C ambient.



MECHANICAL SPECIFICATIONS

Terminal Strength: 3 pounds pull per MIL-STD-202, Method 211, Test Condition A except 180° rotation for a total of 540 °C

Weight: IMS-2 = 0.30 grams maximum

MATERIAL SPECIFICATIONS


Encapsulant: Epoxy

Standard Terminal: #24 AWG tinned copper

TEST EQUIPMENT*


- H/P 4342A Q-Meter
- Measurements Corporation Megacycle Meter, Model 59
- Wheatstone Bridge

* Test procedures per MIL-PRF-15305



ENVIRONMENTAL PERFORMANCE		
TEST	CONDITIONS	SPECIFICATIONS
Barometric Pressure	Test Condition C	MIL-STD-202, Method 105
Thermal Shock	Test Condition A-1	MIL-STD-202, Method 107
Flammability	-	MIL-STD-202, Method 111
Overload	-	MIL-PRF-15305
Low Temperature Storage	-	MIL-PRF-15305
Resistance to Soldering Heat	Test Condition A	MIL-STD-202, Method 210
Resistance to Solvents	-	MIL-STD-202, Method 215

ORDERING INFORMATION				
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD
IMS-2	10 μ H	$\pm 10\%$	ER	e2





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.