



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE1297 Integrated Circuit TV Color Signal Processor/Demodulator

Description:

The NTE1297 is an integrated circuit consisting of an NTSC color signal processor and demodulator circuit. APC color synchronization and DC color-phase control is employed to ensure stability.

Features:

- Peak-type ACC Detector
- Internal Setting of ACC and Color Killer Levels
- APC System uses Sample and Hold for Color Synchronization
- Detector Circuit has Output Temperature Characteristics

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$, unless otherwise specified)

Supply Voltage, V_{CC}	16V
Power Dissipation, P_D	1.4W
Derating ($T_A \geq 25^\circ\text{C}$), K_θ	14mW/ $^\circ\text{C}$
Operating Temperature Range, T_{opg}	-20° to +75°C
Storage Temperature Range, T_{stg}	-40° to +125°C

Electrical Characteristics: ($T_A = +25^\circ\text{C}$, $V_{CC} = 12\text{V}$ unless otherwise specified)

Parameter	Symbol	Test Conditions			Min	Typ	Max	Unit
		Color Signal Input (dB)	Pin 2 Voltage (V)	Pin 8 Voltage (V)				
Circuit Current	I_{CC}	Off	6	6	27	38	49	mA
Color Signal Max. Gain	G_c	-22	8	6	36	42	47	dB
Color Signal Max. Output	V_{cmax}	0	8	6	0.9	1.25	1.6	V_{p-p}
ACC Control Range (Note 1)	R_{ACC}	-	6	6	-18	-	-	dB

Electrical Characteristics (Cont'd): ($T_A = +25^\circ\text{C}$, $V_{CC} = 12\text{V}$ unless otherwise specified)

Parameter	Symbol	Test Conditions			Min	Typ	Max	Unit
		Color Signal Input (dB)	Pin 2 Voltage (V)	Pin 8 Voltage (V)				
Killer Operational Input Level	$V_{I(K)}$	-	6	6	-46	-37	-28	dB
Color Saturation Characteristics	C	0	4 to 8	6	40	-	-	dB
Color Phase Characteristics	T	0	5.5	4 to 8	-	90	-	Deg.
APC Pull-In Range	F_p	0	6	6	± 400	-	-	Hz
Output Voltage	E_{ODC}	Off	6	6	6.6	7.0	7.4	V_{DC}
Output Offset Voltage	ΔE_{ODC}	Off	6	6	-	-	0.3	V_{DC}
Output Voltage Temp. Coefficient	$\delta E_{ODC}/\delta T$	Off	6	6	-2	0	2	$\text{mV}/^\circ\text{C}$
Max. Demodulation Output Voltage (Note 2)	E_{omax}	0	8	6	4	-	-	V_{p-p}
B-Y Demodulation Sensitivity (Note 2,3)	E_{CO}	0	-	6	3	4	5	V_{p-p}
Demodulated Output Voltage Ratio (Note 2,4)	$E_o(R-Y)/E_o(B-Y)$	0	-	6	-	0.81	-	
	$E_o(G-Y)/E_o(B-Y)$	0	-	6	-	0.32	-	
Demodulated Phase Angle	$\theta R-Y$	0	5.5	6	-	106	-	Deg.
	$\theta B-Y$	0	5.5	6	-	259	-	Deg.

Note *. Color Input signal consists of 50mV_{p-p} burst portion and 100mV_{p-p} color portion, treated as 0dB levels (frequency = $3.579545\text{MHz} \pm 5\text{Hz}$)

Note 1. ACC control range is the input level when color output voltage is decreased by 3dB, compared with color output voltage which occurs with a 0dB color input signal.

Note 2. Color portion frequency = 3.50MHz .

Note 3. For color signal output voltage of $0.5V_{p-p}$

Note 4. For color signal output voltage of $0.3V_{p-p}$

Pin Connection Diagram

GND	1		22	Color Signal Input
Color Saturation Control	2		21	Bypass
Burst Gate Pulse Input	3		20	ACC Filter
APC Filter	4		19	Killer Filter
APC Filter	5		18	Color Signal Output
Quartz Control	6		17	B - Y Signal Input
Quartz Control	7		16	R - Y Signal Input
Color Phase Control	8		15	Vcc
Color Subcarrier Output	9		14	B - Y Output
B - Y Subcarrier Input	10		13	R - Y Output
R - Y Subcarrier Input	11		12	G - Y Output

