

Capsule Type Rectifier Diode SHXXC760





Symbol	Characteristics	Conditions	T _J (°C)	Value	Unit
BLOCKING PARAMETERS					
V _{RRM}	Repetitive peak reverse voltage		180	200-600	V
I _{RRM}	Repetitive peak reverse current	V = V _{RRM}	180	25	mA
CONDUCTING PARAMETERS					
I _{F(AV)}	Average on-state current	180 sine, 50Hz, T _C = 104°C		760	A
I _{RMS}	RMS on-state current			1200	A
I _{FSM}	Non repetitive peak surge on-state current	Sine wave, 10mS without reverse voltage	180	8500	A
I ² t	Permissible surge energy			361	kA ² S
V _{FM}	Peak on-state voltage drop	On-state current = 2000A	180	1.39	V
V ₀	Typical forward conduction Threshold voltage		180	0.70	V
r ₀	Typical forward slope resistance		180	0.30	mΩ
THERMAL & MECHANICAL PARAMETERS					
R _{TH(J-C)}	Thermal impedance, 180° conduction, Sine	Junction to case		0.079	°C/W
R _{TH(C-HK)}	Thermal impedance	Case to heatsink		0.015	°C/W
T _J	Maximum Permissible junction temperature			180	°C
T _{STG}	Storage temperature range			-40 – 180	°C
F	Mounting Torque			6.5	KN
W	Weight			70	gms




HIND RECTIFIERS LTD

Capsule Type Rectifier Diode SHXXC760



All dimensions in mm


On State Power Loss




HIND RECTIFIERS LTD




Maximum Permissible Case Temp




Max non repetitive Surge Current







Transient Thermal Impedance Junction to Case



On State Characteristics



Capsule Type Rectifier Diode SHXXC760



Ordering Information: -

SH	XX	C	760
Hirect make Capsule Diode	$V_{RRM} = XX * 100$ e.g.6 * 100 =600V	Capsule Diode	$I_{F(AV)} = 760A$

Hind Rectifiers Ltd reserves the right to change the specifications without notice.

This datasheet specifies technical information for semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.

Hind Rectifiers Ltd
Lake Road
Bhandup (West)
Mumbai – 400 078
Tel: - +91 22 2596 8027/28/29/31
Fax: - +91 22 2596 4114
E-mail: - marketing@hirect.com
Website: - www.hirect.com

June-2008



HIND RECTIFIERS LTD

5 of 5