

isc Silicon NPN Power Transistors

2SC3519/A

DESCRIPTION



- Collector-Emitter Breakdown Voltage-
 $V_{(BR)CEO} = 160V(\text{Min})$ -2SC3519
 $= 180V(\text{Min})$ -2SC3519A
- Good Linearity of h_{FE}
- Complement to Type 2SA1386/A

APPLICATIONS

- Designed for audio and general purpose applications

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	2SC3519	160
		2SC3519A	180
V_{CEO}	Collector-Emitter Voltage	2SC3519	160
		2SC3519A	180
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current-Continuous	15	A
I_B	Base Current-Continuous	4	A
P_C	Collector Power Dissipation @ $T_C=25^\circ\text{C}$	130	W
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-55~150	$^\circ\text{C}$



isc Silicon NPN Power Transistors

2SC3519/A

ELECTRICAL CHARACTERISTICS

 $T_C=25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	2SC3519	$I_C=25\text{mA}; I_B=0$			V
		2SC3519A				
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=5.0\text{A}; I_B=0.5\text{A}$			2.0	V
I_{CBO}	Collector Cutoff Current	2SC3519	$V_{CB}=160\text{V}; I_E=0$			μA
		2SC3519A				
I_{EBO}	Emitter Cutoff Current	$V_{EB}=5\text{V}; I_C=0$			100	μA
h_{FE}	DC Current Gain	$I_C=5\text{A}; V_{CE}=4\text{V}$	50		180	
C_{OB}	Output Capacitance	$I_E=0; V_{CB}=10\text{V}; f_{test}=1.0\text{MHz}$		250		pF
f_T	Current-Gain—Bandwidth Product	$I_E=-2\text{A}; V_{CE}=12\text{V}$		50		MHz

Switching Times

t_{on}	Turn-on Time	$I_C=10\text{A}, R_L=4\Omega,$ $I_{B1}=-I_{B2}=1\text{A}, V_{CC}=40\text{V}$		0.2		μs
t_{stg}	Storage Time			1.3		μs
t_f	Fall Time			0.45		μs

◆ h_{FE} Classifications

O	P	Y
50-100	70-140	90-180