


CHA Series

- No sparks against DC over-voltage
- Downsized from current KLG series
- Endurance with ripple current : 105°C, 2000hours
- Non solvent-proof type
- Pb-free design




◆SPECIFICATIONS

Items	Characteristics		
Category Temperature Range	-25 to +105°C		
Rated Voltage Range	200 & 400Vdc		
Capacitance Tolerance	$\pm 20\%$ (M) (at 20°C, 120Hz)		
Leakage Current	$I=3\sqrt{CV}$ Where, I : Max. leakage current (μ A), C : Nominal capacitance (μ F), V : Rated voltage (Vdc) (at 20°C after 5 minutes)		
Dissipation Factor (tan δ)	200Vdc : 0.15 max. (0.20 max. for $\phi D=35mm$) 400Vdc : 0.15 max. (at 20°C, 120Hz)		
Low Temperature Characteristics (Max.Impedance Ratio)	Rated Voltage (Vdc)	200V	400V
	$Z(-25^\circ\text{C}) / Z(+20^\circ\text{C})$	4	4
ESL	50nH max. (at 120Hz)		
Endurance	The following specifications shall be satisfied when the capacitors are restored to 20°C after subjected to DC voltage with the rated ripple current is applied for 2000 hours at 105°C. Capacitance change $\leq \pm 20\%$ of the initial value D.F. (tan δ) $\leq 200\%$ of the initial specified value Leakage current \leq The initial specified value		
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1000 hours at 105°C without voltage applied. Capacitance change $\leq \pm 15\%$ of the initial value D.F. (tan δ) $\leq 150\%$ of the initial specified value Leakage current \leq The initial specified value		


◆DIMENSIONS [mm]

- Terminal Code : VS ($\phi 22$ to $\phi 35$)



No plastic disk is the standard design

◆PART NUMBERING SYSTEM



Please refer to "A guide to global code (snap-in type)"

◆RATED RIPPLE CURRENT MULTIPLIERS

- Frequency Multipliers

Frequency (Hz)	50	120	300	1k	10k	50k
200 & 400Vdc	0.77	1.00	1.16	1.30	1.41	1.43

CHA Series

◆STANDARD RATINGS

WV (Vdc)	Cap (μ F)	Case size ϕ DXL(mm)	$\tan\delta$	Rated ripple current (Arms/ 105°C, 120Hz)	Part No.	WV (Vdc)	Cap (μ F)	Case size ϕ DXL(mm)	$\tan\delta$	Rated ripple current (Arms/ 105°C, 120Hz)	Part No.
200	180	22×20	0.15	0.82	ECHA201VSN181MP20S	400	56	22×20	0.15	0.45	ECHA401VSN560MP20S
	220	22×20	0.15	0.90	ECHA201VSN221MP20S		68	22×20	0.15	0.51	ECHA401VSN680MP20S
	270	22×25	0.15	1.02	ECHA201VSN271MP25S		82	22×25	0.15	0.58	ECHA401VSN820MP25S
	330	22×30	0.15	1.20	ECHA201VSN331MP30S		100	22×25	0.15	0.66	ECHA401VSN101MP25S
	330	25.4×25	0.15	1.20	ECHA201VSN331MQ25S		100	25.4×25	0.15	0.66	ECHA401VSN101MQ25S
	390	22×30	0.15	1.35	ECHA201VSN391MP30S		120	22×30	0.15	0.76	ECHA401VSN121MP30S
	390	25.4×25	0.15	1.35	ECHA201VSN391MQ25S		120	25.4×25	0.15	0.76	ECHA401VSN121MQ25S
	470	22×35	0.15	1.45	ECHA201VSN471MP35S		150	22×35	0.15	0.85	ECHA401VSN151MP35S
	470	25.4×30	0.15	1.45	ECHA201VSN471MQ30S		150	25.4×30	0.15	0.85	ECHA401VSN151MQ30S
	470	30×25	0.15	1.47	ECHA201VSN471MR25S		150	30×25	0.15	0.85	ECHA401VSN151MR25S
	560	22×40	0.15	1.62	ECHA201VSN561MP40S		180	22×40	0.15	0.94	ECHA401VSN181MP40S
	560	25.4×30	0.15	1.60	ECHA201VSN561MQ30S		180	25.4×35	0.15	0.95	ECHA401VSN181MQ35S
	560	30×25	0.15	1.60	ECHA201VSN561MR25S		180	30×25	0.15	0.95	ECHA401VSN181MR25S
	680	25.4×35	0.15	1.82	ECHA201VSN681MQ35S		220	25.4×35	0.15	1.24	ECHA401VSN221MQ35S
	680	30×30	0.15	1.81	ECHA201VSN681MR30S		220	30×30	0.15	1.24	ECHA401VSN221MR30S
	680	35×25	0.20	1.86	ECHA201VSN681MA25S		270	25.4×45	0.15	1.30	ECHA401VSN271MQ45S
	820	25.4×45	0.15	2.11	ECHA201VSN821MQ45S		270	30×35	0.15	1.30	ECHA401VSN271MR35S
	820	30×35	0.15	2.11	ECHA201VSN821MR35S		270	35×25	0.15	1.30	ECHA401VSN271MA25S
	820	35×25	0.20	2.11	ECHA201VSN821MA25S		330	30×40	0.15	1.47	ECHA401VSN331MR40S
	1000	30×35	0.15	2.40	ECHA201VSN102MR35S		330	35×30	0.15	1.47	ECHA401VSN331MA30S
	1000	35×30	0.20	2.40	ECHA201VSN102MA30S						
	1200	30×45	0.15	2.69	ECHA201VSN122MR45S						
	1200	35×35	0.20	2.65	ECHA201VSN122MA35S						


◆DC OVERVOLTAGE TEST CONDITIONS

The vent will operate and the capacitor shall become an open circuit without burning materials when the following excess DC voltage is applied.

●Test DC voltage

Rated Voltage	Nominal Capacitance	Current Limit	Test Voltage
200Vdc	<330 μ F	4A	300/375Vdc
	330≤C<470 μ F	5A	
	≥470 μ F	7A	
400Vdc	<100 μ F	2A	500/600Vdc
	100≤C<220 μ F	4A	
	≥220 μ F	7A	

●Test Circuit



Constant DC voltage/current power supply