



# Frontier Electronics Corp.

667 E. COCHRAN STREET, SIMI VALLEY, CA 93065

TEL: (805) 522-9998 FAX: (805) 522-9989

E-mail: frontiersales@frontierusa.com

Web: frontierusa.com

## Multi-layers Chip Inductors--TF100505 (0402) Series--Ceramic


### A. Electrical specifications:

Part No.	L @100MHz (nH)	Tolerance	Q Typical		SRF min. (MHz)	DCR (Max) Ω	I rms. (mA)
			@100MHz	@800MHz			
TF100505-1N0S	1.0	S	10	28	6000	0.10	300
TF100505-1N2S	1.2	S	9	28	6000	0.10	300
TF100505-1N5S	1.5	S	10	30	6000	0.10	300
TF100505-1N8S	1.8	S	10	28	6000	0.10	300
TF100505-2N2S	2.2	S	10	30	6000	0.20	300
TF100505-2N7S	2.7	S	10	30	5500	0.20	300
TF100505-3N3	3.3	S, K	10	30	5000	0.30	300
TF100505-3N9	3.9	S, K	11	31	4700	0.30	300
TF100505-4N7	4.7	S, K	10	30	4300	0.40	300
TF100505-5N6	5.6	S, K	11	31	4000	0.40	300
TF100505-6N8	6.8	J, K	10	31	3650	0.50	300
TF100505-8N2	8.2	J, K	12	34	3200	0.50	300
TF100505-10N	10.0	J, K	12	32	2800	0.60	300
TF100505-12N	12.0	J, K	12	31	2700	0.60	300
TF100505-15N	15.0	J, K	11	30	2200	0.70	300
TF100505-18N	18.0	J, K	11	29	2000	0.8	300
TF100505-22N	22.0	J, K	11	28	1800	0.90	300
TF100505-27N	27.0	J, K	12	27	1600	1.00	300
TF100505-33N	33.0	J, K	10	25	1700	1.50	200
TF100505-39N	39.0	J, K	10	25	1650	1.80	200
TF100505-47N	47.0	J, K	9	23	1300	2.00	200

### B. Dimensions: [Unit: mm /( inch)]

P/N & Package Size	A	B	C	D (min.)
TF100505 (0402)	1.0 ± 0.1 (0.04 ± 0.004)	0.5 ± 0.1 (0.020 ± 0.004)	0.5 ± 0.1 (0.020 ± 0.004)	0.100 (0.004)

### C. Part Number Key & Mechanical drawing:



### D. Features:

1. Tolerance: K: ±10%, J: ±5%, D: ±0.5nH, S: ±0.3nH.
2. The product's material: **Ceramic**.
3. No cross coupling between inductors due to magnetic shield. Ideal for high-density installation.
4. Superior Q characteristics guaranteed over the wide frequency and allow high frequency application.
5. The completely monolithic structure gives high reliability and allows high SRF.
6. Operating temperature range: -25°C to +85°C.
7. Both flow and IR re-flow application are possible.
8. Inductance Range:  
\*TF1005 (0402) Series: Multi-layer Ceramic Chip Inductor, from 1.0 nH (300mA) to 47.0 nH (200mA)

**Note:** For “RoHS” parts, we add “-LFR” after the part number.