

RF AMPLIFIER

MODEL BXMP1027

Available as: BXMP1027, SMA Connectorized Housing
3.9" X 3.0" (H-91)

Features

- n Medium Gain: 10.5 dB Typical
- n High Output Power: 4 Watts Typical
- n High Third Order Intercept: +61 dBm Typical
- n High Second Order Intercept: +95 dBm Typical
- n Operating Temp. - 40 °C to +85 °C
- n Environmental Screening Available

Specifications

CHARACTERISTIC		TYPICAL Ta= 25 °C	MIN/MAX Ta = -40 °C to +85 °C
Frequency		50 - 500 MHz	50 - 500 MHz
Gain (dB)		10.5	10.0 Min.
Power @ 1 dB Comp. (dBm)		+37.0	+33.5 Min.
Reverse Isolation (dB)		-17.0	-15.0 Max.
VSWR	In	1.5:1	2.0:1 Max.
	Out	1.5:1	2.0:1 Max.
Noise Figure (dB)		4.0	5.5 Max.
Power	Vdc	+15	+15
	m A	2200	2500 Max.

Note: Care should always be taken to effectively ground the case of each unit.


Typical Intermodulation Performance at 25 ° C

- Second Order Harmonic Intercept Point.....+100 dBm (Typ.)
- Second Order Two Tone Intercept Point.....+95 dBm (Typ.)
- Third Order Two Tone Intercept Point.....+61 dBm (Typ.)

Maximum Ratings

- Ambient Operating Temperature -45°C to +100 °C
- Storage Temperature -50°C to +125 °C
- Case Temperature +125 °C
- DC Voltage +17 Volts
- Continuous RF Input Power +24 dBm
- Short Term RF Input Power . 400 Milliwatts (1 Minute Max.)
- Maximum Peak Power 0.5 Watt (3 µsec Max.)

Typical Performance Data



Legend ——— + 25 °C - - - + 85 °C ····· -40 °C



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532

Rev.
11/9/07

www.SpectrumMicrowave.com · Spectrum Microwave · 2707 Black Lake Place · Philadelphia, Pennsylvania 19154 · PH (215) 464-4000 · Fax (215) 464-4001