

UPDATED: 05/08/2008

EMP210-P1


9.5 – 12.0 GHz Power Amplifier MMIC

FEATURES

- 9.5 12.0 GHz Operating Frequency Range
- 23.5dBm Output Power at 1dB Compression
- 16.0 dB Typical Small Signal Gain
- -40dBc OIMD3 @Each Tone Pout 12.5dBm

APPLICATIONS

- Point-to-point and point-to-multipoint radio
- Military Radar Systems



Optional Packaging solutions are available Contact the Excelics sales team for details.

Caution! ESD sensitive device.

ELECTRICAL CHARACTERISTICS (T_a = 25 °C, 50 ohm, VDD=7V, IDQ=180mA)

SYMBOL	PARAMETER/TEST CONDITIONS	MIN	ТҮР	МАХ	UNITS
F	Operating Frequency Range	9.5		12.0	GHz
P1dB	Output Power at 1dB Gain Compression	21.0	23.5		dBm
Gss	Small Signal Gain	14.0	16.0		dB
OIMD3	Output 3 rd Order Intermodulation Distortion @∆f=10MHz, Each Tone Pout 12.5dBm		-40	-37	dBc
Input RL	Input Return Loss		-10	-8	dB
Output RL	Output Return Loss		-8	-6	dB
ldss	Saturate Drain Current $V_{DS} = 3V, V_{GS} = 0V$	211	264	317	mA
V _{DD}	Power Supply Voltage		7	8	V
Rth	Thermal Resistance (Au-Sn Eutectic Attach)		34		°C/W
Tb	Operating Base Plate Temperature	-35		+85	°C

ABSOLUTE MAXIMUM RATINGS FOR CONTINUOUS OPERATION^{1,2}

SYMBOL	CHARACTERISTIC	VALUE	
V _{DS}	Drain to Source Voltage	8 V	
V_{GS}	Gate to Source Voltage	-4 V	
I _{DD}	Drain Current	ldss	
I _{GSF}	Forward Gate Current	4mA	
P _{IN}	Input Power	@ 3dB compression	
Т _{сн}	Channel Temperature	150°C	
T _{STG}	Storage Temperature	-65/150°C	
Ρ _T	Total Power Dissipation	3.4W	

1. Operating the device beyond any of the above rating may result in permanent damage.

2. Bias conditions must also satisfy the following equation $V_{DS}*I_{DS} < (T_{CH} - T_{HS})/R_{TH}$; where T_{HS} = ambient temperature



EMP210-P1

UPDATED: 05/08/2008

9.5 – 12.0 GHz Power Amplifier MMIC

DISCLAIMER

EXCELICS SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. EXCELICS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN.

LIFE SUPPORT POLICY

EXCELICS SEMICONDUCTOR PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF EXCELICS SEMICONDUCTOR, INC.

AS HERE IN:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.