

Specifications

Parameter	Unit	Minimum	Typical	Maximum
Center Frequency	MHz	134.35	134.5	134.65
Insertion Loss	dB	-	25	28
3 dB Bandwidth	MHz	11.6	11.68	-
35 dB Bandwidth	MHz	-	12.38	12.5
40 dB Bandwidth	MHz	-	12.43	-
45dB Bandwidth	MHz	-	12.48	-
50 dB Bandwidth	MHz	-	12.53	12.8
55 dB Bandwidth	MHz	-	12.6	13
Passband Variation	dB	-	1.4	1.6
Absolute Delay	usec	-	3.86	4.5
Ultimate Rejection(f0±15MHz)	dB	55	60	-
Material Temperature coefficient	KHz/°C	-12.64		
Ambient Temperature	°C	25		
Package Size	DIP3512 (35.0x12.8x4.7mm3)			

Notes:

1. All specifications are based on the test circuit shown
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
4. This is the optimum impedance in order to achieve the performance show

Matching Configuration



Source /Load Impedance = 50 ohm


Notes - Component values may change depending
on board layout.



SIPAT Co., Ltd.
(CETC No.26 Research Institute)
#14 Nanping Huayuan Road,
Chongqing, China, 400060

Part Number	LBN13505		
Rev. Date	2007-08-16		
Ver.	1.0	Page 1/4	

Package Dimension



- 1) ∙: Pad Number 1 Index
- 2) SIPAT: Manufacturer name
- 3) LBN13505: Part Number
- 4) 07XX: Date Code

Input	1
Output	5
Ground	All Others


Package: DIP3512

Unit: mm

	SIPAT Co., Ltd. (CETC No.26 Research Institute) #14 Nanping Huayuan Road, Chongqing, China, 400060	Part Number	LBN13505	
		Rev. Date	2007-08-16	
		Ver.	1.0	Page 2/4


Typical Performance

Frequency Response




Horizontal: 5MHz/Div Vertical: 10dB/Div

Passband Response




Horizontal: 2MHz/Div Vertical: 0.5dB/Div

Group Delay Variation (f0±5MHz)




Horizontal: 2MHz/Div Vertical: 100ns/Div

Phase Linearity (f0±5MHz)




Horizontal: 2MHz/Div Vertical: 10deg/Div

Smith Chart S11



Smith Chart S22



SIPAT Co., Ltd.
(CETC No.26 Research Institute)
#14 Nanping Huayuan Road,
Chongqing, China, 400060

Part Number

LBN13505

Rev. Date

2007-08-16

Ver.

1.0

Page 3/4

Maximum Ratings

Operating Temperature Range	°C	[-40°C;+85°C]
Storage Temperature Range	°C	[-40°C;+105°C]
DC Voltage	V	0
Input Power	dBm	10 max
ESD Class		1

	SIPAT Co., Ltd. (CETC No.26 Research Institute) #14 Nanping Huayuan Road, Chongqing, China, 400060	Part Number	LBN13505	
		Rev. Date	2007-08-16	
		Ver.	1.0	Page 4/4