

PART NUMBER SMI - LXFT0603GC-TR

E.C.N. NUMBER AND REVISION COMMENTS DATE E.C.N. #10967. 3,14,03

REV.

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C f=20mA					
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		565		nm	
FORWARD VOLTAGE		2.0	2.6	Vf	
REVERSE VOLTAGE	5.0			V_r	I _r =100µA
AXIAL INTENSITY		10		mcd	$I_f = 20 \text{mA}$
VIEWING ANGLE		120		2x theta	
EMITTED COLOR:	GREEN				
EPOXY LENS FINISH:	WATER C	LEAR			

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	100	mW
DERATE FROM 25°C	- 2.0	mW/°C
OPERATING TEMP.	- 25 TO + 85	°C
STORAGE TEMP.	- 30 TO +85	*C
* 1 (40 6		

* t<10µS

NOTES:

1. PARTS PACKAGED IN CONDUCTIVE COVER AND CARRIER TAPE. 2. THE CATHODE IS ORIENTED TOWARDS THE TAPE SPROCKET HOLE.

CAUTION: MOISTURE SENSITIVE DEVICE PER JEDEC LEVEL 4 STANDARDS

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.127 (±0.005). LEAD SIZE=±0.05 (0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX.= +0.00 -DECIMAL PRECISION MAX.= +0.00 -DECIM

REV. PART NUMBER SML-LXFT0603GC-TR

TAPE FEED DIRECTION -

1.6mm x 0.8mm ULTRA THIN SURFACE MOUNT LED. 565nm GREEN LED, WATER CLEAR LENS. TAPE AND REEL.

LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY:

CHECKED BY:

APPROVED BY: DATE: 11.1.02 PAGE: 1 OF 1

N/A

SCALE:

CT