



|                  |                  |
|------------------|------------------|
| <b>Spec. No.</b> | PS-LL-U305YL4-A0 |
| <b>Rev.</b>      | A                |

# PRODUCT SPECIFICATION

**Model No : CSLR-U305YL4-A0**

| Descriptions:    |                     |
|------------------|---------------------|
| ■ LED Type       | : Lighting LED Lamp |
| ■ LED Package    | : Round LED Lamp    |
| ■ Emitting Color | : Yellow            |
| ■ Viewing Angle  | : 30°               |
| ■ No Stopper     |                     |



| CUSTOMER APPROVED SIGNATURES | APPROVED BY | CHECKED BY | PREPARED BY |
|------------------------------|-------------|------------|-------------|
|                              |             |            |             |

**CHINA SEMICONDUCTOR CORPORATION**  
Address: 2FL. NO.909, Chung-Cheng Road,  
Chung-Ho City Taipei Hsien, Taiwan.

**OPTO PLUS TECHNOLOGIES CO.,LTD**  
Address: 696 Shun jiang Rd., Ji Shan St. Shaoxing,  
ZheJiang, China

Tel: 886-2-2223-9696  
Fax: 886-2-2223-9377

Tel: 86-0575-88623888  
Fax: 86-0575-88623112



**Model No : CSLR-U305YL4-A0**


**Features -**

1. Low Power Consumption.
2. High Luminous Output
3. High Reliability and Solid Performance
4. Optimal Optical/Mechanical Design
5. Rohs Compliant

**Device Selection Guide -**

| Part No.        | Chip     |               | LED Lens          |
|-----------------|----------|---------------|-------------------|
|                 | Material | Emitted Color |                   |
| CSLR-U305YL4-A0 | AlInGaP  | Yellow        | Water Transparent |

**Package Outline Dimensions -**



\* Tolerance :  $\pm \frac{0.01}{0.25}$  Unit :  $\pm \frac{\text{inch}}{\text{mm}}$



Model No : CSLR-U305YL4-A0

■ Absolute Maximum Rating -

(Ta=25°C)

| Parameter                  | Symbol | Rating   | Unit |
|----------------------------|--------|--|------|
| Power Dissipation          | Pd     | 52   | mW   |
| Forward Current (DC)       | IF     | 30   | mA   |
| Peak Forward Current *     | IFP    | 100  | mA   |
| Reverse Voltage            | VR     | 5  | V    |
| Operating Temp.            | Topr   | -30 ~ +80  | °C   |
| Storage Temp.              | Tstg   | -40 ~ +100   | °C   |
| Lead Soldering Temperature | Tsol   | Max. 260°C for 5 sec Max.<br>(3mm from the epoxy body) |      |

\* Pulse width  $\leq 0.1$  msec. duty  $\leq 1/10$

■ Electro-optical Characteristics

(Ta=25°C)

| Parameter           | Symbol         | Min.  | Typ.  | Max.  | Unit    | Condition |
|---------------------|----------------|-------|-------|-------|---------|-----------|
| Forward Voltage     | VF             | ----- | 2.1   | 2.6   | V       | IF=20mA   |
| Luminous Intensity  | Iv             | 6600  | 11000 | ----- | mcd     |           |
| Dominant Wavelength | $\lambda D$    | ----- | 590   | ----- | nm      |           |
| Viewing Angle       | 2 $\theta$ 1/2 | ----- | 30    | ----- | deg     |           |
| Reverse Current     | IR             | ----- | ----- | 50    | $\mu A$ | VR=5V     |



**Model No : CSLR-U305YL4-A0**

**■ Luminous Intensity Rank Limits (  $I_f = 20\text{mA}$  )**

unit : mcd

| Part No. | CSLR-U305YL4-A0 |       |
|----------|-----------------|-------|
| Code     | min.            | max.  |
| V        | 6600            | 8600  |
| W        | 8600            | 11200 |
| X        | 11200           | 14600 |
| Y        | 14600           | 19000 |
| Z        | 19000           | 24700 |

**■ Dominant Wavelength Rank Limits (  $I_f = 20\text{mA}$  )**

unit : nm

| Part No. | CSLR-U305YL4-A0 |       |
|----------|-----------------|-------|
| Code     | min.            | max.  |
| Y3       | 589.5           | 592   |
| Y4       | 592             | 594.5 |
| Y5       | 594.5           | 597   |

**■ Forward Voltage Rank Limits (  $I_f = 20\text{mA}$  )**

unit : v

| Part No. | CSLR-U305YL4-A0 |      |
|----------|-----------------|------|
| Code     | min.            | max. |
| B        | 1.6             | 1.8  |
| C        | 1.8             | 2.0  |
| D        | 2.0             | 2.2  |
| E        | 2.2             | 2.4  |
| F        | 2.4             | 2.6  |

Notes:


1. Tolerance of measurement of luminous intensity :±15%
2. Tolerance of measurement of Color Coordinates :±0.01
3. Tolerance of measurement of forward voltage :±0.05v
4. All data are measured by CSC's test equipment.
5. One delivery will include several color rank, VF rank and Iv ranks of the products.
6. The quantity-ratio of the ranks is decided by CSC.
7. Please confirm with CSC salesman,if your request different form standard specification.




Model No : CSLR-U305YL4-A0

■ Typical Electrical / Optical Characteristics Curves -


(Ta = 25°C Unless Otherwise Noted)




Ambient Temperature Ta (°C)  
Fig 1. Forward Current  
Vs. Ambient Temperature



Forward Voltage VF (V)  
Fig. 2 Forward Current  
Vs. Forward Voltage



Forward Current IF (mA DC)  
Fig 3. Relative Intensity  
Vs. Forward Current



Forward Voltage (V)  
Fig. 4 Peak Forward Voltage  
Vs. Forward Current  
(100us test pulse, 1% duty cycle)




Fig 5. Relative Intensity Vs. Wavelength




Fig 6. Relative Luminous Intensity vs. Radiation Angle




Model No : CSLR-U305YL4-A0

## ■ Precautions For Use -

### 1. Recommended Soldering conditions

#### Wave Soldering



### 2. Soldering Iron

Basic SPEC. is  $\leq 5$ sec. When  $260^{\circ}\text{C}$ . If temperature is higher, time should be shorter ( $+10^{\circ}\text{C} \rightarrow -1$ sec.). Power dissipation of iron should be smaller than 15W, and temperature should be controllable. Surface temperature of the device should be under  $230^{\circ}\text{C}$ .

### 3. Static Electricity

- Static electricity or surge voltage damages LEDs.  
It is recommended that a wrist band or an anti-electrostatic glove be used when handling the LEDs.
- All devices, equipment and machinery must be properly grounded. It is recommended that measures be taken against surge voltage to the equipment that mounts the LEDs.

Note: The specifications are subject to change without notice. Please contact us for updated information.