

EURO Package Precision OCXO



Model: FTE5__AH Series

Preliminary

Rev. 11/10/2006

Page 1 of 1

http://www.foxonline.com/need_a_sample.htm



FEATURES

- 5.0V Operation
- 12V Available
- HCMOS Output
- SC Cut Resonators
- EURO Package
- 1" x 1.4" x .75"

• PART NUMBER SELECTION Learn More - Internet Required				
Part Number	Model Number	Frequency Stability vs. Temp	Operating Temperature	*Frequency Range (MHz)
693-Frequency-xxxxx	FTE501AH	±7 PPB	0 ~ +70°C	5.000 ~ 50.000
694-Frequency-xxxxx	FTE502AH	±10 PPB	-20 ~ +70°C	5.000 ~ 50.000
695-Frequency-xxxxx	FTE503AH	±15 PPB	-40 ~ +75°C	5.000 ~ 50.000

• ELECTRICAL CHARACTERISTICS	
PARAMETERS	MAX (unless otherwise noted)
Frequency Range (Fo)	5.000 ~ 50.000 MHz*
Supply Voltage	+5 VDC ± 5%
Power (Warm-Up for 3 minutes)	3 Watts
Power Stabilized at +25°C (Still air)	0.8 Watts Typical
Voltage (± 5% Change)	±2 PPB
Short Term Aging (3 weeks min operation)	± 0.5 PPB / Day
Long Term Aging (After 60 days operation)	± 50 PPB / Year
Allan Variance (1 sec samples)	10 ⁻¹¹ / Sec
Phase Noise (Offset)	(Typical @ 10 MHz)
10 Hz	-120 dBc
100 Hz	-140 dBc
1 KHz	-155 dBc
10 KHz	-158 dBc
Warm-Up to within ± 100 PPB (Referenced to freq after 1/2 hour power on)	3 minutes
Frequency Adjust (0 to +5 VDC)	± 0.5 PPM Min.
Slope	Positive
Non-Linearity (0.8V-5.0V)	± 10%
Input Impedance	> 100 K Min
Output (Typical @ 10 MHz)	HCMOS
VOL	10% VDD
VOH	90% VDD Min
T-rise (10% ~ 90% VDD)	5 nS
T-fall (90% ~ 10% VDD)	5 nS
Duty Cycle @ 50% VDD	50% ± 5%
Resonator Type	Glass Sealed, SC Cut

All specifications subject to change without notice.

*Specifications are applicable to 10 MHz units. Performance at other frequencies will vary from these values. Other frequencies and performance is available.

Contact Fox Custom Products Center (CPC) for details at 877-369-8041 or email at <http://www.foxonline.com/email.htm>

