

330 W NEBS 3 Redundant Universal AC-DC Power Supply



Key Features

- 330 Watts Power Output, greater than 80% efficiency
- Redundant
- Front Access for use with the WR3500E, WR3500 shelves
- Universal application:
 - 95 to 264 V AC universal
 - 47 to 63 Hz
 - Input current - 6 A rms maximum
- Output over voltage/load protection
- Inrush current limited

Applications

- AC power supply for WR3500 and WR3500F shelves

Compliance

- Telcordia NEBS Level 3
- UL 60950 Third Edition (IEC 950)
- CAN/CSA C22.2 No. 60950 00 Third Edition
- FCC Class A, CE
- EN 300 386

The JDSU 1U-high power supply shelf contains two 330 W flat-profile power conversion cassettes that generate -48 V output. Each AC-DC unit is cooled by two internal fans and an alarm circuit, with Form C contacts, monitors the output voltage of each card. Mounting options include 19" or 23", via reversible ears, and ETSI. The unit features front-accessible air filters with airflow direction from front to back.

Rectangular current limiting protects output, while thermal shutdown and automatic recovery occur in the case of insufficient airflow.

2

Specifications

Parameter	Specification
Electrical¹	
Input voltage	95 to 264 V AC
Input frequency	47 to 63 Hz
Power dissipation	Typical 330 W
Output voltage	48 volts, current limited to 7.8 A, output is open
Line regulation	±1% combined from zero load to full load
Dynamic response	Maximum 5% voltage deviation for 10 to 50% load step, with more than 1 ms recovery time
Output ripple/noise	More than 50 mVrms or 300 mVpp (20 MHz BW)
Alarm relay signals	Dry contact major and minor alarms. Relay open under normal operation. Relay closed when power is off.
Physical¹	
Size (W x H x D) without power connectors	16.9 x 1.6 x 10.9 inches (430 x 40.64 x 277 mm)
Weight (approximate)	6 lbs. (2.7 Kg)
Environmental¹	
Short-term operating ambient temperature	-5 to 55 °C
Normal operating ambient temperature	0 to 40 °C
Storage temperature	-40 to 85 °C
Relative humidity, non-condensing	5 to 95%
Interface	
Input	IEC connector
Output and alarm	AMP 9-position Mate-N-Lok 350835-1
LED	Red – unit failure, Green – output power fine

1. All specifications are guaranteed over the life, operating temperatures, and wavelength range specified.

Ordering Information

For more information on this or other products and their availability, please contact your local JDSU account manager or JDSU directly at 1-800-498-JDSU (5378) in North America and +800-5378-JDSU worldwide or via e-mail at customer.service@jdsu.com.

Sample: DMS-3500PWR02

Product Code	Description
DMS-3500PWR02	Mate-N-Lock Cable and 2 AC to DC power modules
DMS-3500PMO02	Replacement AC to DC power module

Telcordia is a registered trademark of Telcordia Technologies Incorporated.

All statements, technical information and recommendations related to the products herein are based upon information believed to be reliable or accurate. However, the accuracy or completeness thereof is not guaranteed, and no responsibility is assumed for any inaccuracies. The user assumes all risks and liability whatsoever in connection with the use of a product or its application. JDSU reserves the right to change at any time without notice the design, specifications, function, fit or form of its products described herein, including withdrawal at any time of a product offered for sale herein. JDSU makes no representations that the products herein are free from any intellectual property claims of others. Please contact JDSU for more information. JDSU and the JDSU logo are trademarks of JDS Uniphase Corporation. Other trademarks are the property of their respective holders. ©2005 JDS Uniphase Corporation. All rights reserved. 10143157 Rev. 001 11/05 DMS3500PWR02.DS.CMS.AE