

P-tec Corporation Tel:(800)688-0613  
 2405 Commerce Circle Tel:(719) 589 3122  
 Alamosa Co. 81101 Fax:(719) 589 3592  
 www.p-tec.net sales@p-tec.net



## PL318 Series 3mm LED Snap-in Holder

### Features

- \*Snap-In Panel Mount Indicator
- \*Mounting Hole 4 mm (.156")
- \*No mounting Hardware required
- \*Housing Material Black Nylon UL94V-2
- \*1 Bi-Color Green/Yellow LED with White Diffused Lens used
- \*Standard Terminals
- \*RoHS Compliant

### Absolute Maximum Ratings at T<sub>A</sub> = 25°C

Power Dissipation.....	78mW
Reverse Voltage (<100 μA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6 mm below body).....	260°C for 5 seconds

### Electrical & Optical Characteristics at T<sub>A</sub> = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Lumious Intensity @20mA (mcd)	
			nm	nm	Deg	Typ	Max	Typ	Max
PL318-1GY1301	Green Yellow	GaP GaAsP	567 585	572 590	110°	2.1	2.6	5.0 4.0	11.0 9.0

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.

