

P-tec Corp. Tel:(800)688-0613
 2405 Commerce Circle Tel:(719) 589 3122
 Alamosa Co. 81101 Fax:(719) 589 3592
 www.p-tec.net sales@p-tec.net



PL318 Series 3mm LED Snap-in Holder

Features

- *Snap-In Panel Mount Indicator
- *Mounting Hole 4 mm (.156")
- *No mounting Hardware required
- *Housing Material Black Nylon UL94V-2
- *1 Red LED with Color Diffused Lens used
- *26AWG 6" (+) Red and (-) Black Wire Leads
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation.....	90mW
Reverse Voltage (<100 μA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6 mm below body).....	260°C for 5 seconds

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ 1/2	Forward Voltage @20mA (V)		Lumious Intensity @20mA (mcd)	
						Typ	Max	Typ	Max
6" Wire Leads			nm	nm	Deg				
PL318-1R24-2	Red	GaP	700	650	54°	2.1	3.0	1.5	3.0

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.

