# Single Junction Drop-In Isolator 3.3 GHz—3.4 GHz


# Technology Solutions


#### **Features**

- · Designed for WiMax market
- 25dB Isolation typical
- 0.20dB Insertion Loss typical
- Low cost package
- RoHS compliant
- Flat pack packaging

#### **Description**

This isolator is designed specifically for WiMax applications and features high reliability performance at a low cost. It is in a low cost package ideally suited for high volume manufacturing. M/A Com is one of the largest suppliers of isolator and circulators in the world.





## **Electrical Specifications**

 $T = T_{op}^{-1}, Z_0 = 50 \text{ Ohms}$ 

Parameter	Test Conditions	Units	Min	Typ @25⁰C	Max
Frequency Range		GHz	3.3		3.4
Insertion Loss	3.3 GHz—3.4 GHz	dB		0.20	0.25
Isolation	3.3 GHz—3.4 GHz	dB	20.0	25.0	
Return Loss (Port 1 & 2)	3.3 GHz—3.4 GHz	dB	20.0	25.0	
Intermodulation	3.3 GHz—3.4 GHz	dBc	60.0	65.0	
Circulation			Clockwise		

1. See "Absolute Maximum Ratings" for Top.

## **Absolute Maximum Ratings**

Parameter	Absolute Maximum		
Forward Power, CW	200 Watts		
Peak Forward Power	1000 Watts		
Reverse Power, CW	60 Watts max for 2 minutes max		
Operating Temperature	-40°C to +85°C		
Storage Temperature	-40°C to +100°C		

- ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.

  PRELIMINARY: Data Sheets contain information regarding a product WA-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.
- North America Tel: 800.366.2266 Europe Tel: +353.21.244.6400
- India Tel: +91.80.4155721
   China Tel: +86.21.2407.1588
   Visit www.macomtech.com for additional data sheets and product information.