


SPECIFICATION FOR APPROVAL

REF : 20070320-A




PAGE: 1

PROD. NAME	SMD POWER INDUCTOR	ABC'S DWG NO. ABC'S ITEM NO.	CB6011□□□□L□-□□□
---------------	--------------------	---------------------------------	------------------

. CONFIGURATION & DIMENSIONS :





A :	6.20±0.15	m / m
B :	6.60 max.	m / m
C :	1.10±0.10	m / m
D :	2.00±0.30	m / m
E :	1.50±0.20	m / m
F :	2.20 ref.	m / m
G :	6.60 ref.	m / m
H :	4.00 ref.	m / m



(PCB Pattern Suggestion)

. SCHEMATIC DIAGRAM :




. MATERIALS :

- a . Core : Ferrite core
- b . Wire : Enamelled copper wire
- c . Base : Cu/Ag(1.0um)
- d . Adhesive : Epoxy resin
- e . Remark : Products comply with RoHS' requirements

Peak Temp : 260 max.
 Max time above 230 : 50sec max.
 Max time above 200 : 70sec max.

. GENERAL SPECIFICATION :

- a . Temp. rise : 40 typ.
- b . Storage temp. : -40 ----+120
- c . Operating temp. : -40 ----+125
(included Temp. rise)
- d . Resistance to solder heat : 260 .10 secs.



SPECIFICATION FOR APPROVAL

REF : 20070320-A

PAGE: 2


PROD. NAME	SMD POWER INDUCTOR	ABC'S DWG NO.	CB6011□□□□L□-□□□
		ABC'S ITEM NO.	

. ELECTRICAL CHARACTERISTICS :

DWG No.	Inductance (μ H) 0.1V/100KHz	RDC (Ω) max.	Irms. (A) typ.	Isat. (A) max.
CB60111R5ML□-□□□	1.5 \pm 20%	0.09	1.90	2.50
CB60112R7ML□-□□□	2.7 \pm 20%	0.12	1.65	1.80
CB60114R7ML□-□□□	4.7 \pm 20%	0.17	1.38	1.55
CB60116R8ML□-□□□	6.8 \pm 20%	0.30	1.24	1.24
CB6011100ML□-□□□	10.0 \pm 20%	0.36	1.07	1.07
CB6011150ML□-□□□	15.0 \pm 20%	0.55	0.88	0.88
CB6011220ML□-□□□	22.0 \pm 20%	0.74	0.73	0.72
CB6011330ML□-□□□	33.0 \pm 20%	1.25	0.57	0.54
CB6011470ML□-□□□	47.0 \pm 20%	1.65	0.50	0.46

- 1). Packing information : [A]: Bulk [B]: Taping Reel
- 2). "- □□□ " : Reference code
- 3). I rms. base on temp. rise 40 typ.
- 4). Isat. base on L/LOA=10% max.

AR-001A



SPECIFICATION FOR APPROVAL



REF : 20070320-A

PAGE: 3

PROD. NAME	SMD POWER INDUCTOR	ABC'S DWG NO.	CB6011□□□□L□-□□□
		ABC'S ITEM NO.	

PACKAGING INFORMATION

(1) Configuration



(2) Dimensions

Unit:m/m

Style	A	B	C	D	G	N	T
07 - 12	178	21±0.8	13	12	14 ⁺⁰	50 ⁻⁰	18.4

(3) Q'TY & G.W. Per package

Series	Inner : Reel			Outer : Carton		
	Q'TY (pcs)	G.W. (gw)	Style	Q'TY (pcs)	G.W. (Kg)	Size (cm)
CB6011	1,500	330	07 - 12	60,000	13.2	42 x 41 x 24

AR-001A

SPECIFICATION FOR APPROVAL

REF : 20070320-A

PAGE: 5

PROD. NAME	SMD POWER INDUCTOR	ABC'S DWG NO.	CB6011□□□□L□-□□□
		ABC'S ITEM NO.	

. RELIABILITY TEST :

Test item	Specification	Test condition														
Solderability	More than 90% of the terminal electrode shall be covered With fresh solder.	Preheat : 150±25 for 60 seconds Solder : Sn96.5 / Ag3 / Cu0.5 or equivalent Solder temp. : 260±5 Flux : Rosin Dip time : 4±1 seconds														
Thermal shock test (Temp. cycle)	Inductance shall not change more than ±20%	<table style="width: 100%; border: none;"> <tr> <td style="border: none;">Room temp. 15 minutes</td> <td style="border: none; text-align: center;">→</td> <td style="border: none; text-align: center;"> <table style="border: none;"> <tr> <td style="border: none;">-25±2</td> <td style="border: none;">_____</td> </tr> <tr> <td style="border: none;">30 minutes</td> <td style="border: none;"></td> </tr> </table> </td> </tr> <tr> <td style="border: none;">Room temp. 15 minutes</td> <td style="border: none; text-align: center;">→</td> <td style="border: none; text-align: center;"> <table style="border: none;"> <tr> <td style="border: none;">85±2</td> <td style="border: none;">_____</td> </tr> <tr> <td style="border: none;">30 minutes</td> <td style="border: none;"></td> </tr> </table> </td> </tr> </table> Total : 50 cycles	Room temp. 15 minutes	→	<table style="border: none;"> <tr> <td style="border: none;">-25±2</td> <td style="border: none;">_____</td> </tr> <tr> <td style="border: none;">30 minutes</td> <td style="border: none;"></td> </tr> </table>	-25±2	_____	30 minutes		Room temp. 15 minutes	→	<table style="border: none;"> <tr> <td style="border: none;">85±2</td> <td style="border: none;">_____</td> </tr> <tr> <td style="border: none;">30 minutes</td> <td style="border: none;"></td> </tr> </table>	85±2	_____	30 minutes	
Room temp. 15 minutes	→	<table style="border: none;"> <tr> <td style="border: none;">-25±2</td> <td style="border: none;">_____</td> </tr> <tr> <td style="border: none;">30 minutes</td> <td style="border: none;"></td> </tr> </table>	-25±2	_____	30 minutes											
-25±2	_____															
30 minutes																
Room temp. 15 minutes	→	<table style="border: none;"> <tr> <td style="border: none;">85±2</td> <td style="border: none;">_____</td> </tr> <tr> <td style="border: none;">30 minutes</td> <td style="border: none;"></td> </tr> </table>	85±2	_____	30 minutes											
85±2	_____															
30 minutes																
Humidity Resistance test		Temperature : 40±2 Humidity : 90 ~ 95% Applied current : Per spec. Time : 500 hours														
High temp. Resistance test		Temperature : 80±2 Applied current : Per spec. Time : 500 hours														

AR-001A



SPECIFICATION FOR APPROVAL

REF : 20070320-A

PAGE: 6

PROD. NAME	SMD POWER INDUCTOR	ABC'S DWG NO.	CB6011□□□□L□-□□□
		ABC'S ITEM NO.	

. UL CARD :

OBMW2 September 8, 2000
Magnet Wire-Component
JUNG SHING WIRE CO LTD E174837
231 CHUNG CHENG RD, SEC 3 JEN-TEH HSIANG, TAINAN
HSIEN TAIWAN

Mtl Dsg	Mark Dsg	BC	Coat Typ	OC	ANSI Type	Temp Class
AIW	---	Polyamideimide		---	MW81-C	220
CFUEWB	---	Polyurethane		---	MW75C	130
EIAIW	---	Polyesterimide	Polyamideimide		MW35C	200
EILOCKY	---	Polyesterimide	Polyamide		---	180
EILOCKW	---	Polyesterimide	Modified Epoxy		---	200
EIW	---	Polyesterimide		---	---	220
EIW-2	---	Polyesterimide		---	MW74-C	200
FL.EILOCKY	---	Modified Polyester	Polyamide		---	155
LSFFW	---	Polyurethane		---	MW79-C	155
LSUEW	---	Polyurethane		---	---	130
PEW	---	Polyester		---	---	155
PEY	---	Polyester	Nylon		MW24-C	155
SF.FLW	---	Modified Polyester		---	MW26C	155
SF.EIW	---	Polyesterimide		---	MW77C	180
SF.BY@	---	Modified Polyester	Nylon		MW27-C	155
SF.FLY@	---	Modified Polyester	Nylon		MW27-C	155
SF.BLOCKBS	---	Modified Polyester	Modified Polyamide		---	155
SF.EILOCKY#	---	Polyesterimide	Polyamide		---	180
SF.EILOCKBS	---	Polyesterimide	Modified Polyamide		---	180
SF.BW@	---	Modified Polyester		---	MW26C	155
SFFW	---	Polyurethane		---	MW79	155

287806002 Page 1 of 2

A not-for-profit organization dedicated to public safety and committed to quality service

Mtl Dsg	Mark Dsg	BC	Coat Typ	OC	ANSI Type	Temp Class
SFFY	---	Polyurethane		Polyamide	MW80C	155
UEW-1	---	Polyurethane		---	MW2-C	105
UEW-2	---	Polyurethane		---	---	130
UEW-4	---	Polyurethane		---	MW75C	130
UEY	---	Polyurethane		Nylon	MW28-C	130
UEY-2	---	Polyurethane		Polyamide	MW28-C	130

287806002 Page 2 of 2

OBMW2E174837
September 8, 2000

AR-001A

