




SPECIFICATION FOR APPROVAL

REF : 20070719-B


PAGE: 1

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SU2011□□□□L□-□□□
		ABC'S ITEM NO.	

. CONFIGURATION & DIMENSIONS :



- A : 2.80 ±0.20 m/m
- B : 2.80 ±0.20 m/m
- C : 1.10 ±0.10 m/m
- D : 0.90 typ m/m
- E : 0.90 typ m/m
- F1 : 1.30 ref m/m
- F2 : 3.00 ref m/m
- G : 0.65 ref m/m
- H : 2.10 ref m/m
- I : 1.20 ref m/m
- J : 1.00 ref m/m
- R : 1.00 ref m/m



(PCB Pattern Suggestion)


. SCHEMATIC DIAGRAM :



. MATERIALS :

- a . Core : Ferrite DR core
- b . Core : Ferrite RI core
- c . Wire : Enamelled copper wire (Class H)
- d . Adhesive : Epoxy resin
- e . Terminal : Ag/Ni/Sn
- f . Remark : Products comply with RoHS' requirements

Peak Temp : 260 max.
 Max time above 230 : 50sec max.
 Max time above 200 : 70sec max.



. GENERAL SPECIFICATION :

- a . Temp. rise : 40 typ.
- b . Storage temp. : -40 ----+125
- c . Operating temp. : -40 ----+105
- d . Resistance to solder heat : 260 .10 secs.

AR-001A

SPECIFICATION FOR APPROVAL

REF : 20070719-B

PAGE: 2


PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SU2011□□□□L□-□□□
		ABC'S ITEM NO.	

ELECTRICAL CHARACTERISTICS :

DWG No.	Inductance (μ H)	Q ref.	Test Freq. (MHz)	SRF (MHz) typ.	RDC ($m\Omega$)		Irms (mA) typ.	Isat (mA) typ.	Marking
					typ.	max.			
SU20111R0YL□-□□□	1.0 \pm 30 %	6	7.96	160	75	100	1650	1500	A
SU20112R2YL□-□□□	2.2 \pm 30 %	6	7.96	120	125	165	1200	900	C
SU20113R3YL□-□□□	3.3 \pm 30 %	6	7.96	80	185	240	900	760	E
SU20114R7YL□-□□□	4.7 \pm 30 %	6	7.96	70	280	365	725	580	F
SU20116R8YL□-□□□	6.8 \pm 30 %	6	7.96	60	330	450	700	540	G
SU2011100YL□-□□□	10.0 \pm 30 %	10	2.52	45	570	740	520	400	H
SU2011150YL□-□□□	15.0 \pm 30 %	10	2.52	40	920	1200	375	340	I
SU2011220YL□-□□□	22.0 \pm 30 %	12	2.52	25	1220	1580	325	270	J
SU2011330YL□-□□□	33.0 \pm 30 %	12	2.52	24	2200	2860	230	220	K

- 1). □ : Packaging Information... [A]: Bulk [B]: Taping Reel
- 2). "- □□□ " : Reference code
- 3). Inductance Test Freq. : 100KHz /0.1V
- 4). Irms base on Temp. rise 40 typ.
- 5). Isat base on L / LOA=35% typ.

@ Inductance VS. DC Current Curve



AR-001A



SPECIFICATION FOR APPROVAL



REF : 20070719-B

PAGE: 3

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SU2011□□□□L□-□□□
		ABC'S ITEM NO.	

PACKAGING INFORMATION :

(1) Configuration



(2) Dimensions

Unit:m/m

Style	A	B	C	D	G	N	T
07 - 12	178	21±0.8	13	12	14 ⁺⁰	50 ⁻⁰	16.5

(3) Q'TY & G.W. Per package

Series	Inner : Reel			Outer : Carton		
	Q'TY (pcs)	G.W. (gw)	Style	Q'TY (pcs)	G.W. (Kg)	Size (cm)
SU2011	1,500	120	07 - 12	60,000	5.3	42 x 41 x 24

AR-001A




SPECIFICATION FOR APPROVAL

REF : 20070719-B

PAGE: 4

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SU2011□□□□L□-□□□
		ABC'S ITEM NO.	

. DWGING NUMBER EXPRESSION :



Appendix code 1 : Product Classification

- L : Lead Free Standard products comply with RoHS' requirements
- 1 ~ 9 : Lead Free Special products comply with RoHS' requirements

Appendix code 2 : Package Information

Code	Inner package	Inner package Q'TY	Remark
A	T.B.D.	T.B.D.	
B	T / R (Reel package)	1,500 pcs	

SPECIFICATION FOR APPROVAL

REF : 20070719-B

PAGE: 5

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO. ABC'S ITEM NO.	SU2011□□□□L□-□□□
---------------	--------------------------------	---------------------------------	------------------

. RELIABILITY TEST :

Test item	Specification	Test condition						
Solderability	More than 95% of the terminal electrode shall be covered with fresh solder.	Preheat : 155 / 4 hours. Solder : Sn96.5 / Ag3 / Cu0.5 or equivalent Solder temp. : 235±5 Flux : Rosin Dip time : 5±0.5 seconds						
Thermal shock test (Temp. cycle)	Electrical oharacteristics shall not change more than ±20%	<table style="width: 100%; border: none;"> <tr> <td style="text-align: center;">Room temp. 15 minutes</td> <td style="text-align: center;">→</td> <td style="text-align: center;">-40 30 minutes</td> </tr> <tr> <td style="text-align: center;">Room temp. 15 minutes</td> <td style="text-align: center;">→</td> <td style="text-align: center;">+105 30 minutes</td> </tr> </table> <p>Total : 50 cycles</p>	Room temp. 15 minutes	→	-40 30 minutes	Room temp. 15 minutes	→	+105 30 minutes
Room temp. 15 minutes		→	-40 30 minutes					
Room temp. 15 minutes		→	+105 30 minutes					
Humidity test		Temperature : 40±2 Humidity : 90±5% Time : 1000 hours						
High temp. Resistance test	Temperature : 105±5 Applied current : Per spec. Time : 96 hours							

SPECIFICATION FOR APPROVAL

REF : 20070719-B

PAGE: 6

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SU2011□□□□L□-□□□
		ABC'S ITEM NO.	

. UL CARD :

OBMW2 August 27, 1999
 Magnet Wire-Component

ELEKTRISOLA (MALAYSLA) SDN BHD E143312
 IALAN DAMN SATU IANDA BAIK 28750 BENTONG, PAHANG
 DARUL MAKMUR MALAYSIA

Mtl Dsg	Mark Dsg	Coating Type		ANSI Typ	Temp Class
		BC	OC		
Estersol 160	E180	Polyesterimide (solderable)	—	MW-77	180
Amldester 200	A200	Polyesterimide	—	MW-74	200
Polysol-N 155	PN155	Polyurethane	Nylon	MW-80, MW-28	155, 100
Polysol 155	P155	Polyurethane	—	MW-79, MW-79	155, 130
Polysol 155g	Pg155	Polyurethane	—	MW-79	130
Polysol 155p	Pp155,Gp155	Polyurethane	—	MW-79	155
Polysol 160	P160	Polyurethane	—	MW-79	155
Polysol 180	P180	Polyurethane	—	MW-79	155
Polysol 170	P170 or G170	Polyurethane	—	MW-79	156
Polysol-N 180	PN180	Polyurethane	Nylon	—	180

Marking : Dompany name/nateriel designation or marked designation and factory identification on package ok reel

See General Information preceding These Recognitions
 For use only in equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.