

# RS501 THRU RS507

## SINGLE-PHASE SILICON BRIDGE RECTIFIER

VOLTAGE: 50-1000V

CURRENT: 5.0A


### FEATURES

- Ideal for printed circuit board
- Surge overload ratings-150 Amperes

### MECHANICAL DATA

- **Case:** plastic encapsulation
- **Epoxy:** UL 94V-0 rate flame retardant
- **Lead:** MIL-STD- 202E, Method 208 guaranteed
- **Polarity:** As marked
- **Mounting position:** Any
- **Weight:** 2.74 grams

### RS-5



Dimensions in inches and (millimeters)

### MAXIMUM RATINGS AND ELECTRONICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

	SYMBOL	RS501	RS502	RS503	RS504	RS505	RS506	RS507	units
Maximum Recurrent Peak Reverse Voltage	<b>V<sub>RRM</sub></b>	50	100	200	400	600	800	1000	<b>V</b>
Maximum RMS Bridge Input Voltage	<b>V<sub>RMS</sub></b>	46	88	140	280	420	560	700	<b>V</b>
Maximum DC Blocking Voltage	<b>V<sub>DC</sub></b>	50	100	200	400	600	800	1000	<b>V</b>
Maximum Average Forward rectified Output Current at T <sub>A</sub> =75°C	<b>I<sub>o</sub></b>								<b>A</b>
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	<b>I<sub>FSM</sub></b>								<b>A</b>
Maximum Forward Voltage Drop per element at 2.5A DC	<b>V<sub>F</sub></b>								<b>V</b>
Maximum DC Reverse Current at Rated DC Blocking Voltage per element	@ T <sub>A</sub> =25°C @ T <sub>A</sub> =100°C	<b>I<sub>R</sub></b>				10			<b>μA</b>
I <sup>2</sup> t Rating for Fusing (t<8.3ms)						500			
Typical Junction Capacitance (Note 1)	<b>C<sub>J</sub></b>					15			<b>pF</b>

Notes: 1. Measured at 1MHz and applied reverse voltage of 4.0 volts

2. Thermal Resistance from Junction to Ambient and from junction to lead mounted on P.C.B. with 0.47×0.47"(12×12mm) copper pads