



Recommended P.C.B. Layout
Layout Tolerance = ± 0.05 mm

- NOTE:
- MATERIAL,
HOUSING: HIGH TEMP PLASTIC, UL94-V0, BLACK
TERMINAL: COPPER ALLOY, SQ=0.40±0.03MM
 - FINISH:
TERMINAL: GOLD AT CONTACT,
G/F OVER 1um(40u")MIN Ni OVER ALL
 - SPEC.:
PRODUCT SPEC: GS-12-629
PACKING SPEC: GS-14-1420
 - THE HSG. WILL WITHSTAND EXPOSURE TO 260C PEAK TEMP. FOR 10 SEC. IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.
 - PRODUCT NUMBERING:
20021121 - 0 0 0 XX X X LF

LEAD FREE
PLATING:
1: GOLD FLASH ALL OVER
4: 0.25um(10u")GOLD AT CONTACT
8: 0.76um(30u")GOLD AT CONTACT
PACKING
D: TUBE+ CAP
T: TUBE
C: REEL+CAP(6,8,10,12,16,20P)
PIN COUNT
04,06,08, 12, 14,..., 98,A0
(4 - 100 EVERY EVEN PIN)

□ 0.10 FOR 4 to 40 POS.
□ 0.12 FOR 42 to 100 POS.

Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriete de c FCI. Droits de reproduction FCI.

All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.



mat'l. code				tolerances unless otherwise specified		CUSTOMER COPY	 www.fciconnect.com	
ltr	ecn no	dr	date	linear	.X ± 0.38	projection	title	
A	T09-1117	S.LIN	09/15/09		.XX ± 0.25		1.27X1.27MM BTB,HEADER	
B	T10-0013	S.LIN	01/22/10	angles	.XXX ± 0.10		UNSTROUDED, SMT	
					0° ±2°		product family 585	
				dr	STERLING LIN	09/15/09	MM	size
				engr	STERLING LIN	09/15/09		dwg no
				chr	GARY HSIEH	09/15/09	scale	A4
				appd	JOSEPH HSIA	09/15/09		
sheet index	revision sheet	B	1					code
								1 of 1