



Surface Mount Zener Diode

DL47 Series

RoHS Compliant Product

A suffix of "-C" specifies halogen & lead-free

1W, MELF

Type Number	Nominal Zener Voltage Vz at Iz*	Test Current IzT	Maximum Zener Impedance			Maximum Reverse Leakage Current		Surge Current IR At Ta=25	Maximum Regulator Current IzM
			ZzT at IzT	Zzk at IzK	IzK	IR	Test-Voltage Suffix B		
			Ω	Ω	mA	μA	Volts		
DL4728A	3.3	76	10	400	1.0	100	1.0	1380	276
DL4729A	3.6	69	10	400	1.0	100	1.0	1260	252
DL4730A	3.9	64	9	400	1.0	50	1.0	1170	234
DL4731A	4.3	58	9	400	1.0	10	1.0	1085	217
DL4732A	4.7	53	8	500	1.0	10	1.0	965	193
DL4733A	5.1	49	7	550	1.0	10	1.0	890	178
DL4734A	5.6	45	5	600	1.0	10	2.0	810	162
DL4735A	6.2	41	2	700	1.0	10	3.0	730	146
DL4736A	6.8	37	3.5	700	0.5	10	4.0	660	133
DL4737A	7.5	34	4	700	0.5	10	5.0	605	121
DL4738A	8.2	31	4.5	700	0.5	10	6.0	550	110
DL4739A	9.1	28	5	700	0.25	10	7.0	500	100
DL4740A	10	25	7	700	0.25	10	7.6	454	91
DL4741A	11	23	8	700	0.25	5	8.4	414	83
DL4742A	12	21	9	700	0.25	5	9.1	380	76
DL4743A	13	19	10	700	0.25	5	9.9	344	69
DL4744A	15	17	14	700	0.25	5	11.4	304	61
DL4745A	16	15.5	16	700	0.25	5	12.2	285	57
DL4746A	18	14	20	750	0.25	5	13.7	250	50
DL4747A	20	12.5	22	750	0.25	5	15.2	225	45
DL4748A	22	11.5	23	750	0.25	5	16.7	205	41
DL4749A	24	10.5	25	750	0.25	5	18.2	190	38
DL4750A	27	9.5	35	750	0.25	5	20.6	170	34
DL4751A	30	8.5	40	1000	0.25	5	22.8	150	30
DL4752A	33	7.5	45	1000	0.25	5	25.1	135	27
DL4753A	36	7.0	50	1000	0.25	5	27.4	125	25
DL4754A	39	6.5	60	1000	0.25	5	29.7	115	23
DL4755A	43	6.0	70	1500	0.25	5	32.7	110	22
DL4756A	47	5.5	80	1500	0.25	5	35.8	95	19
DL4757A	51	5.0	95	1500	0.25	5	38.8	90	18
DL4758A	56	4.5	110	2000	0.25	5	42.6	80	16
DL4759A	62	4.0	125	2000	0.25	5	47.1	70	14
DL4760A	68	3.7	150	2000	0.25	5	51.7	65	13
DL4761A	75	3.3	175	2000	0.25	5	56.0	60	12
DL4762A	82	3	200	3000	0.25	5	62.2	55	11
DL4763A	91	2.8	250	3000	0.25	5	69.2	50	10
DL4764A	100	2.5	300	3000	0.25	5	76.0	45	9

Standard Voltage Tolerance is ± 5 %

Measured with Pulses Tp = 40m Sec.

• Absolute Maximum Ratings

Characteristic	Symbol	Value	Unit
Zener Current see Table "Characteristics"			
Power Dissipation at Tamb=25	Ptot	1*	W
Junction Temperature	Tj	200	
Storage Temperature Range	Ts	-65 to +200	


*Valid provided that leads at a distance of 10mm from case are kept at ambient temperature.

• Characteristic at Tamb=25

	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction to Ambient Air	RθA	-	-	170*	K/mW
Forward Voltage At IF=200mA	VF	-	-	1.2	V

*Valid provided that leads at a distance of 10mm from case are kept at ambient temperature.

Breakdown Characteristics



Admissible power dissipation versus ambient temperature

Valid provided that leads are kept at ambient temperature at distance of 10 mm from case

