



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, Ca 90638
 Phone: (562) 404-4474 * Fax: (562) 404-1773
 ssdi@ssdi-power.com * www.ssdi-power.com

SDA676-12 thru SDA676-50

**0.125 to 0.400 AMPS, 1,200 to 5,000 VOLTS
 STANDARD RECOVERY
 SINGLE PHASE BRIDGE RECTIFIER**

Designer's Data Sheet

Part Number/Ordering Information^{1/}
SDA676 -

$\overline{\text{L}}$ Screening ^{2/} $\underline{\quad}$ = Not Screened
 TX = TX Level
 TXV = TXV
 S = S Level


Peak Inverse Voltage
 12 = 1,200V, 18 = 1,800V,
 24 = 2,400V, 30 = 3,000V
 36 = 3,600V, 42 = 4,200V
 48 = 4,800V, 50 = 5,000V.

- FEATURES:**
- Miniature High Voltage Bridges
 - 0.125 to 0.400 Amp Ratings
 - PIV 1,200 to 5,000 Volts
 - Reverse Recovery Time 500ns Maximum
 - Controlled Avalanche Characteristics
 - Available in Fast, Ultra Fast and Hyper Fast Versions
 - TX, TXV, and S-Level Screening Available
 - Superior Replacement for Unitrode 676 Series

ELECTRICAL CHARACTERISTICS^{3/}

Part Number	Peak Inverse Voltage (per leg)	Body Size	Reverse Recovery Time ^{4/}	Average DC Output Current T _C =Case Temp		Non-Repetitive Sinusoidal Surge (8.3ms)	Maximum Forward Voltage Drop (per leg)		Maximum Reverse Current (per leg) @ PIV	
				I _{F(AV)}	I _{FSM}		V _F	I _R		
Symbol	PIV		T _{rr}	I _{F(AV)}		I _{FSM}	V _F		I _R	
Units	kV		ns	Amps		Amps	Volts	Amps	μA	
Conditions			Max	Air 25°C	Oil 100°C		V _F	I _F	25°C	100°C
SDA676-12	1.2	J	500	0.400	1.000	30	3.3	0.50	5	150
SDA676-18	1.8	K	500	0.350	0.850	30	4.0	0.50	5	150
SDA676-24	2.4	L	500	0.325	0.800	20	5.5	0.50	5	150
SDA676-30	3.0	M	500	0.250	0.625	20	7.7	0.50	5	150
SDA676-36	3.6	N	500	0.175	0.425	20	8.8	0.40	5	150
SDA676-42	4.2	O	500	0.150	0.375	20	9.5	0.35	5	150
SDA676-48	4.8	P	500	0.135	0.325	20	10	0.30	5	150
SDA676-50	5.0	P	500	0.125	0.300	20	10	0.25	5	150

- NOTES:**
1. For Ordering Information, Price, Curves, and Availability - Contact Factory.
 2. Screened to MIL-PRF-19500.
 3. Unless Otherwise Specified, T_A = 25°C.
 4. Recovery Conditions:
 I_F = 10mA, I_R = 10mA, I_{RR} = 5mA



Body Size	J	K	L	M	N	O	P
LENGTH, MAX	0.562"	0.668"	0.875"	1.125"	1.250"	1.375"	1.625"

NOTE: All specifications are subject to change without notification. SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RA0076A

DOC