



### Features

- Frequency Range: 2.4~2.8GHz
- Standard Hermetic Package
- Operating Temperature Range: -55°C ~ +85°C


### Specifications (50 Ω, V<sub>CC</sub> = +12V, T<sub>A</sub> = -55°C ~ +85°C)

Parameter	Symbol	Unit	Guaranteed	Typical
Frequency Range	f <sub>L</sub> ~f <sub>H</sub>	GHz	2.4~2.8	---
Gain	G <sub>p</sub>	dB	≥22.0	24.0
Gain Flatness	ΔG <sub>p</sub>	dB	---	±0.5
Noise Figure	F <sub>n</sub>	dB	≤1.5Δ	1.2
Input VSWR	VSWR <sub>i</sub>	---	≤2.5:1Δ	1.8:1
Output VSWR	VSWR <sub>o</sub>	---	≤2.5:1Δ	1.6:1
Output Power @ 1dB Compression	P-1	dBm	≥10.0Δ	10.5
DC Current	I <sub>CC</sub>	mA	---	65


“Δ” T<sub>A</sub> = 24 ± 1°C;

### Maximum Rating

DC Voltage : +13.5VDC  
 RF Input: +10dBm  
 Storage Temp: +125°C




T0-8D



SMO-8D

### Application Notes

1. Typical application shown as right, C<sub>1</sub> = 10~33 μF ; C<sub>2</sub> = 3300~6800pF;
2. See assembly section for mounting information
3. Connectorized package(SMA-1) available
4. ESD observe handling precautions



### Typical Curves

