

## RJ Filter Multi-Port Jacks T1/E1

**EPJ9078-4** 


- Space saving RJ-45 Connectors •
- Available in shielded and unshielded packaging •

## Electrical Parameters @ 25° C

Turns Ratio (±5%)	OCL (µH Typ.)	<b>DCR</b> (Ω Max.)				CMRR ( dB Min. )					
Xmit/Rcv	10 KHz, 0.01V	P1-J1	P2-J2	P4-J4	P5-J5	1 Mhz	5 Mhz	20 Mhz	70 Mhz	200 Mhz	500 Mhz
1:1 / 1:1	65	0.5	0.5	0.5	0.5	-5	-15	-15	-20	-17	-6

## **Schematic**





## **Dimensions**

	(	(Inches)		(millimeters)			
Dim.	Min.	Max.	Nom.	Min.	Max.	Nom.	
Α			2.324			59.03	
В			.837			21.27	
С			.543			13.80	
D			.350			8.89	
E			.118			3.00	
F			.050			1.27	
G			.100			2.54	
Н	.018	.020	.019	.457	.508	.483	
- 1			.010			.254	
J			.350			8.89	
K			.429			10.89	
L			.550			13.97	
M			.180			4.57	
N			2.320			58.81	
Р			.100			2.54	
Q			2.100			53.34	
R			.063			.160	
S			.127			3.25	
Т			.035			.900	
U			.126			3.20	