

P-tec Corp. Tel:(800)688-0613
 2405 Commerce Circle Tel:(719) 589 3122
 Alamosa Co. 81101 Fax:(719) 589 3592
 www.p-tec.net sales@p-tec.net



PL0084 Series SMD LED PLCC-4 Package White

Features

- *PLCC-4 Package 3.2 x 2.7 x 1.9 mm
- *High Luminous Output
- *Very Wide Viewing Angle
- *For use as Optical Indicator, Backlighting
- *For Optical Coupling into Light Pipes/Lenses
- *2000 pc reels, 12mm Tape
- *Integrated Zener Diode for ESD protection
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation.....	120mW
Reverse Voltage (<100μA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Reflow Soldering Temperature.....	260°C for 5 seconds
Electric Static Discharge Threshold (HBM).....	6000V

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	CIE Chromacity Coordinates		View Angle	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
			X axis	Y axis	2θ ½	Typ	Max	Min	Typ
PL0084-WCW15Z	White	InGaN	0.31	0.30	120°	3.2	4.0	500	1030

Package Dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.

