

## Features

- Universal AC Input / Full Range
- Built-in active PFC function
- Short Circuit, overload, over voltage, over temperature protected
- Current Sharing (Available)
- Current Monitoring
- Power Good Signal
- Built-in Remote Inhibit
- Built-in Remote Sense
- Extended temperature range: -40 ~ +75 °C available



Model <sup>1</sup>	Preset Voltage	Output <sup>2, 3, 4</sup>	Output Current		Max. Power <sup>5, 6</sup>	Ripple & Noise <sup>7, 8</sup>	
			Minimum	Maximum		Regulation <sup>7</sup>	(Vpp)
VPF-S800-12R(I)-N	12V	12 - 14 V	0 A	62.5 A	750 W	+/- 1%	1%
VPF-S800-15R(I)-N	15V	15 - 19 V	0 A	50 A	750 W	+/- 1%	1%
VPF-S800-24R(I)-N	24V	20 - 26 V	0 A	40 A	800 W	+/- 1%	1%
VPF-S800-36R(I)-N	36V	27 - 36 V	0 A	29.63 A	800 W	+/- 1%	1%
VPF-S800-40R(I)-N	40V	37 - 47 V	0 A	21.62 A	800 W	+/- 1%	1%
VPF-S800-48R(I)-N	48V	48 - 60 V	0 A	16.67 A	800 W	+/- 1%	1%

## Notes:

- 1 Adding "I" Indicates Current sharing model.
- 2 Customer must specify output voltage.
- 3 Output is fully isolated.
- 4 Output voltage is measured at output power connector.
- 5 Provides peak power of 900 W within 500  $\mu$ S for all models. For longer duty duration please contact us.
- 6 Must use external forced airflow min. 30 CFM to achieve maximum power.
- 7 1% minimum load is required to maintain the ripple and regulation.
- 8 Ripple and noise is measured from 10 KHz to 20 MHz at output terminals with a 0.1  $\mu$ F ceramic capacitor and a 22  $\mu$ F electrolytic capacitor in parallel.



### Input

Parameter	Conditions/Description	Min	Nom	Max	Units
Input Frequency		47		63	Hz
Input Voltage		90		264	VAC
Input Current	At 90-264 VAC			12	A
Inrush Current	Peak measured at 230 VAC at full load, cold start			70	A
Power Factor	Active power factor correction meets EN61000-3-2 class D				

### Output

Parameter	Conditions/Description	Min	Nom	Max	Units
Transient response	Output voltage returns to within 1% in less than 2.5 mS for a 50% load change. Peak transient does not exceed 5%.				
Overshoot	Turn-on and turn-off overshoot shall not exceed 5% over nominal voltage.				
Efficiency	Measured at 230 V and full load 12 V model: 80% All other models: 83%				
Turn on delay	At 120 VAC			1	second
Hold up time	80% of rated maximum load	20			mS
Adjustability	Adjustable with built-in trim pot.	+/- 5%			
Remote sense	Designated as RS+ and RS- on the CN3. Total voltage compensation for cable losses with respect to the main output. (NOT available for current sharing models.)				
Remote Inhibit	Designated as RSW on the CN3. Requires a low signal to inhibit the output.				
LED display (LED 1)	Green - the power supply is operating normally. Orange - when any protection occurs or when Remote Inhibit is in effect.				
Power Good	Designated as PG on the CN3. This signal goes high 100-500 mS after the output reaches regulation. It goes low at least 1 mS before loss of regulation.				
Current Sharing	Designated as CSH on (CN3), use in parallel for forced current sharing function. Accuracy of shared current with up to 4 parallel units is within 10% at full load.				
Current Monitor	Designated as CMN on (CN3) for current sense purpose. CMN is a 0.5 to 3VDC output voltage to represent a linear 0% to 100% output current.				

### Protection Circuit

Parameter	Conditions/Description
Input Fuse	Built-in ac fuse. A blown fuse usually indicates permanent damage to the power supply serviceable by factory only.
Input under-voltage	Power supply shuts down when ac input is under 80 VAC. When ac line reappears over 86 +/- 5 VAC, the power supply restarts automatically.
Overload	Current limiting starts at 110-140% of the rated output current and recovers automatically.
Short circuit	Short circuit can be continuous. Recovers automatically upon removal of short.
Output Over-voltage	Output is protected against overvoltage. Unit shuts down and latches when voltage at output terminals exceeds 130%. AC input needs to be reset to restart the power supply.
Over temp.	Power supply shuts down when temperature is in excess of 85 °C. Auto recovery.

## General and Safety

Parameter	Conditions/Description	Min	Nom	Max	Units
Operating temp.	Derates linearly from 100% load at 50 °C to 50% load at 70 °C.	0		50	°C
Optional operating temp.	Derates linearly from 100% load at 50 °C to 37.5% load at 75 °C.	-40		75	°C
Storage temp.		-20		85	°C
Optional storage temp.		-40		85	°C
Operating humid.	Non-condensing	5%		90%	RH
Storage humid.	Non-condensing	5%		95%	RH
EMI	FCC Part 15, CISPR 22 class B, Conducted				
Safety	UL60950-1 (E222889), CSA C22.2 No. 60950-1-03, TUV EN60950-1, CE Mark(LVD) EN61000-3-2,3 & IEC61000-4 series regulations and CB.				
Leakage Current	at 240 VAC			3.5	mA
Isolation Voltage (HI-POT)	Applied for 3 seconds Primary to secondary: Primary to transformer core: Primary to earth ground:	3000			VAC VAC VAC
Grounding Test	Allowable resistance measured when 25 A current is applied from the ground pin of the three prong plug to the farthest earthed connection point.			0.1	Ohm
Warranty	Standard warranty length			2	years
MTBF	According to MIL-HDBK-217 at 30 °C	150,000			hours
Burn-in	Full load, at 45 +/- 5 °C, 230 VAC. Burn-in for up to 8 hours in early productions. Time reduced gradually as product matures.	1		8	hours

**Note:** Customer must specify extended temperature on PO.

## Mechanical

Parameter	Conditions/Description	Min	Nom	Max	Units
Weight				1450	grams
Enclosure	8.00(L) x 4.33(W) x 2.56(H)				inches
Mounting holes	Two sets of 8 threaded mounting holes available on the enclosure B: 6-32, maximum insertion depth of 0.2 inches. C: M4, maximum insertion depth of 0.2 inches.				

## Input Connector - (CN1)

Parameter	Conditions/Description
AC input (Option 1)	Molex Part No. 26-48-1201 or similar (5 pin). <b>Suggested mating plug: Molex Part No. 09-91-0500 or equivalent (5 pin, 3 used)</b>
AC Input (Option 2)	Howard Terminal block Part No. HD-121-3P (3 pin, M3 Screw) 9.5mm spacing <b>Suggested mating connector: Molex 19198-0045 or similar</b>

**Note:** Input connector needs to be specified on the PO.

### Output Connector - (CN2)

Parameter	Conditions/Description
Output (Option 1)	Molex Part No. 26-48-1201 or similar.(20 pin) Output pin assignment, VO+ (Pins 1-10), VO- (Pins 11-20) <b>Suggested mating connector:</b> Molex Part No. 09-91-2000, contact:08-50-0106 or similar.
Output (Option 2)	Howder Terminal block Part No. HD-121-8P (8 pin, M3.5 Screw) 9.5mm spacing Output pin assignment, VO+ (Pins 1-4), VO- (Pins 5-8) <b>Suggested mating connector:</b> Molex 19198-0045 or similar.

**Note:** Output connector needs to be specified on the PO.

### Logic Connector - (CN3)

Parameter	Conditions/Description
Logic	JS B7B-XH-A <b>Suggested mating connector:</b> JST XHP-7 or equivalent , Contact: SXH-001T-P0.6.
Pin Assignments:	<ol style="list-style-type: none"> <li>1. CMN - Current Monitoring</li> <li>2. CSH - Current Sharing</li> <li>3. RTN - Return / Output Ground</li> <li>4. PG - Power Good Signal</li> <li>5. RSW - (Remote On-Off / Remote Inhibit)</li> <li>6. RS(-) - Remote Sense</li> <li>7. RS(+) - Remote Sense</li> </ol>
Fan	JST B2B-XH-A <b>Suggested mating connector:</b> JST XHP-2 or equivalent, Contact: SXH-001T-P0.6.

