



15 Watt Universal 2-Wire Input Desktop Adapter PSAA15W Single Output Series Meets CEC and EISA Requirements



Features

- 0A Minimum Load
- Efficiency Level IV Compliance
- Class B EMI
- <0.25mA Leakage Current
- Compact Size

Applications

- Portable Equipment
- Peripherals and Terminals
- Low-power Computers
- Networking

Safety Approvals

- cUL/UL
- CE
- TUV
- Meeting Cal. Prop. 65

Mechanical Characteristics

- Length: 81.2mm (3.20in)
- Width: 50mm (1.97in)
- Height: 29.8mm (1.17in)
- Weight: 140g (4.94oz.)

Output Specifications

Model	DC Output Voltage	Load		Ripple (1) P-P (max.)	Regulation Line & Load	Efficiency Level
		Min.	Max.			
PSAA15W-050	+5V	0A	3.0A	70mV	±5%	IV
PSAA15W-120	+12V	0A	1.25A	120mV	±5%	IV
PSAA15W-180	+18V	0A	0.83A	180mV	±5%	IV
PSAA15W-240	+24V	0A	0.63A	240mV	±5%	IV
PSAA15W-480	+48V	0A	0.31A	480mV	±5%	IV

(1) Measured by using a 12 inch twisted pair terminated with a 10uF capacitor and 0.1uF ceramic in parallel.

Phihong is not responsible for any error and change. Content is subject to change without notice. Please consult the factory and visit www.phihong.com for the most up-to-date specifications.

INPUT:

AC Input Voltage Rating
100 to 240VAC

AC Input Voltage Range
90 to 264VAC

AC Input Frequency
47 to 63Hz

Input Current
0.5A (rms) max. @ 120VAC
0.25A (rms) max. @ 240VAC

Leakage Current
0.25mA max.

Inrush Current (cold)
30A for 120VAC at max. load
60A for 240VAC at max. load
(Cold start @ ambient 25°C)

Input Power Saving
0.5W maximum at no load

OUTPUT:

Efficiency
> 74% average efficiency

Hold-up Time
10mS min. @ 120VAC and max. load

Over Voltage Protection

By Zener clamping, adapter will be shut down

Over Current Protection

Output equipped with short circuit protection – auto restart

Short Circuit Protection

Output can be shorted without damage

ENVIRONMENTAL:

Temperature

Operation 0 to +40°C
Non-operation -25 to +75°C

Humidity

Operation 20 to 90%

Emissions

FCC Class B
EN55022 Class B

Dielectric Withstand (Hi-pot) Test

Primary to Secondary: 3000VAC for 1 minute, 10mA

DC Output Connector

2.1x5.5mm Center Positive Standard

Mating Connector

Kycon KLD-0202-A or equivalent

Dimension Diagram Unit: mm

